

**SETTLEMENT ANALYSIS OF EMBANKMENT GROUND IMPROVED
BY VERTICAL DRAINS AND SURCHARGE**

By

RITZAWATY HJ. MOHAMAD SHUKERI

Report is submitted as
the requirement for the degree of
Bachelor Engineering (Hons)(Civil)

**UNIVERSITI TEKNOLOGI MARA
MAY 2006**

ACKNOWLEDGMENTS

In the name of Allah, The Most Beneficent and The Most Merciful.

I am greatly indebted to Ir. Mohd. Farid Ahmad, a Final Year Project supervisor for providing me with invaluable information and guidance on this study and for providing me with his endless advices.

I would like to acknowledgment the help of Ir. Kim Har from Emas Kiara Marketing Sdn. Bhd. for explaining to me the manufacturing process and quality control test on PVD.

My appreciation is extended to Ir. R. Pogeswaran for giving me some settlement data and allowing me to have a visit at construction site.

I wish to acknowledge the aid, advice, and assistance received from the following individuals: Hazhar Maulan, Zulkiflee Mohamad Noor, and Shamsul Yusuf.

Last, but certainly not least, to my family; abah, mama, brothers, and sisters for their support, for their concern, and of course for their love to me while doing this study.

TABLE OF CONTENTS

	PAGE
DECLARATION	i
ACKNOWLEDGMENT	ii
TABLE OF CONTENT	iii
LIST OF FIGURES	vi
LIST OF TABLES	viii
ABBREVIATIONS	ix
ABSTRACT	x
CHAPTER	
1 INTRODUCTION	
1.1 Background	1
1.2 Problem Statement	3
1.3 Objectives	3
1.4 Scope of Work	4
1.5 Significance of Research	4
1.6 Research Methodology	5
2 LITERATURE REVIEW	
2.1 Introduction	7
2.2 Vertical Drains	8
2.3 Properties of Pvd	9
2.3.1 Discharge Capacity	11

ABSTRACT

The preloading with vertical drains offers an economically viable solution to improve the ground for lightly loaded industrial and housing development over areas of soft compressible deposits, which require deep foundations. Preloading can be carried out by earth or sand fill, water, vacuum or by lowering the ground water. There are wide ranges of prefabricated vertical drains available locally and many projects have been successfully completed using them. In this study, a review of the properties of the drains, their selection criteria, methods of installation, design considerations of the preloading with vertical drains, and settlement analysis using Asaoka Method was made. Then, the manufacturing and installation of vertical drain of a project site in Bandar Baharu were investigated. Finally, analyses were then conducted using Asaoka's and Hyperbolic Curve Method on settlement of embankments in Bandar Baharu, Juru, Kuala Sg. Baru, and Kerteh. Based on these studies it was found that at the end of consolidation, the higher period of interval i.e. 21 days, for monitoring will give similar estimate of total consolidation and degree of consolidation would be almost similar for the two techniques. Asaoka's Method would give higher estimate of degree of consolidation as compared to Hyperbolic Curve Method. As to the accuracy, Asaoka's Method gave the most accurate prediction of degree of consolidation. When the settlement values lie on 45° line, it will give the final consolidation settlement. As to Hyperbolic Curve Method, it is hard to find the final consolidation because of the fluctuating and it required some calculations to predict the ultimate settlement.

CHAPTER 1

INTRODUCTION

1.1 Background

Structures built on soil are subject to settlement. Some settlement is often unavoidable, and, in some circumstances, some settlement is acceptable. For example, settlement of a garage or warehouse building might be acceptable, but for settlement (especially differential settlement) of a luxury hotel building would not be because of damage to walls, ceilings, and so on.

Although there are several possible causes of settlement (e.g. dynamic forces, changes in the groundwater table, adjacent excavation, etc.), probably the major cause is compressive deformation of soil beneath a structure (Figure 1.1).



Figure 1.1: Settlement at pedestrian pavement.

Compressive deformation generally results from reduction in void volume, accompanied by rearrangement of soil particles, and compression of the