

**PROPERTIES OF WOOD RELATING TO STACKING AND DEFECTS OF
TIMBER IN KILN DRYING**

By

Mohd Junaidi bin Mohamad

**Final Project Paper Submitted in Partial Fulfilment for the Diploma in
Wood Industry, Faculty of Applied Science,
Universiti Teknologi MARA**

April 2001

ACKNOWLEDGEMENT

My special thanks to Allah S.W.T. for His blessing and strength rendered to me to complete my final project entitle “ Properties of Wood Relating to Stacking and Defects of Lumber in Kiln Drying” and also to my beloved friends for their support.

I would also like to offer my special thanks to my advisor, Associate Professor Abdul Jalil bin Ahmad, Associate Professor Dr. Jamaludin Kasim and Mr. Wan Nazri Wan Abdul Rahman for helping me at every phase of the study. Who are so generous in lending me helping hands and showing me the correct ways of performing my tasks.

I also would like to extend my appreciation to those who are involved either directly or indirectly in completing this project. I believed, without their helps, I would not be able to complete this final project.

TABLE OF CONTENTS

TITLE	PAGE
TITLE PROJECT.....	i
APPROVAL SHEET.....	ii
DEDICATION.....	iii
ACKNOWLEDGEMENT.....	iv
LIST OF PLATES.....	viii
ABSTRACT.....	ix
ABSTRAK.....	x
CHAPTER	
1 INTRODUCTION.....	1
1.1 Justification.....	1
1.2 Objective.....	1
2 BOTANICAL STRUCTURE OF WOOD.....	2
2.1 The Cambium.....	2
2.2 Sapwood.....	3
2.3 Heartwood.....	3
2.4 Grain.....	4
2.5 Fibres and Vessels.....	4
2.6 The Tangential.....	5
2.7 The Radial.....	5
3 DRYNESS AND MOISTURE CONTENT.....	6
3.1 Definition.....	7

3.2	Moisture Movement in Drying.....	7
3.3	Moisture Travel.....	8
3.4	Standard Method.....	9
4	STACKING THE TIMBER.....	10
4.1	Sorting.....	10
4.1.1	Sorting for Thickness.....	10
4.1.2	Sorting for Species.....	10
4.1.3	Sorting for Moisture Content.....	11
4.1.4	Sorting for Heartwood and Sapwood.....	12
4.1.5	Sorting for Grain.....	12
4.1.6	Sorting for Density.....	13
4.2	Sticker the Lumber.....	13
4.2.1	Sticker Material.....	13
4.2.2	Sticker Size.....	14
	4.2.2.1 Sticker Width.....	14
	4.2.2.2 Sticker Thickness.....	14
4.2.3	Sticker Location, Spacing, and Alignment.....	15
	4.2.3.1 Location of Stickers.....	15
	4.2.3.2 Spacing of Stickers.....	16
	4.2.3.3 Alignment of Stickers.....	17
4.3	Normal Stacking Procedure.....	17
4.4	Time of Stacking.....	18
5	AIR CIRCULATION.....	19
5.1	Natural Circulation Kilns.....	19
5.2	Forced Circulation Kilns.....	20

**PROPERTIES OF WOOD RELATING TO STACKING AND DEFECTS OF
TIMBER IN KILN DRYING**

By

MOHD JUNAIDI BIN MOHAMAD

April 2001

ABSTRACT

Wood must be dried before use. The methods in dry kiln are important. In stacking the timber, sticker in correct location will influence proper drying to produce good timber. The location of sticker that is not of uniform thickness and an unequally in stacking are causes to wood warping beside an unequal air circulation to the timber. The good air circulation in kiln influenced the rate of moisture content decrease without effected to the timber.