

**NATURAL WOOD DEFECT**

**NAME: MUHAMAD AMRAN B ABDUL WAHAB**

**FINAL PROJECT PAPER SUBMITTED IN PARTIAL FULFILLMENT  
FOR THE DIPLOMA IN WOOD INDUSTRY OF APPLIED SCIENCES,  
UNIVERSITI TECNOLOGY MARA**

**APRIL 2009**

## **ACKNOWLEDGE**

Firstly of all, I would like to take this opportunity to express my special thanks to Allah S.W.T for His blessing and strength rendered to me to complete this final year project entitle Natural Wood Defect. Added to my gratitude and thanks is to my advisor, Prof. Madya Abdul Jalil B Ahmad for becoming my advisor in this project paper and giving the support and advice from the beginning until the end of my research. For the spirit, support, and information to all my family, all staff at Al-Bukhari library, UiTM Jengka Pahang for the permission for loaning of book and giving help for the information searched. Lastly and not forgotten very grateful thanks to my fellow friend.

## TABLE OF CONTENT

| TITLE                 | PAGE |
|-----------------------|------|
| APPROVAL SHEET.....   | ii   |
| DEDICATION.....       | iii  |
| ACNOWLEDGE.....       | iv   |
| TABLE OF CONTENT..... | v    |
| LIST OF TABLE.....    | vii  |
| LIST OF FIGURES.....  | viii |
| ABSTRACT.....         | ix   |
| ABSTRAK.....          | x    |

| CHAPTER |                                   | PAGE |
|---------|-----------------------------------|------|
| 1.      | <b>INTRODUCTION</b>               | 1    |
|         | 1.1 OBJECTIVE                     | 2    |
| 2.      | <b>NATURAL WOOD DEFECT</b>        |      |
|         | 2.1 Decay, Rot or Unsound Wood    | 3    |
|         | 2.2 Knot                          | 3    |
|         | 2.3 Burl                          | 6    |
|         | 2.4 Shakes, Galls, Pitch Pockets  | 6    |
|         | 2.5 Timber Breaks                 | 10   |
|         | 2.6 Pitch                         | 10   |
|         | 2.7 Heart Stain And Sap Stain     | 11   |
|         | 2.8 Bark Pockets                  | 15   |
|         | 2.9 Reaction Wood                 | 16   |
|         | 2.10 Compression Wood             | 17   |
|         | 2.11 Frost Splits                 | 18   |
|         | 2.12 Cross Grain                  | 20   |
| 3.      | <b>OTHERS NATURAL WOOD DEFECT</b> |      |
|         | 3.1 Dead wood                     | 22   |
|         | 3.2 Cracks                        | 23   |
|         | 3.3 Weak Branch Unions            | 24   |
|         | 3.4 Decay                         | 25   |
|         | 3.5 Cankers                       | 26   |
|         | 3.6 Root Problems                 | 27   |
|         | 3.7 Insect Damage                 | 28   |
| 4.      | <b>DISCUSSION</b>                 | 30   |
|         | 4.1 conclusion                    | 30   |

## LIST OF FIGURE

| PLATE |                              | PAGE |
|-------|------------------------------|------|
| 1     | Decay, Rot or Unsound Wood   | 3    |
| 2     | Knot                         | 3    |
| 3     | Burl                         | 6    |
| 4     | Shakes, Galls, Pitch Pockets | 6    |
| 5     | Timber Breaks                | 9    |
| 6     | Pitch                        | 9    |
| 7     | Heart Stain And Sap Stain    | 10   |
| 8     | Bark Pockets                 | 14   |
| 9     | Reaction Wood                | 14   |
| 10    | Compression Wood             | 15   |
| 11    | Dead wood                    | 20   |
| 12    | Cracks                       | 21   |
| 13    | Weak Branch Unions           | 22   |
| 14    | Decay                        | 23   |
| 15    | Cankers                      | 24   |
| 16    | Root Problems                | 25   |
| 17    | Insect Damage                | 26   |

# **NATURAL WOOD DEFECT**

**BY  
MUHAMAD AMRAN B ABDUL WAHAB**

**APRIL 2009**

## **ABSTRACT**

Wood is a basic sources for producing product based on wood and yet used in daily used. Besides, good condition of wood will produces better quality product. At the same time, the wood defect will effect the manufacturer because uncontrolled defects on wood. Example of wood defects are defects by nature, defects during drying process and defects during machining process. The best way to reduce the defects on wood are during drying the wood by following the proper drying schedule and the worker have to handle the machine carefully. This is important to get the better quality wood product in the market industry.