THERMOPLASTIC COMPOSITE FROM ARA (FICUS SP.) WOOD DUST

By

Izwandy Bin Azizan

Final Project Submitted in Partial Fulfillment For The Diploma In Wood Industries,
Faculty Applied Science,
Universiti Teknologi MARA

MAC 2002

ACKNOWLEDGEMENT

Alhamdulillah, first of all, I like to take this opportunity to express my special thanks to Allah S.W.T. for His Blessing and Strength rendered to me to complete my final project successfully.

My special thanks to my beloved mother and father because of their pray for me always. I would like to offer my special thanks to my head program and as my project advisor, Prof. Madya Dr. Jamaludin Bin Kasim, because of his guide and lesson also helping me at every phase of study and completed my final project. He is so generous in lending me helping hands and showing me the correct ways of forming my tasks. I would like to express my most sincere thanks to him.

Beside that, special thanks too for all my beloved friends, because of their continuous support and helping me to complete this project paper. They always give me encourage to do the best in my study. Then, to Mr. Ismail as a lab assistant and all staff Faculty Applied Science, UiTM Shah Alam, because of their helps and guide when I was there to do my project.

Finally, I also give my appreciation to those who are involving either directly or indirectly in completing this project paper. I believe, without their helps and guide, I would not be able to completely finish this project successfully.

TABLE OF CONTENT

		Page
APPROVAL	SHEET	i
DEDICATIO	ON	ii
ACKNOWL	EDGEMENT	iv
LIST OF TA	ABLES	vii
LIST OF FIG	GURES	viii
LIST OF PL	ATES	ix
ABSTRACT		x
ABSTRAK		xi
CHAPTER		
1.0 INTRODUCTION		1
1.1	Objective	2
2.0 LITERATURE REVIEW		3
2.1	Physical Properties of Ara	3
2.2	Thermoplastic Composite	3
2.3	Polypropylene	4
2.4	Potential and Uses of Thermoplastic Composite	

3.0 MATERIAL AND METHOD	8
4.0 RESULTS AND DISCUSSION	20
5.0 CONCLUSION AND RECOMMENDATION	26
REFERENCES	27
APPENDIX	28
VITA	37

ABTRACT

THERMOPLASTIC COMPOSITE FROM ARA (FICUS SP.) WOOD DUST

By

IZWANDY BIN AZIZAN

MAC 2002

This is a research of producing thermoplastic composite from Ara (*Ficus sp.*) wood dust. Thermoplastic composite from Ara (*Ficus sp.*) is follwed from 10%, 20%, and 30% of wood dust. Tests such as bending, tensile, thickness swelling and water absorption are carried out. The results showed that 10% of composite is most suitable. This is because from bending test showed that composite is very strength compare to the other percentage. By using more Polypropylene (PP) can give chance to the wood dust bounded each other with PP. The results of thickness swelling and water absorption showed that the water could absorb into 10% lower than the other percentage. Generally, using 10% of wood dust is the most suitable quantity to mix with PP for making the best thermoplastic composite from Ara (*Ficus sp.*).