# FACULTY OF ELECTRICAL ENGINEERING UNIVERSITY TEKNOLOGI MARA PULAU PINANG

#### **FINAL REPORT:**

FIRE AND GAS DETECTION WITH GSM ALERT

MUHAMMAD AZRI ASYRAF BIN MOHD HAFEZ

**MUHAMMAD NAFIS BIN HAMDAN** 

SUPERVISOR:
PUAN ROHAIZA BINTI BAHARUDIN

### This report is submitted to the Faculty of Electrical Engineering,

Universiti Teknologi MARA (UiTM).

In partial fulfilment of the requirement for the award of Diploma in Electrical Engineering.

Supervisor's name (PUAN ROHAIZA BINTI BAHARUDIN) Date: 6/10/ユロル	This report is approved by:
	(PUAN ROHAIZA BINTI BAHARUDIN)

#### **ABSTRACT**

Dangerous gas leakage as well as fire had caused wide damage to industries and residential area in the past. It is also can danger human's life. It is very important to detect a gas leak or fire as soon as it breaks out so that it can be prevented from spreading instantly. Thus, this project propose a system that detects gas leakage as well as fire with GSM alert to aid early detection of fire and gas leakage before its spread wildly. This research is to develop and demonstrate the fire and gas detection prototype for home application with GSM alert system. To build this project, it use hardware components and the software for build the program. This project use the microcontroller PIC 16F877A as a brain for this project. This project use two sensors which are temperature sensor (LM35) to detect fire and gas sensor (MQ5) to detect any gas leaked. This project also use GSM Modem as a component to transmit the message to the user to warn them if the building is in a warning situation. For the output, this project use LCD to display the current condition, it also use buzzer to trigger the alarm and it will indicates the current warning using light indicator. The Fire and Gas Detection with GSM Alert procedure was successfully designed and simulate. The simulation shown that the temperature and gas sensor can detect any gas reading more than 2000 ppm or any temperature reading that more than 40°C. Then, it will display the warning via the LCD. At the same time, the LED-RED will turn on to indicate the reading of gas or temperature is in danger. Then, it will trigger the alarm via the speaker. Lastly, the PIC16F877A will transmit the message to the user by using GSM model.

#### **ACKNOWLEDGEMENT**

In the name of Allah, the most compassionate, the most merciful. Alhamdulillah, we have finally completed our final year project. To be honest, none of us thought that we can't finish this job on time but apparently we did it and thanks to Allah SWT for giving us the strength and the will to complete this final year project.

During the whole period of preparing this project, we went through a lot of tough times we must face the hardship to finish this project. We believe without one person that has been guiding us throughout this project, we can't finish this task successfully. We are deeply indebted to our lecturer, Madam Rohaiza Baharuddin, who always helps us improving and give an idea in term of report and the project progress. Without her as our supervisor from FYP 1 until FYP 2, this whole project will not finish on time and our report is not organized and systematically.

Furthermore, our special thanks towards our senior, Mr. Shamim who is sacrifice his time and his energy to thought us a lot of knowledge from the beginning of this project until this project completed. Next, we also wants to thank to our parents for providing a financial and support morale towards both of us. We also want to thanks and appreciate each other for the cooperation and the teamwork were given by both of us towards this task.

Lastly, I offer my regards and blessings to my friends and all of those who supported us in any aspect during the completion of the project.

## **TABLE OF CONTENTS**

ACKNO	DWLEDGEMENTS	i
ABSTRA	ACT	ii
LIST OF	F FIGURES	3
LIST OF	F TABLES	5
LIST OF	F ABBREVIATIONS	6
CHAPT	ER 1	7
INTROI	DUCTION	7
1.1	Background of Study	7
1.2	Problem Statement	9
1.3	Objectives of Research	9
1.4	Scope of Study	10
CHAPT	ER 2	11
MATER	RIALS AND METHODS	11
2.1 Me	ethodology	11
2.1.	1 FYP Flow Chart	11
2.1.	2 Project Flow Chart	13
2.1.	3 Block Diagram	15
2.1.	4 Algorithm	17
2.2 Ex	xperimental Setup	18
2.2.	1 Simulation	18
2.2.	2 Hardware	19
2.3 Eq	quipment and Component	20
2.3.	1 Microcontroller (PIC 16F877A)	21
2.3.	2 Temperature Sensor (LM35)	22
2.3.	3 Gas Sensor (MQ-5)	23
2.3.	4 GSM Modem	24
CHAPT	ER 3	25
CIRCUI	IT DESIGN AND OPERATIONS	25
3.1 Sc	hematic Diagram	25
3.1.	1 Software Development	25