

**UNIVERSITI TEKNOLOGI MARA**

**THE OPTIMIZATION AND  
CHARACTERIZATION OF TITANIUM  
DIOXIDE NANOSTRUCTURES  
COATED GLASS SURFACE  
PROPERTIES FOR SELF-CLEANING  
AND ANTI-BACTERIAL  
APPLICATIONS**

**MOHD FAIZAL BIN ACHOI**

Thesis submitted in fulfillment  
of the requirements for the degree of  
**Master of Science**

**Faculty of Applied Sciences**

July 2013

## **AUTHOR'S DECLARATION**

I declare that the work in this thesis was carried out in accordance with the regulations of Universiti Teknologi MARA. It is original and is the result of my work, unless otherwise indicated or acknowledged as referenced work. This thesis has not been submitted to any other academic institution or non-academic institution for any other degree or qualification.

I, hereby, acknowledge that I have been supplied with the Academic Rules and Regulations for Post Graduate, Universiti Teknologi MARA, regulating the conduct of my study and research.

Name of Student : Mohd Faizal Bin Achoi

Student ID No. : 2009908009

Programme : Master of Science

Faculty : Faculty of Applied Sciences

Thesis Title : The Optimization and Characterization of Titanium  
Dioxide Nanostructures Coated Glass Surface Properties  
for Self-cleaning and Anti-bacterial Applications

Signature of Student :

Date : July 2013

## ABSTRACT

The preparation of TiDoNs was successfully prepared on the glass surface using two phases process; Phase I process is sol-gel spin-coating technique while Phase II process is new invented technique, heat sol-dispersions immersion technique. The TiDoNs coated glass surface was optimized with four different parameters in Phase I process which affects precursor molar concentration, spinning rate, annealing temperature and multilayer TiDoNs while in Phase II process affects growth temperature. An optimum sample of TiDoNs was optimized shows that the surface morphology is random distribution and uniform shape with growth of small TiDoNs thorn-like structures at 100°C. The height of TiDoNs thorn is 17.5 nm and mean of particle size is 9.46 nm. It has 0.316 nm and 2.631 nm of roughness and thickness, respectively whereas, the optical properties shows that TiDoNs has transmittance at 84.03% attributed for absorption coefficients and optical band gap energy is about 25.25  $\alpha$  and 3.60 eV, respectively. An optimum sample of TiDoNs was then characterized for self-cleaning (SC) and anti-bacterial (AB) applications. For application I, the results of self-cleaning application characterized using contact analyzer (CA) shows that the working efficiency and performance of hydrophilic TiDoNs coated glass surface was drastically decreased from 68.12° to 0.35° of contact angle after 2.30 minutes. For application II, the results of anti-bacterial testing indicated that after 24 hours, an *Escherichia coli* (E. Coli ATTC 25922) species bacterial was not seen growth at the middle of TiDoNs coated glass surface but it grew away from the coated area. After 40 hours, the bacterial species was found to be dead.

## ACKNOWLEDGEMENTS

In the name of Allah s.w.t., the Most Gracious and the Most Merciful. Alhamdulillah, may all my work is blessed and the knowledge about this research and all the matters related to it can be used in the future. I would like to express my special appreciation to my research supervisor Prof. Dr. Saifollah Abdullah for his advice, encouragement and guidance throughout the research. I also wish to acknowledge my co-supervisor Prof. Dr. Mohamad Rusop Mahmood for always giving me idea, support and motivation throughout my research.

Many thanks to my colleagues and student of NANO-SciTech Centre (NST) and NANO-Electronics Centre (NET), particularly Dr. Zuraida Khusaimi, Dr. Hafiz Mamat, Dr. Suriani Abu Bakar, Madam Asiah Mohd Nor, Mr. Shamsul Faez, Mr. Mohd Firdaus Bin Malek, Mr. Musa Mohamed Zahidi and others for their help, motivation, kindness, and support during my studies. I also would like to thank Universiti Teknologi MARA (UiTM) and Ministry of Higher Education (MOHE) for the scholarship and financial support.

I gratefully acknowledge NANO-SciTech Centre (NST) and NANO-Electronics Centre (NET) staffs, Madam Nurul Wahida Bte Abdul Aziz, Mr. Azlan Jaafar, Mr. Salifairus, Mr. Suhaimi, Mr. Azwan, Mr. Shahril and Mr. Danial for their assistance in the lab. I also wish to acknowledge Mr. Mohd Faizal Bin Othman and Mr. Shahrill for anti-bacterial testing at medicine multipurpose laboratory.

Finally, I would like to express my deepest thanks to my mother, , my father, Achoi Bin Csin Kintai, my younger brothers, Mohd Faizarazi, Rafizee, Aszroy and my youngest sister, Bibie Nazira and Nor Sakinah for their love, encouragement, understanding, and support during my entire research period.

# CHAPTER ONE

## INTRODUCTION

### 1.1 INTRODUCTION

Titanium dioxide ( $\text{TiO}_2$ ) was discovered in 1918. It has been employed in research into various applications. Since 1959, the discovery of the nanometer scale materials has become a favourable research to scientists all over the world. It is due to many advantages such as has high surface area per volume ratio and specific surface area [1, 2], the ability to function at lower level dimension and have novel properties towards solar cell, anti-reflective coating, water purification and others applications. The first man who discovered the nanotechnology is Nobel Laureates Richard P. Feynman the receiver of Nobel Prize in 1959 [3]. At National Nanotechnology Initiative (NNI), according to the Richard Booker et. al., (2005) the nanotechnology is defined as the research and development technology of the materials in the range between 1 to 100 nm [4]. Due to that, the nanomaterial has been utilized and created towards their small size with various methods. These structures have novel properties and can be manipulated at the atomic level [4]. Afterwards, the nanotechnology continuously experience the era of evolution due to high demand from worldwide market to fulfill all aspects of applications. Among the fields that have experienced a large evolution are biotechnology, automotive industry, medicine, pharmaceutical, engineering manufacturing, energy and electrical, health, safety and security, and others. These fields have been using three dimensions of  $\text{TiO}_2$  nanomaterial to fulfill the present demand. Based on nanometer scale materials, one dimension nanomaterial is nanocoating while two dimension is nanowires and nanotubes, three dimension is nanoparticles[5].

An example of a well-known and most favourable material in the nanomaterial research is titanium dioxide ( $\text{TiO}_2$ ). It is due to its unique structural properties; existence in three phases is anatase [6], rutile [7] and brookite [8]. These properties have made  $\text{TiO}_2$  most prominent and are widely useful in many applications. Among the three