

UNIVERSITI TEKNOLOGI MARA

**SEISMIC PERFORMANCE OF
FULL-SCALE PRECAST NON-
SEISMIC BEAM-COLUMN JOINTS
WITH CORBELS UNDER IN-PLANE
LATERAL CYCLIC LOADING**

KAY DORA BINTIABD GHANI

Thesis submitted in fulfillment
of the requirements for the degree of
Doctor of Philosophy

Faculty of Civil Engineering

January 2015

ABSTRACT

Precast concrete building had been widely used in Malaysia for the public amenities such as residential housings, shopping complexes, hospitals, and school buildings. Moreover, most of the precast concrete buildings in Malaysia were designed in accordance to British Standard (BS8110) which has no specific detailing design of joint for precast elements under seismic loading. Thus, this study aims to evaluate the behavior of non-seismic designed precast buildings when subjected to long-distant earthquakes from Sumatera and near-field earthquakes. Three sub-assemblages of the specimens consisting of corner, interior and exterior of precast beam-column joints, were designed, constructed and tested under reversible in-plane lateral cyclic loading. These sub-assemblages were representing the main joints in the prototype precast two-storey school building. Direct Displacement-Based Design (DDBD) approach was utilized in developing load versus displacement curve (hysteresis loops) for all three sub-assemblages studied. Subsequently, the exterior beam-column joint was retrofitted using Carbon Fiber Reinforced Polymer (CFRP) wrapping and steel plate bonding. Ruaumoko Programming was utilized in modeling the inelastic behavior of the joints and overall structural deformation of the school building. The hysteresis loops of the precast beam-column joints were modeled using Hysteres program. The behavior of prototype school building was analyzed using Ruaumoko 2D and the mode shapes of the structural failure were illustrated by using Dynaplot program. In addition, a seismic assessment under Performance Based Earthquake Engineering (PBEE) was carried out using the fragility curve based on the Design Basis Earthquake (DBE), Maximum Considered Earthquake (MCE) and four past earthquake records. Finally, the capacity-demand response spectrum of the prototype two-storey precast school building was developed. Experimental results have demonstrated that the corner joint with corbel suffered severe damage when tested up to $\pm 1.35\%$ drift. Large gap opening between precast beam and column were also observed during experimental work. Nonetheless, the interior beam-column joints were tested up to $\pm 1.15\%$ drift and exterior precast beam-column joints were tested up to $\pm 1.0\%$ drift and suffered moderate damage called as captive column, due to strong beam-weak column design. Major crack at the cast-in-place (monolithic) area near the beam-column joint were also observed for all specimens. The retrofitted precast beam-column exterior specimen was tested up to $\pm 1.75\%$ drift and exhibited approximately 9.7% increment in lateral loading capacity as compared to the specimen before retrofitting work. Finally, a guideline of repair and strengthening of beam-column joints has been proposed for the damage structures so that it is easier for designer to apply the retrofitting procedures to the damaged elements after earthquake. From the capacity-demand response spectrum analysis, it can be concluded that the precast beam-column joints would not survive when subjected to earthquake excitation with surface-wave magnitude, M_w , more than 5.5 Scale Richter (Type 1 of spectra) which means that the beam-column joint which is designed by using BS8110 would severely damage when subjected to strong earthquake excitation. Therefore, this study help in enhancing the understanding of the behavior of non-seismically designed beam-column joints under earthquake loadings.

ACKNOWLEDGEMENT

In The Name of Allah, The Most Beneficent and The Most Merciful. Thank you Allah for giving me the chances, blessings and the strength to complete my PhD work and this thesis. A special thank you goes to Universiti Teknologi MARA (UiTM) and also to the Ministry of Higher Education for funding and supporting the research work.

I wish to express my deep gratitude to my supervisor, Associate Professor Dr. Nor Hayati Abdul Hamid@Zulkurnail for giving me this opportunity, believing in me and polishing my aptitude. Also I thank her for the guidance, direction and encouragement throughout this research. She was not only my research advisor but also a counselor in my life. The knowledge and experience that I have gained will forever be valuable and appreciated. Not forgotten, my sincere appreciation to my co-supervisor Professor Ir. Dr. Siti Hawa^ Hamzah for her support and encouragement that have contributed to the success of this research work. Nevertheless, I also want to express my gratitude to the technicians of Heavy Structures Laboratory of Faculty of Civil Engineering, UiTM Shah Alam, for their great commitment toward this research work. Also thanks to the office staffs of Faculty of Civil Engineering, UiTM Shah Alam for their co-operations. Special thanks goes to all seniors and friends which I cannot forget their help, advice and encouragement.

Last but not least, my heartfelt appreciation and very special thanks to my mother for her prayer, patience, inspiration and her love throughout my life. To my dear late father, thank you for the love, encouragement and support during the early stage of my study. Very special thanks to my husband for his love, care and inspiring words. To my son, thank you for being the apple of my heart, mama loves you so much. Finally, thanks to all family members and to those who indirectly contributed in this research work, your cooperation and prayers means a lot to me. Thank you very much.

TABLE OF CONTENTS

	Page
CONFIRMATION BY PANEL OF EXAMINERS	ii
AUTHOR'S DECLARATION	iii
ABSTRACT	iv
ACKNOWLEDGEMENT	v
TABLE OF CONTENTS	vi
LIST OF TABLES	xiii
LIST OF FIGURES	xviii
LIST OF SYMBOLS	xxvii
LIST OF ABBREVIATIONS	xxxix

CHAPTER ONE: INTRODUCTION

1.1	Background of study	1
1.2	Problem Statement	13
1.3	Objectives of the Study	15
1.4	Scope of the Study	16
1.5	Significance of the Study	18
1.6	Outline of Thesis	18

CHAPTER TWO: LITERATURE REVIEW

2.1	Introduction	20
2.2	Earthquakes Terminology and Tectonic Plate	21
2.2.1	Earthquakes and Setting of Tectonic Plates	21
2.2.2	Low-Seismic Region in Malaysia	24
2.3	Long-distance Earthquakes and Seismic Hazard Map of Malaysia	25
2.3.1	Earthquakes Around and in Malaysia	25
2.3.2	Sleeping and Active Faultlines in Malaysia	28
2.3.3	Seismic Hazard Map for Malaysia	32

2.4	Previous Research Findings for Beam-Column Joints of Precast Concrete Structures	34
2.5	Previous Research Findings on the Retrofitting of a Precast Beam-Column Joint	41
2.6	Theoretical Background of the Study	44
2.6.1	Moment-Curvature Relationship for Unconfined Section	44
2.6.2	Direct Displacement-Based Design (DDBD)	49
2.6.3	Monolithic Beam Analogy	53
2.7	Parameters used for Analysis	67
2.7.1	Stiffness	67
2.7.2	Yield Displacement	68
2.7.3	Displacement Ductility (μ_A)	69
2.7.4	Equivalent Viscous Damping	70
2.8	Modeling using the Ruaumoko Program	72
2.9	Performance-Based Seismic Assessment	75
2.9.1	Fragility Curve	77
2.9.2	Theoretical Development of a Fragility Curve	79
2.9.3	Demand Response Spectrum using Eurocode 8	82
2.9.4	Capacity Spectrum Design Method	84
2.10	Gap in the Research	85

CHAPTER THREE: RESEARCH METHODOLOGY

3.1	Introduction	87
3.2	Research Framework	88
3.3	Select and Design the Prototype Building	90
3.3.1	Details of the Prototype Structure and Selected Specimens	90
3.3.2	Design of the Specimens	92
3.4	Material Properties	100
3.4.1	Concrete	100
3.4.2	Reinforcement Bar	106
3.4.3	Formwork	109
3.4.4	Grout	110