

UNIVERSITI TEKNOLOGI MARA

**A STUDY ON THE BALLISTIC
IMPACT PERFORMANCE OF NEAT
AND NATURAL RUBBER LATEX-
COATED UNIDIRECTIONAL (NON-
WOVEN) HIGH STRENGTH FABRICS**

NORMALA BINTI HASSIM

Thesis submitted in fulfillment
of the requirements for the degree of
Doctor of Philosophy

Faculty of Applied Sciences

May 2015

CONFIRMATION BY PANEL OF EXAMINERS

I certify that a panel of examiners has met on 16th March 2015 to conduct the final examination of Normala Binti Hassim on her Doctor of Philosophy thesis entitled “A Study on the Ballistic Impact Performance of Neat and Natural Rubber Latex-Coated Unidirectional (Non-woven) High Strength Fabrics” in accordance with Universiti Teknologi MARA Act 1976 (Akta 173). The Panel of Examiners recommends that the student be awarded the relevant degree. The panel of Examiners was as follows:

Ahmad Bin Saat, PhD
Associate Professor
Faculty of Applied Sciences
Universiti Teknologi MARA
(Chairman)

Valliyappan David A/L Natarajan, PhD
Faculty of Mechanical Engineering
Universiti Teknologi MARA
(Internal Examiner)

Ahmad Mujahid Bin Ahmad Zaidi, PhD
Professor
Department of Mechanical Engineering
Universiti Pertahanan Nasional Malaysia (UPNM)
(External Examiner)

Rajiv Padhye, PhD
Associate Professor
Centre for Advanced Materials and Performance Textiles
School of Fashion and Textiles
College of Design and Social Context, RMIT University
25 Dawson Street, Brunswick, Victoria 3056 Australia
(External Examiner)

SITI HALIJJAH SHARIFF, PhD
Associate Professor
Dean
Institute of Graduate Studies
Universiti Teknologi MARA
Date: 24th July 2015

AUTHOR'S DECLARATION

I declare that the work in this thesis/dissertation was carried out in accordance with the regulations of Universiti Teknologi MARA. It is original and is the result of my own work, unless otherwise indicated or acknowledged as referenced work. This thesis has not been submitted to any other academic institution or non-academic institution for any degree or qualification.

I, hereby, acknowledge that I have been supplied with the Academic Rules and Regulations for Post Graduate, Universiti Teknologi MARA, regulating the conduct of my study and research.

Name of Student	: Normala Binti Hassim
Student I.D. No.	: 2009562635
Programme	: Doctor of Philosophy
Faculty	: Applied Sciences
Thesis Title	: A Study on the Ballistic Impact Performance of Neat and Natural Rubber Latex-Coated Unidirectional (Non- woven) High Strength Fabrics

Signature of Student

: 

Date

: July 2015

ABSTRACT

This research explores the application of natural rubber (NR) latex as a thin coating matrix on unidirectional (UD) fabrics for ballistic impact applications. Pre-vulcanised NR lattices were used to coat ballistic fabrics mainly by the single dip method and half dip method. It was found that NR latex changes the frictional aspects among the fibers attached with thin polyethylene film in the coated fabrics. The NR latex film was able to bind the polyethylene film, restrict mobility and share in resisting load applied to the fabric. In particular, an increase in friction was evident from the higher tensile, tearing and puncture resistance of the NR latex coated fabrics in comparison with neat fabrics. In the ballistic impact tests, utilizing several NR latex-coated fabrics in a fabric system increases the ballistic limit as high as 65% in comparisons with all-neat fabric system. The single dip coating technique gave higher ballistic limit value than the all-neat and other types of coating technique which was fired by Full Metal Jacketed Round Nose bullet. Somehow, the half dip coating method has the potential for ballistic applications because of the slight increase in the ballistic limit of a 12-layer fabric system. In subsequent tests, as high 23% in blunt trauma reduction was achieved using 4 NR latex-coated layers in the fabric system. The main deformation modes were small deflection or ballistic punch and peeling off of the NR latex film at the impact point. Neat fabrics failed mainly through broken fibers, fiber delamination, fiber pull out and fiber stretching. Calcium carbonate dispersion as a filler in the NR latex compounding also contributed in increasing the ballistic limit of the fabric systems. However, when compared with the unfilled NR latex-coated fabrics, the filler did not show to give any significant differences. As a conclusion, it can be said that the NR latex-coated fabrics were effective in absorbing the impact energy and reducing blunt trauma and has the potential to be used as blunt trauma panel and positioned at the rear of a body armour fabric system.

TABLE OF CONTENTS

	Page
CONFIRMATION BY PANEL OF EXAMINERS	ii
AUTHOR'S DECLARATION	iii
ABSTRACT	iv
ACKNOWLEDGEMENTS	v
TABLE OF CONTENTS	vi
LIST OF TABLES	x
LIST OF FIGURES	xi
LIST OF PLATES	xv
LIST OF ABBREVIATIONS	xviii
 CHAPTER ONE: INTRODUCTION	
1.1 Motivation	3
1.2 Objectives of Research	5
1.3 Reaching the Objectives	5
 CHAPTER TWO: LITERATURE REVIEW	
2.1 Introduction of Body Armour	7
2.2 Materials used in Ballistic Protection	12
2.2.1 Nylon	12
2.2.2 Aramids	13
2.2.3 Ultra High Molecular Weight Polyethylene (UHMWPE)	15
2.2.3.1 Production of UHMWPE Fiber	15
2.2.3.2 Properties of UHMWPE Fiber	16
2.2.4 Polybenzobisoxazole (PBO)	20
2.2.5 Polypyridobisimidazole	21
2.3 Main Factors Influencing Ballistic Impact Resistance	22
2.3.1 Material Properties	22