

BARELOR OF SPECIE (HARA) FEVELS FROM TO FROM SPECIES CONTRACTOR FROM SPECIES

POLYMER ELECTROLYTES BASED ON PVC - PEMA BLEND

SITI SUMAIYAH BINTI SHEIKH ABDUL AZIZ

×.

Final Year Project Report Submitted in Partial Fulfillment of the Requirements for the Degree of Bachelor of Science (Hons.) Physics in the Faculty of Applied Science University Teknologi MARA

MAY 2009

ACKNOWLEDGEMENTS

Alhamdulillah, I am highly grateful to Allah S.W.T for giving the permission, to complete this thesis entitled '**Polymer electrolytes based on PVC-PEMA blend**' which has been successfully submitted as planned.

ž.

Firstly I would like to express special thanks to my supervisors, Assoc. Prof .Dr Ri Hanum Yahaya Subban and Assoc.Prof. Dr. Nor Sabirin Mohamad, who have given their trust and confidence in me in doing this thesis and who also gave me encouragement in order to finish it. I also would like to express my appreciation and thanks especially to my friends and my family who gave me continuous support and encouragement. Thank you.

TABLE OF CONTENTS

		Page
ACI	KNOWLEDGEMENTS	iii
TAF	BLE OF CONTENTS	iv
LIS LIS ABS	F OF TABLES F OF FIGURES F OF ABBREVIATIONS STRACT STRAK	vi vii viii ix x
CHA	APTER 1: INTRODUCTION	
1.0 1.1 1.2 1.3 1.4	Introduction Problem Statement Objective Scope of Works Aim of Present Work	1 2 2 3 3
CHA	APTER 2: LITERATURE REVIEW	ŷ
2.0	Introduction	4
2.1	Polymer Electrolyte 2.1.1 Classification of polymer electrolytes 2.1.2 Plasticization 2.1.3 Review on polymer electrolytes	4 5 9 10
2.2 2.3	Polyvinyl chloride (PVC) as polymer host 2.2.1 Properties of Polyvinyl chloride (PVC) 2.2.2 Properties of Poly ethyl methacrylate (PEMA) Ethylene carbonates (EC)	11 13 15 16
	•	

CHAPTER 3: METHODOLOGY

3.0	Sample preparation	17
3.1	Impedance spectroscopy	20

ABSTRACT

In this work, polymer electrolytes composed of the blend of Poly (vinyl chloride) (PVC)/ poly (ethyl methacrylate) (PEMA) + LiCF_3SO_3 + EC was prepared where Polyvinyl chloride (PVC-PEMA) was used as the polymer host with Lithium triflate (LiCF_3SO_3) as the doping salt and ethylene carbonate (EC) as the plasticizer to prepare plasticized/gel solid polymer electrolyte films. The ionic conductivity of all these samples were measured by impedance spectroscopy. The optimum percentage of EC that could enhance the conductivity of the salted samples was determined.

÷.