



**FINITE ELEMENT ANALYSIS OF BIOSCREW FIXATION IN ACL
RECONSTRUCTION**

AHMAD ZAINALABIDIN ZOLKEPLI
(2006689277)

A thesis submitted in partial fulfillment of the requirement for the award of Bachelor
Engineering (Hons.) (Mechanical)

Faculty of Mechanical Engineering
Universiti Teknologi MARA (UiTM)

MAY 2010

ACKNOWLEDGEMENT

With the name of Allah s.w.t, the most gracious who given me the strength to complete this project.

Firstly, I would like to express my sincere gratitude and appreciation to my supervisor, Mr. Abdul Halim Abdullah for the continuous support, generous guidance, help, patience, and encouragement in the duration of thesis preparation until its completion and not to forget the entire technician that had involve in this project.

I would also like to express my gratitude to my family who had given support direct or indirectly in the completion of this project.

Last but not least, I would like to thank all my friends who had given me support, share information, and guidance during this project completion.

ABSTRACT

Bio-screw is an interference screw used in Anterior Cruciate Ligament (ACL) reconstruction. ACL reconstruction is a process of replacing the broken ACL with a graft made from soft tissue from the other parts of human body. The screw is used to fix the graft in the tunnel. Bio-screw is a screw made from bio-absorbable material that is Poly-L Lactide Acid (PLLA). It replace the use of metal interference screw for its bio-absorbable properties and the strength it posses. However, its capability to fix the graft to the femoral tunnel is questioned by the clinical. Thus, experimental study had been done to answer it. In this project, the mechanical behavior of samples of screws with different diameters and lengths in the bone tunnel with respect to the ACL reconstruction is studied. In spite using experimental study, finite element modeling is used to study the behavior. The distal femur and the bio-screw is remodeled using computer aided design (CAD) software and the stress distribution between the screw and the bone tunnel is obtained using the finite element software. In this project, a tensile force of 200 N is used as the loading conditions because it is the approximation of the graft tension at full extension of the knee during gait. It is found that the maximum Von Mises stress occurs on the tunnel is 29 MPa which is far away from the bone's yield strength that is 182 MPa. The maximum Von Mises stress occurs on the screw is 15.5 MPa which is also far from the screw's yield strength that is 26 MPa. The maximum deformation occurs on the screw caused by the 200 N tensile force is recorded to be 0.021 which is too small. It can be concluded that the bio-screw is capable to fix the graft in the tunnel. Further study using different contact condition is suggested to clarify the effects of bio-screw in the tunnel.

TABLE OF CONTENTS

CONTENTS	PAGE
PAGE TITLES	i
ACKNOWLEDGEMENT	ii
ABSTRACT	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	viii

CHAPTER 1 INTRODUCTION

1.1 Introduction	1
1.2 Problem Statement	2
1.3 Project Objectives	2
1.4 Scope of Project	3
1.5 Significant of Project	3

CHAPTER 2 LITERATURE REVIEW

2.1 Knee Stability	4
2.2 ACL Reconstruction	6
2.21 Operatives Techniques	6
2.22 Graft Selection	7

2.23 Graft Placement	9
2.3 ACL Graft Fixation	9
2.3.1 Tibial and Femoral Fixations	10
2.3.2 Ideal Graft Fixation	10
2.4 Current ACL Femoral Fixation Options	10
2.4.1 Interference Fit SCrew	11
2.4.2 Cross Pin Fixation	13
2.4.3 Buttons	14
2.5 Screw Design	15

CHAPTER 3 METHODOLOGY

3.1 Introduction	17
3.2 Geometry	19
3.3 Finit Element Analysis	20
3.3.1 Geometry	21
3.3.2 Material Properties	21
3.3.3 Contact Pair Definition	22
3.3.4 Mesh Definition	23
3.3.5 Boundary and Loading Conditions	23

CHAPTER 4 RESULTS

4.1 Introduction	25
4.2 Analysis of bio-screw with 7 x 20 mm dimension	27
4.3 Analysis of bio-screw with 7 x 25 mm dimension	29
4.4 Analysis of bio-screw with 7 x 30 mm dimension	31
4.5 Analysis of bio-screw with 8 x 20 mm dimension	33
4.6 Analysis of bio-screw with 9 x 20 mm dimension	35