UNIVERSITI TEKNOLOGI MARA

EFFECTS OF ETHANOL ADDITIVES ON SPARK IGNITION ENGINE PERFORMANCE AND EMISSIONS FUELLED WITH METHANOL-GASOLINE BLENDS

MOHAMAD QAYYUM BIN MOHD TAMAM

Dissertation submitted in partial fulfillment of the requirements for the degree of **Master of Science in Mechanical Engineering**

Faculty of Mechanical Engineering

March 2020

AUTHOR'S DECLARATION

I declare that the work in this dissertation was carried out in accordance with the regulations of Universiti Teknologi MARA. It is original and is the results of my own work, unless otherwise indicated or acknowledged as referenced work. This thesis has not been submitted to any other academic institution or non-academic institution for any degree or qualification.

I, hereby, acknowledge that I have been supplied with the Academic Rules and Regulations for Post Graduate, Universiti Teknologi MARA, regulating the conduct of my study and research.

Name of Student	:	Mohamad Qayyum Bin Mohd Tamam
Student I.D. No.	:	2018427416
Programme	:	Master of Science in Mechanical Engineering
Faculty	:	Mechanical Engineering
Dissertation Title	:	Effects of Ethanol Additives on Spark Ignition Engine Performance and Emissions Fuelled with Methanol- Gasoline Blends – EM703
Signature of Student	:	
Date	:	March 2020

ABSTRACT

Emissions of greenhouse gases resulting from automobile exhaust emissions is a major concern in recent years due to its effect on climate change. Therefore, an environmentally friendly alternative for fossil fuel needs to be developed to reduce heavy reliance on fossil fuels. Ethanol possesses a great potential to serve as substitute to gasoline due to its favourable physicochemical properties. This research investigated the effects of ethanol additives on spark ignition engine performance and emissions fuelled with methanol-gasoline blends. Four ethanol-methanol-gasoline blends or GEM blends were prepared with variable ethanol concentrations (0%, 5%, 10%, 15%) and constant methanol concentration (10%). Resultant blends were denoted as M10, E5M10, E10M10, and E15M10 in reference to each respective alcohol constituents. Physicochemical properties of these blends were measured in terms of density, calorific value, as well as kinematic viscosity and the results were compared to that of pure gasoline. Results showed that density and kinematic viscosity of ethanol-methanolgasoline fuel blends increases with ethanol concentration. E15M10 has shown the most improvement in terms of density and kinematic viscosity with 10.7% and 18.7% increase respectively as compared to pure gasoline. In contrast, calorific value was found to decrease as ethanol concentration decreases. E15M10 possesses lowest calorific value with 16.9% decrease as compared to pure gasoline. Engine performance and emissions were carried out on a single-cylinder SI engine at constant speed of 3000 rpm under various engine loads of 1.6, 3.2, and 4.8 Nm. Results showed that generally ethanol-methanol-gasoline fuels possess increased BSFC and BTE on average than pure gasoline. E15M10 displayed highest increment of BSFC at 17.2% average increase with respect to pure gasoline. E10M10 has displayed the highest improvement in BTE with an average of 9.4% increase as compared to gasoline. Meanwhile, no significant variations of EGT were observed. Exhaust emissions indicate that all ethanol-methanolgasoline blends produced increased CO₂ and NO_x emissions while CO emissions decreases. E15M10 showed the most reduction in CO emissions with 90.6% decrease compared to pure gasoline while E10M10 has shown the most increased CO₂ and NOx emissions with 1.0% and 6.7 times increase respectively. In conclusion, ethanolmethanol-gasoline fuel blends improved engine performance and emissions in terms of BTE and CO emissions in comparison to pure gasoline. Thus, ethanol additives are a practical alternative for blending with methanol-gasoline fuels in lower blend ratios.

ACKNOWLEDGEMENT

Firstly, I wish to express my deepest gratitude to God Almighty Allah S.W.T for the strength, resilience, and good health He has bestowed upon me throughout the duration of my research. It is by His will that this thesis becomes a reality

Secondly, I would like to thank my family members who have supported me and comforted me in times of distress. My beloved Ayah who have been patient and always offering to lend a hand whenever I am down on my feet. My brothers Kholif and Zakwan who have been a constant source of encouragement and inspiration.

Next, I would like to extend my appreciation to my research supervisor Assoc. Prof. Ts. Dr. Nik Rosli Abdullah for his continuous sharing of wisdom and guidance, as well as supporting me whenever I feel lost and disoriented in my research

I would like to also thank UiTM staff members who have supported my research; Mr Ameran, Mr Amin, Mr Azizi, Mr Fadhli, Mr Kamal, and all other faculty staff members who have assisted me and providing invaluable technical know-how.

My friends and colleagues in the postgraduate room, I will always thank all of you for the laughs and the support.

To you, thank you for all the love you have given me. This past year has been great with you in it.

Finally, I dedicate this thesis in loving memory of my late mother. Ibu, not a day passes without thinking of you, and I am glad I have finally fulfilled your wish.

TABLE OF CONTENTS

50

CON	ii	
AUTI	iii	
ABST	iv	
ACK	v	
TABI	vi	
LIST	ix	
LIST	xi	
LIST	xiv	
LIST	XV	
CHA	1	
1.1	Research Background	1
1.2	Problem Statement	3
1.3	Research Objectives	4
1.4	Research Significance	4
1.5	Scope and Limitation of Study	5
CHA	7	
2.1	Engine Performance Parameters	7
2.2	Exhaust Emissions Parameters	7
2.3	Methanol and Ethanol as Fuels	8
2.4	Research on Methanol and Methanol-Gasoline Fuels	14
2.5	Research on Ethanol and Ethanol-Gasoline Fuels	21
2.6	Comparison Between Methanol and Ethanol Blends	34
2.7	Research on GEM Fuel Blends	40
2.8	Summary and Research Gap	46
CHA	50	

3.1 Introduction