# UNIVERSITI TEKNOLOGI MARA



# ASSESSMENT OF SLOPES USING ROM SCALE IN

## PENANG AND SELANGOR

MOHD SIDDIQ ABD RAHIM

**B.ENG (HONS) (CIVIL)** 

UNIVERSITI TECHNOLOGY MARA

2006

#### **DECLARATION BY THE CANDIDATE**

I Mohd Siddiq Bin Abdul Rahim, 2003479473 confirm that the work is my own and the appropriate credit has been given where references has been made to the work of others.

(\_\_\_\_\_)

#### ACKNOWLEDGEMENT

In the name of ALLAH the Almighty, The Most Beneficent and the Most Merciful. First thing, I would like to grateful to The Merciful Allah S.W.T because give me strength, and health to complete this Final Year Report (KJC 537) according to the given time.

I would like to thanks to Mr. Abdul Rahim Bin Itam, Senior Technical Assistant at Jabatan Kerja Raya (JKR) Cawangan Barat Daya for the information, knowledge and cooperation. A special thanks to a nice supervisor, Prof. Madya Ir Damanhuri Jamalludin for his knowledge, information, understanding and guidance on how to deal the problem during my preparation for this report.

I also thanks to my entire friend who give me a lot of support and helpfulness, my parent and my family that give me a moral support and advice. Also not forget to those involved directly or indirectly in the preparation of this report.

Thank you very much.

#### ABSTRACT

Slopes failures are commonly occurring in Malaysia. The factor causing slope failure including soil properties, environment effect, rainfall effect and many more. ROM Scale is used to determine the landslide risk based on the soil physical properties to know the possibility of the landslide failure. In this study, there are sixteen landslide locations in Penang and Selangor that were chosen in this assessment of the slopes failures using ROM Scale. The slope failures in Penang were along Jalan Gertak Sanggul, Balik Pulau, Penang and Federal Route 6. In Selangor, the locations of slopes failures are at Wangsa Maju, Kg Bukit Sungai Putih, Ampang, and Taman Bukit Belimbing, Kajang. In order to obtain the results, laboratory tests were conducted and then the ROM Values were calculated and compared with ROM Scale to determine the landslide risk. From the results, low to moderate risk of landslide occurring when the clay content is higher. High to critical risk of landslides occur when the sand and silt content are high.

#### TABLE OF CONTENTS

ACKNOWLEDGEMENT	i
TABLE OF CONTENTS	ii
LIST OF FIGURES	iv
LIST OF TABLES	v
LIST OF NOTATIONS	vi
LIST OF APPENDICES	vii
ABSTRACT	viii

### **CHAPTER 1**

#### 1 INTRODUCTION

1.1	Background	1
1.2	Problem Statement	1
1.3	Objectives	2
1.4	Scope of Study	2
1.5	Significant of Research	2

### **CHAPTER 2**

## 2 LITERATURE REVIEW

2.1	Slope Stability	3
2.2	Factor Affecting Slope Stability	4
2.3	Rom Scale	6
	2.3.1 Definition of ROM Scale	5