PREPARATION AND CHARACTERIZATION OF LOW-COST CELLULOSIC MICROFILTRATION MEMBRANE

INSTITUT PENYELIDIKAN, PEMBANGUNAN DAN PENGKOMERSILAN
UNIVERSITI TEKNOLOGI MARA
40450 SHAH ALAM, SELANGOR
MALAYSIA

DISEDIAKAN OLEH :

NOR AIDA BT ZUBIR
NURHASLINA BT CHE RADZI

OKTOBER 2009

Tarikh : 20 Oktober 2009
No. Fail Projek : 600-UiTMPP (URDC:5/2/265)

Penolong Naib Canselor (Penyelidikan)
Institut Penyelidikan, Pembangunan dan Pengkomersilan (IRDC)
UiTM, Shah Alam

السلام عليكم ورحمة الله وبركاته

Y. Bhg. Prof.,

LAPORAN AKHIR PENYELIDIKAN 'PREPARATION AND CHARACTERIZATION OF LOW-COST CELLULOSIC MICROFILTRATION MEMBRANE'

Merujuk kepada perkara di atas, bersama-sama ini disertakan 4 (empat) naskah Laporan Akhir Penyelidikan bertajuk 'Preparation and characterization of low-cost cellulosic microfiltration membrane' oleh kumpulan Penyelidik dari Fakulti Kejuruteraan Kimia untuk makluman pihak tuan.

Sekian, terima kasih.والسلام

Yang benar,

NOR AIDA BT. ZUBIR
Ketua
Projek Penyelidikan

ABSTRACT

An attempt to investigate the possibility of using pineapple leave fibers (PALFs) as one of the alternative source of cellulose polymer for membrane fabrication has been carried out in this research. The PALFs were extracted mechanically from raw pineapple leaves. The extracted PALFs were then chemically treated and characterized prior to the membrane preparation. It was found that PALFs contained 94.58% holocellulose, 9.02% hemicellulose, 4.32% lignin and 1.10% ash. The chemical constituents obtained were found to be in the range of data reported in literatures. The cellulosic microfiltration membranes were prepared from the cellulose/*N*-methylmorpholine-*N*-oxide (NMMO)/ PEG 400 solutions (dope) at different cellulose concentrations (i.e. 6–8 wt%) by using immersion precipitation method. The influence of cellulose concentrations on the mechanical properties, microfiltration rate (MFR) and rejection rate (RR) of membranes were investigated in determining the optimized cellulosic microfiltration membrane. The optimized membrane was found to be at the cellulose concentration of 8 wt% that possessed considerable mechanical properties at MFR of 91.79 $mLh^{-1}m^{-2}mmHg^{-1}$ and dextran's RR of 86.51% under an applied pressure of 10 psi. Further characterizations on the optimized membrane were carried out in order to confirm the chemical structure, morphological changes, thermal properties and stability upon substituting the former cellulose's source, i.e. hardwood plant. The optimized cellulose membranes for both types (i.e. PALFs and hardwood) possessed analogous chemical structures which have been confirmed by the existence of similar functional groups detections. Meanwhile, scanning electron microscopy analysis of the optimized cellulose membranes elucidated that the source of cellulose has brought profound effect on the structural and morphology of resulting membranes. In general, matte and porous surfaces in a sponge-like configurations and uniform granular microporous structure were observed throughout the thickness of both membranes. But, the average pore size of membrane derived from PALFs was exhibited to be smaller than the hardwood which in turn affecting the MFR and RR performances. The use of PALFs as alternative source of cellulose polymer did not bring much alterations in the thermal properties and stability of resultant membranes. Both of the optimized cellulose membranes were observed to have a thermal stability up to 275 ± 5°C before enduring further decomposition in nitrogen atmosphere. These membranes have found to undergo two-stage decomposition patterns due to dehydration and degradation of the polymer matrixes. Hence, based on the overall results, it can be concluded that PALFs as a non-wood plant can be utilized as one of alternative source for cellulose polymer in preparing the cellulosic microfiltration membranes.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
ABSTRACT		i
TABLE OF CONTENTS		ii
LIST OF TABLES		iv
LIST OF FIGURES		v
CHAPTER I	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement	3
	1.3 Research Objective	4
	1.4 Scopes of the Research	4
CHAPTER II	LITERATURE REVIEW	5
	2.1 Membrane Separation Processes	5
	2.2 Cellulosic Membrane	7
	2.2.1 Cellulose and Its' Characteristics	7
	2.2.2 Types of Cellulose's Source	8
	2.2.3 Types of Cellulose's Extraction Method	12
	2.2.3.1 Chemical Treatment	12
	2.2.3.2 Mechanical Treatment	13
	2.2.4 Composition of Cellulose Extraction	13
	2.2.5 Pineapple Leaf Fibers (PALFs)	15
	2.3 Membrane Classification in Cellulosic Membranes	18
	2.3.1 Cellulose Membranes and Its' Applications	20
	2.3.2 Preparations and Characterizations Of Cellulose Membranes	21
CHAPTER III	METHODOLOGY	27
	3.1 Research Design	27
	3.2 Cellulose Extraction	27
	3.3 Characterization of Extracted Cellulose From PALFs	29
	3.4 Preparation of Cellulose Membrane	29

3.4.1 Materials 29
3.4.2 Preparation of Dope Solution 30
3.4.3 Casting of Flat Sheet Membrane 31
3.5 Characterization of Cellulose Microfiltration Membranes 32
3.5.1 Optimlzation of Cellulose Microfiltration Membranes 32
3.5.1.1 Mechanical Properties 33
3.5.1.2 Microfiltration Rate (MFR) 33
3.5.2 Characterization of Optimized Cellulose Microfiltration Membranes 34
3.5.2.1 FTIR Measurements 34
3.5.2.2 Scanning Electron Microscopy (SEM) 34
3.5.2.3 Thermal Gravimetric Analysis (TGA) 35

CHAPTER IV RESULTS AND DISCUSSIONS 36
4.1 Introduction 36
4.2 Characterization of Extracted Cellulose From PALFs 36
4.3 Optimization of Cellulose Microfiltration Membranes 37
4.3.1 Mechanical Properties 37
4.3.2 Microfiltration Rate (MFR) 38
4.4 Properties of Optimized Cellulose Microfiltration Membranes 40
4.4.1 FTIR Spectroscopy 41
4.4.2 Scanning Electron Microscopy (SEM) 43
4.4.3 Thermal Gravimetric Analysis (TGA) 46

CHAPTER V CONCLUSIONS AND RECOMMENDATIONS 48
5.1 Conclusions 48
5.2 Recommendations 50

REFERENCES 52