

UNIVERSITI TEKNOLOGI MARA

**CHARACTERISATION AND PROPERTIES OF
OIL PALM FRUIT BUNCH (OPFB)/
POLYPROPYLENE (PP) COMPOSITES, PP
NANOCLAY/PP AND OPFB/PP NANOCLAY/PP
HYBRID COMPOSITES**

ANIZAH KALAM

**Thesis submitted in fulfilment of the requirements
for the degree of
Doctor of Philosophy**

Faculty of Mechanical Engineering

May 2010

Candidate's Declaration

I declare that the work in this thesis was carried out in accordance with the regulations of University Teknologi MARA. It is original and is the result of my own work unless otherwise indicated or acknowledged as referenced work. This thesis has not been submitted to any other academic institution or non-academic institution for any other degree or qualification.

In the event that my thesis be found to violate the conditions mentioned above, I voluntarily waive the right of conferment of my degree and agree to be subjected to the disciplinary rules and regulations of University Teknologi MARA.

Name of Candidate	ANIZAH BINTI KALAM
Candidate's ID No	2005104905
Programme	Ijazah Kedoktoran Kejuruteraan Mekanikal (EM990)
Faculty	Kejuruteraan Mekanikal
Thesis Title	Characterisation and Properties of Oil Palm Fruit Bunch (OPFB)/ Polypropylene (PP) Composites, PP nanoclay/PP and OPFB/PP nanoclay/PP Hybrid Composites
Signature of Candidate	
Date	

ABSTRACT

In this study the oil palm fruit bunch fibres were used as the filler or reinforcement in polypropylene. Thus the aim of this thesis was to achieve a greater understanding of the various parameters that contribute to the variations of water absorption, thermal stability and mechanical properties, and to manipulate these parameters in order to produce an improved oil palm fruit bunch fibre reinforced polypropylene composite material. Several characterization techniques, such as tensile test, flexural test, impact test, water absorption analysis, thermal analysis and chemical analysis were used to assess the effect of each parameter. OPFB/PP composites at four different sizes of 250 μm , 180 μm , 125 μm and 100 μm were investigated on the water uptake ability and were found to increase as the OPFB size increase. Meanwhile the thermal stability decrease at temperature range of 200°C - 450 °C. The investigations also showed that the tensile and flexural properties were increased with the increasing of OPFB size and indicated that the 250 μm OPFB/PP composites had the most enhances mechanical properties. PPnanoclay/PP composites were compounded at four PPnanoclay loadings of 10 phr, 25 phr, 40 phr and 100 phr. The water uptake of PPnanoclay/PP composites was found to increase as the PPnanoclay loading increase followed by the increase in thermal stability as well. Tensile tests, flexural tests and impact tests revealed that the optimum composite consisted of polypropylene with 25 phr PPnanoclay loading. Combination of OPFB and PPnanoclay as fillers in PP indicates that the tensile modulus, flexural modulus and flexural strength has increased at lower PPnanoclay loading and decreased at higher PPnanoclay loading. The optimum loading of PPnanoclay in OPFB/PPnanoclay/PP hybrid composites was also found to be at 25 phr. Further investigation on the effects of OPFB size in OPFB/PPnanoclay/PP hybrid composites showed that the 250 μm size gave the most mechanical properties enhancement. Properties improvement after OPFB treatment and increase of MAPP loading with the increase of OPFB loading suggested that the good bonding between filler and matrix contributed to the mechanical properties enhancement, decrease of water uptake and increase of thermal stability.

ACKNOWLEDGEMENTS

بسم الله الرحمن الرحيم

First of all, I want to thank ALLAH the Almighty for giving me the ability to complete this challenging research and for giving me the strength and courage to go on day by day despite of the lack of resources. This experience has shown me that through God, all things are possible.

Next, I would like to thank the Universiti of Teknologi MARA for providing the opportunity and funds to make this study possible. I would also like to thank my supervisor Prof. Dr. Ir. Mohamad Nor Berhan and co-supervisor Prof. Dr. Hanafi Ismail for giving guidance throughout this project. I also appreciate the help and supports of the former Dean, Prof. Ir. Dr. Abdul Rahman Omar and current Dean Associate Prof. Ahmad Jaafar, who believed that this research could be accomplished, despite the lack of facilities. In addition, I would like to thank all other colleagues in the Fakulti Kejuruteraan Mekanikal, UiTM for all the supports given throughout the years.

I am very much indebted to all the technical staff; Naziman, Hairi, Norazman, Ziyadi, Rahimi, En. Shawal, Sham, En. Hayub and En Yusri for being there when I needed them most. You guys have helped me a lot through the years. Also many thanks for all the staff from Fakulti Sains Gunaan, Syam, Sham, Siti, Joe and Hj. Rahimi.

I would also like to thank Prof. Dr. Daniel Dee Kee for his kindness to give a copy of his articles free of charge though we only communicate through the e-mail. Many thanks also to Nanocor Inc. and Sabutek Sdn. Bhd. for supplying the materials. Not to forget all the people surround me that directly and indirectly have give courage and keep supporting in whatever means, which I appreciate them very much.

Lastly but the most important, I would also like to thank the love of my life, my family, husband, sons (Amir Hazman, Ariff Hazwan, Amin Hakim and Alif Harith) and daughter (Azwa Hasanah) for supporting me throughout this arduous journey. Their tolerance and understanding while I have been engaged in this labour of love are indeed appreciated. My kids may find it hard to adjust now that I am free for conversation and monitoring their activities! I would also like to thank my mom and sisters and brother for supporting me through all of my educational endeavours. You all have given me so much throughout my life, and I am sincerely grateful for that. There have been many people who have helped with the development of this thesis and if I have forgotten to thank anyone, my sincerest apologies.

The Author