

EM110 DIPLOMA OF MECHANICAL ENGINEERING FACULTY OF MECHANICAL ENGINEERING UITM CAWANGAN JOHOR, PASIR GUDANG CAMPUS

MEC332 MECHANICAL ENGINEERING DESIGN

PROJECT:

CLIMBER HAND TRUCK

SUPERVISOR'S NAME:

SIR AHMAD FAIZAL BIN KHODORI

LECTURER'S NAME:

SIR FARIS SHAFIQ BIN KHALID

GROUP:

J4EM1105C

NO.	NAME	STUDENT ID
1	AZAMUDDIN BIN A BAKAR	2018413164
2	AKMAL ZULHILMI BIN ANNUAR	2018643612
3	AMZAR MUIZZUDDIN BIN MAZWAN	2018444228
4	IFWAT UMAR BIN IKHWAN	2018671154
5	AMIRUDDIN ARIF BIN AZIZAN	2018673158

ACKNOWLEDGEMENT

First and foremost, we would like to extend our greatest gratitude to Allah S.W.T for giving us the opportunity to complete this group assignment together successfully.

We are also like to express our deep and sincere gratitude to our supervisor, Sir Ahmad Faizal Bin Khodori for providing invaluable guidance throughout this assignment. His dynamism, vision, sincerity and motivation have deeply inspired us. He has taught us the methodology to carry out the assignment and to present the final year project as clearly as possible. It was a great privilege and honour to study under him guidance. We would also like to thank him for the friendship and empathy.

Next, we would also like to thank our lecturer, Sir Faris Shafiq Bin Khalid and group members for being cooperative and making sure this project is to be done on time. This project would not be a success if it was not for their hard work and dedication.

Lastly, we would also like to thank our beloved family members for helping us mentally, physically and financially. They made our jobs at ease by providing us with necessary help and finance so that our assignment is done perfectly.

ABSTRACT

This report shows the progress of our project. Each week we will hold a meeting to find out the progress of each of our members in doing the task. In the meeting we will also discuss how to solve every problem we face to complete this project. We also ask for ideas from our supervisors to improve our products. Our products are inspired by overseas products and we innovate the products to be safer and according to the preference of Malaysians.

Design for this product we use the existing design only we add some appropriate factors. Among them, we added a belt on the shelf so that when the item is lifted there will be no accidents. In addition, we also use minimum size treads so as not to disturb customers when using this product.

In this product there is also a poka-yoke to prevent accidents when using this product. The poka-yoke on this product is on the button to start the movement of the treads. The button has a cover so it is not stressed while the treads are moving.

TABLE OF CONTENTS

2.1 Problem Statement 2.2 Market Analysis 2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	CONTENT	PAGES	
• 1.2 Significant of the Project • 1.3 Project Planning 2.0 PROBLEM DEFINITION • 2.1 Problem Statement • 2.2 Market Analysis • 2.3 Customer Needs and Identification • 2.4 Competitive Benchmarking Product • 2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION • 4.1 Morphological Chart and Analysis • 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN • 5.1 Product Architecture • 5.2 Configuration Design • 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN • 6.1 Part/Machine Detail • 6.2 Assembly Drawing • 6.3 Exploded View • 6.4 Bill of Material • 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	1.0 INTRODUCTION		
 1.2 Significant of the Project 1.3 Project Planning 2.0 PROBLEM DEFINITION 2.1 Problem Statement 2.2 Market Analysis 2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	• 1.1 Design Objective	5 (
2.0 PROBLEM DEFINITION 2.1 Problem Statement 2.2 Market Analysis 2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	• 1.2 Significant of the Project	5 - 6	
2.1 Problem Statement 2.2 Market Analysis 2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	• 1.3 Project Planning		
2.2 Market Analysis 2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	2.0 PROBLEM DEFINITION		
2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	• 2.1 Problem Statement		
 2.3 Customer Needs and Identification 2.4 Competitive Benchmarking Product 2.5 Product Design Specification 3.0 LITERATURE REVIEW 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	• 2.2 Market Analysis	7 16	
2.5 Product Design Specification 3.0 LITERATURE REVIEW 17 4.0 CONCEPT GENERATION AND EVALUATION 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	• 2.3 Customer Needs and Identification	7 – 10	
3.0 LITERATURE REVIEW 4.0 CONCEPT GENERATION AND EVALUATION • 4.1 Morphological Chart and Analysis • 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN • 5.1 Product Architecture • 5.2 Configuration Design • 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN • 6.1 Part/Machine Detail • 6.2 Assembly Drawing • 6.3 Exploded View • 6.4 Bill of Material • 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	2.4 Competitive Benchmarking Product		
4.0 CONCEPT GENERATION AND EVALUATION • 4.1 Morphological Chart and Analysis • 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN • 5.1 Product Architecture • 5.2 Configuration Design • 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN • 6.1 Part/Machine Detail • 6.2 Assembly Drawing • 6.3 Exploded View • 6.4 Bill of Material • 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	2.5 Product Design Specification		
 4.1 Morphological Chart and Analysis 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	3.0 LITERATURE REVIEW	17	
 4.2 Pugh Chart and Analysis 5.0 EMBODIMENT OF DESIGN 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	4.0 CONCEPT GENERATION AND EVALUATION		
5.0 EMBODIMENT OF DESIGN • 5.1 Product Architecture • 5.2 Configuration Design • 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN • 6.1 Part/Machine Detail • 6.2 Assembly Drawing • 6.3 Exploded View • 6.4 Bill of Material • 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	4.1 Morphological Chart and Analysis	18 – 26	
 5.1 Product Architecture 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	• 4.2 Pugh Chart and Analysis		
 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	5.0 EMBODIMENT OF DESIGN		
 5.2 Configuration Design 5.3 Parametric Design for Custom Parts 6.0 DETAIL DESIGN 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52	• 5.1 Product Architecture	27 29	
6.0 DETAIL DESIGN • 6.1 Part/Machine Detail • 6.2 Assembly Drawing • 6.3 Exploded View • 6.4 Bill of Material • 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	• 5.2 Configuration Design	21-30	
 6.1 Part/Machine Detail 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	• 5.3 Parametric Design for Custom Parts		
 6.2 Assembly Drawing 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	6.0 DETAIL DESIGN		
• 6.3 Exploded View • 6.4 Bill of Material • 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	6.1 Part/Machine Detail		
 6.3 Exploded View 6.4 Bill of Material 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	• 6.2 Assembly Drawing	20 51	
 6.5 Costing Evaluation 7.0 CONCLUSION AND RECOMMENDATIONS 7.1 Conclusion 52 	• 6.3 Exploded View	39 – 31	
7.0 CONCLUSION AND RECOMMENDATIONS • 7.1 Conclusion 52	• 6.4 Bill of Material		
• 7.1 Conclusion 52	• 6.5 Costing Evaluation		
	7.0 CONCLUSION AND RECOMMENDATIONS		
7.2 Decommendations	• 7.1 Conclusion	52	
• 7.2 Recommendations	• 7.2 Recommendations		

1.0 INTRODUCTION

The first ever hand truck were called sack trucks and it was initially used in the 18th century. It was created in order to help young boys carry large sacks of supplies as efficient as how young men would carry items around by hand. The base design of the hand truck consists of an L-shapedcart with handles on each end, two wheels on the base and a ledge to place objects.

A few innovations were created for the hand trucks to increase its functionality such as increasing the area of the ledge to increase the maximum capacity of load that is carried, using hard materials for the hand truck so that it can carry more weight or the design of the tires resembles a fidget spinner to help it climb steps. However, many industries would prefer the original designdue to the cost and it will still be able to achieve the same purpose with other advance hand trucks.

1.1 Design Objective

The major objective of this project is to ensure the user's package or load reaches its destination safely. However, a few minor objectives must be accomplish in order to achieve this goal. These minor objectives are the criteria that is needed for the final product. The objectives areas follows:

- The product will be able to function properly on inclining steps either ascending ordescending.
- The product will be able to hold the package or load without damaging it
- The product needs to maintain its stability on multiple terrain.

1.2 Significance of the Project

This project is related to carrying everyday object on stairs. Thus, the importance of this project that can contribute to the buyers are as follows:

- The object that is carried is guaranteed to reach its destination with ease.
- The object carried will not fall off or slip from the product.

- Users will be able to carry more object with less effort.

• The product will be easy to use and stored. The product will use eco-friendly and non-hazardous components