



# PROGRAMMABLE AC POWER CONTROL

MUHAMMAD AMIRUL IDHAM BIN LAILI  
MEGAT AMIR HANAFI BIN MEGAT TAFTAZANI

TK  
3141  
.M84  
2015

FACULTY OF ELECTRICAL ENGINEERING  
UNIVERSITI TEKNOLOGI MARA  
MALAYSIA

MARCH 2015

## TABLE OF CONTENTS

ACKNOWLEDGEMENTS	1
DECLARATION OF ORIGINAL WORK	2
ABSTRACT	3
LIST OF FIGURES	4
LIST OF TABLES	5
LIST OF ABBREVIATION	6
<b>INTRODUCTION</b>	
1.1. Background of Study	7
1.2. Problem Statement	11
1.3. Objectives	11
1.4. Scope of Study	12
<b>MATERIALS AND METHODS</b>	
2.1. Methodology	13
2.2. Experimental Setup	14
2.3. Equipment and Component	15
<b>CIRCUIT DESIGN AND OPERATIONS</b>	
3.1. Schematic Diagram	26
3.2. Circuit Operations	26
3.3. PCB Design	35
<b>RESULT AND DISCUSSION</b>	
4.1. Software Simulation Result	37
4.2. Hardware Implementation Result	38
4.3. Circuit Testing and Troubleshooting	40
4.4. Data Analysis and Discussions	41
<b>CONCLUSION AND RECOMMENDATION</b>	
5.1. Conclusion	43
5.2. Recommendation and Suggestion	44
REFERENCES	45
APPENDICES	46

## **ACKNOWLEDGEMENT**

First and foremost, we would like to offer my honest gratitude to our supervisor Dr. Muhammad Asraf Bin Hairuddin for his guidance and constant supervision as well as for providing necessary information regarding the project and also for his support in completing the project.

We would like to express my gratitude towards my parents and our member for their kind co-operation and encouragement which help us in completion of this project.

Our thanks and appreciations also go to my colleague in developing the project and people who have willingly helped us out with their abilities.

## **ABSTRACT**

The project is designed to see the effect of the firing angle of the transistor to the load power. Based on the principle of firing angle control of thyristors, one can control the ac power. A display unit displays the full power or any percentage and one can enter the desired percentage to reduce the power to the load.

The firing angle would be automatically adjusted to maintain the load power. The project uses a lamp such that the entered power matches the required one.

## LIST OF FIGURES

<i>Figure 1.1: Embedded System Design Calls</i>	8
<i>Figure 1.2 :“V Diagram”</i>	9
<i>Figure 2.1 : System Flowchart</i>	13
<i>Figure 2.2 : Block Diagram</i>	14
<i>Figure 2.3: Voltage Regulator Internal Block Diagram</i>	16
<i>Figure 2.4 : Block Diagram of AT89S52</i>	18
<i>Figure 2.5: Keypad</i>	20
<i>Figure 2.6: LM 358</i>	22
<i>Figure 2.7: Optoisolator Description</i>	23
<i>Figure 2.8: SCR</i>	25
<i>Figure 3.1: Schematic Diagram</i>	26
<i>Figure 3.2: Comparator</i>	28
<i>Figure 3.3: Optocoupler</i>	29
<i>Figure 3.4: Triac</i>	30
<i>Figure 3.5: Zero-Voltage Sensing Circuit</i>	32
<i>Figure 3.6: Zero-Voltage Waveform</i>	32
<i>Figure 4.1: Simulation Result</i>	37
<i>Figure 4.2: The lamp glows at full intensity.</i>	38
<i>Figure 4.3: The lamp is glow at 40% after the input is inserted. Input = 40%.</i>	39