## PROPERTIES OF CEMENT BOARD FROM DIFFERENT PARTICLE GEOMETRY AND LAYER OF OIL PALM TRUNK (OPT)

### MOHD NAHWAN NUR BIN MOHD GHAZALI

Final Year Project Report Submitted in
Partial Fulfillment of the Requirement for the
Degree of Bachelor of Science (Hons.) Bio-Composite Technology
in the Faculty of Applied Sciences
Universiti Teknologi MARA

#### **ACKNOWLEDGEMENTS**

I would like to take this opportunity to express our special thanks to ALLAH S.W.T for his blessing and strength rendered to completed my final project "Properties of Cement Board from different particle geometry and layer of Oil Palm Trunk (OPT)" and thanks to all my friends for their support.

I also would like to offer special thanks to my supervisor, Dr. Shaikh Abdul Karim Yamani Bin Zakaria, for helping and teach me along the final project process. He who are so generous in lending helping hands and show me how to complete the task. May Allah repay all his kindness towards me. Not to forget En. Ahmad Fauzi, En. Nazri, En. Rudaini and En. Shahril that also helping to complete my final project.

Lastly, I wish to convey my special gratitude to my beloved parents, Mohd Ghazali Bin Mejah and Saodah Binti Abdullah and my family for their support throughout my study period and also a lot of thanks to all our friends who have helped in every way to make this project successful.

## TABLE OF CONTENTS

				Page	
	DOM	CHERT			
APP	ii 				
ACI	iii :				
	SLE OF T OF TA	CONTE	NIS	iv	
		GURES		vi vii	
	T OF PI			viii	
LIS'	ix				
ABS	X				
ABS	xi				
ADS	IKAK			AI	
CH	ADTED	1 INTRO	DUCTION		
		round of s		1	
1.2	_	ms statem	2	3	
1.3		Scopes and limitation of the study			
1.4		tives of stu		4 4	
CH	APTER	2 LITER	ATURE REVIEW		
2.1	Oil pal	5			
	_	Oil palm	n crops	5	
		-	a production	6	
	2.1.3	-	7		
2.2	Wood	8			
	2.2.1	2.2.1 Cement board			
	2.2.2	Properti	Properties of wood cement board		
		2.2.2.1	Workability	10	
			Fungus and termites resistant	10	
		2.2.2.3	Sound insulation	10	
		2.2.2.4	Health safety	11	
		2.2.2.5	Fire resistance	11	
		2.2.2.6	Utilization	11	
	2.2.3	2.2.3 Uses of wood cement board			
		2.2.3.1	Partition and wall	12	
		2.2.3.2	Permanent formwork	12	
		2.2.3.3	Fire safety requirements	12	
	2.2.4		affecting board properties	13	
		2.2.4.1	Particle size	13	

CHA	APIEK	3 METHODOLOGY			
3.1	Manu	facturing steps	14		
	3.1.1	Materials preparation	15		
	3.1.2	Mixing	17		
	3.1.3	Mat forming	19		
	3.1.4	Cold press, hardening and conditioning	20		
	3.1.5	Cutting and board evaluation	21		
3.2	Mechanical test				
	3.2.1	Bending test	22		
	3.2.2	Internal bond test	22		
3.3	Physic	eal test	22		
	3.3.1	Thickness swelling and water absorption test	22		
3.4	Analy	sis	23		
<b>CH</b> A	APTER	4 RESULTS AND DISCUSSIONS			
4.1	Mecha	anical and physical properties of WCB according to	24		
	differe	ent layers and particle size			
4.2	Statist	Statistical significance			
4.3	Effect of OPT layer onto mechanical properties				
4.4		t of particle geometry onto mechanical			
	prope	erties	28		
4.5	Effect	of OPT layer onto physical properties	29		
4.6	Effect of particle geometry onto physical properties				
CHA	APTER	5 CONCLUSIONS			
5.1	Concl	usion and recommendations	32		
DDY	nn na	org	34		
REFERENCES APPENDICES CURRICULUM VITAE					

#### ABSTRACT

# PROPERTIES OF CEMENT BOARD FROM DIFFERENT PARTICLE GEOMETRY AND LAYER OF OIL PALM TRUNK (OPT)

The objective of this study is to investigate the physical and mechanical properties of cement board from different particle geometry and layer of oil palm trunk (OPT) and were evaluated based on Malaysian Standard (MS 544: 2001). Variable factors were layers of OPT (L1, L2 and L3) and particle geometry (Unscreen, 1.0mm and 2.0mm). The physical and mechanical data were analyzed using statistical package for social sciences (SPSS) software to determine significant different of the variable. From this study, layer 2 of OPT results in higher mechanical and physical strength than other layer. Meanwhile for particle geometry, unscreen particle size also produce a significant difference in term of mechanical and physical properties of board, thus result in stronger board.