

DEPARTMENT OF BUILDING UNIVERSITI TEKNOLOGI MARA (PERAK)

DESIGN AND CONSTRUCTION OF STEEL CONNECTION

PREPARED BY: MUHAMAD NAJMUDDIN BIN HASRI 2012621772

DEPARTMENT OF BUILDING FACULTY OF ARCHITECTURE, PLANNING AND SURVEYING UNIVERSITI TEKNOLOGI MARA (PERAK)

SEPTEMBER 2014

It is recommended that the report of this practical training provided

 $\mathbf{B}\mathbf{y}$

Muhamad Najmuddin Bin Hasri 2012621772

entitled

Design & Construction of Steel Jointing (Welding)

accepted in partial fulfillment of requirement has for obtaining Diploma In Building

Report Supervisor

En. Mohd Najib B. Abd Rashid

Practical Training Coordinator

Puan Wan Nordiana Bt. Wan Ali

Faculty Coordinator

Dr. Mohd Rofdzi Abdullah

DEPARTMENT OF BUILDING

FACULTY ARCHITECTURAL PLANNING AND SURVEYING

UNIVERSITY TECHNOLOGY MARA

(PERAK)

SEPTEMBER 2014

STUDENT'S DECLARATION

I hereby declare that this report is my own work, except for extract and summaries for

which the original references stated herein. I've completed my practical training for 4

months started from 12 Mei 2014 until 29 September 2014 by the side of Preserver

Bina Sdn. Bhd. This practical training report is also as a part of my duty to complete

my practical training. Furthermore, it is also as one of my requirements towards this

course DBN307 of Diploma in Building.

Name

: Muhamad Najmuddin Bin Hasri

ID No. UiTM: 2012621772

Date

: 29 SEPTEMBER 2014

ACKNOWLEDGEMENT

Alhamdulillah, thank you Allah S.W.T with His greaters allow me to completed my practical training in about 5 month with under Preserver Bina Sdn. Bhd.. Beside that, i would like to thanks to all individuals involved directly or indirectly in Preserver Bina Sdn. Bhd. whom help me to completing this practical training report especially my practical supervisor, En. Nur Rahmat Zainuddin as site engineer at site construction KL-Kepong Oleomas Sdn. Bhd., Pulau Indah, Klang. My acknowledge is also to my entire senior staff and supervisor in Preserver Bina Sdn Bhd because had thought me all about being supervisor in site and making decision to solve all problem produce in site. Thanks to Preserver Bina Sdn Bhd because allow me to be as their practical trainee from 12 May 2014 until 29 September 2014. Last but not least, to my report supervisor, En. Mohd Najib b. Abdul Rashid because support me at every single time, build my strength, give an idea in every single things to make this practical training report completely done.

Thank you very much

ABSTRACT

This report will review a general procedure on the erection of steel connection in construction and design. It is one of report that comes with complete guidance in every aspect of steel connection for specific project needs. Almost 5 months in practical training at Preserver Bina Sdn. Bhd. I have learnt so much about all steps, proper procedure and all requirements of steel jointing especially on site. Objective of this practical training report is to identify more precisely on how steel jointing are installed at site which is to study the method of steel jointing using the welding method (welding SMAW machine) and to identify welding method used for a few type of steel connection. Many methodology had been used to ensure this report completed, which is Primary Data and Secondary data. As a conclusion, A proper work of installation will definitely need a proper skill of labour and sufficient tools and machineries to do it. As we know all these tools will need to be sufficient enough to make a work become more easy and fast. This is because, not only the installation of work will requires the tools and machineries.

CONTEN	Γ		PAGES
Acknowledg	gement		i
Abstract			ii
Content			iii-iv
List of Table	es		v
List of Diag	rams		vi
List of Photo	0		vii
List of Shor	t forms		viii
CHAPTER	1.0	INTRODUCTION	
1.1	Introd	uction	1
1.2	Objec	tive reports	2
1.3	Scope	of report	2
1.4	Metho	odology	3
CHAPTER	2.0	COMPANY BACKGROUND	
2.1	Introd	luction	4
2.2	Comp	oany Profile	5
	2.2.1	Information establishment	6-7
	2.2.2	Company Awards	7
2.3	Comp	oany Objectives	8
2.4	Comp	oany Organizational Chart	9
2.5	List o	f Project	
	2.5.1	Project On-going	10- 11
	2.5.2	Project has completed	12-15

CHAPTER 3.0 INSTALLATION OF STEEL JOINTING USING WELDING METHOD

3.1	Introdu	action	16-17
3.2	Backgr	cound of project	17-18
3.3	Case Study		
	3.3.1	Welding Work Procedure	18-19
	3.3.2	Welder Qualification	20
	3.3.3	Consumables	20-21
	3.3.4	Permissible Condition For Welding	22
	3.3.5	Preparation For Welding	22
	3.3.6	Edge Preparation	23
	3.3.7	Preheating	23
	3.3.8	Tack Welding	23-24
	3.3.9	Welding Sequence & 'Waiting'	24
	3.3.10	Executive Of Butt Welding	24-25
	3.3.11	Repairing Of Other Defects	25
	3,3,12	Acceptance Criteria	26
	3.3.13	Inspection	26
	3.3.14	Documentation	26
	3.3.15	Tools Of Welding	27-28
CHAPTER	4.0	CONCLUSION AND RECOMMENDATION	
4.1	Recom	nmendation	29
4.2	Conclu	usion	30
REFERENCE	es .		31
APPENDIX			32

LIST OF TABLE

Table 2.5.1	List of On-Going Projects	10-11
Table 2.5.2	List of completed projects	12-15
Table 3.3.3	Electrodes Dry Condition	21
Table 3.3.10	The height of reinforcement of weld	25

LIST OF DIAGRAM

Diagram 3.3.16 SMAW system setup

27

LIST OF IMAGE

Photo 3.1	Steel Structure	16
Photo 3.2	Site Project	17
Photo 3.3.3	Electrode	20
Photo 3.3.6	Welder with the safety tools	22
Photo 3.3.13	Painting or finishing	26
Photo 3.3.16	SMAW	27
Photo 3.3.16.3	Electrode	27
Photo 3.3.16.1	The Welder	28
Photo 3.3.16.2	Face cover	28
Photo 3.3.16.4	Hand Cover	28

LIST OF SHORT-FORMS

SMAW Sheild metal arc welding

QA/QC Quality Approve/Quality Control

CHAPTER 1

INTRODUCTION

1.1 Introduction

For an introduction, steel structure are the most easier method used in any kind of construction industrial in entire world. If we see for example Eiffel tower at Paris, it's completely shown to us that the steel structure can make the building done faster, tougher and stronger, taller and make the symbol of engineering to the Paris. For another example, the Malaysian Penang Bridges structure is completely use steel structure. Penang bridges are the glory symbol for the Malaysia.

But in this report is directly shown only the steel jointing or steel erection using welding method. Installation method and the tools that related with this things.

What make this report different from others are, all the contents in this report are hereby provided by using a types of methodology which is an observation works, research or revision works and interview sessions from individuals involved. There are few type of methodology is done to help collect crucial information by practical method on proper step of installing steel jointing using welding method which is no other books or articles had written before.

Besides review on procedures of installation, this report will help to understand all the components function and tools needs for completing this installation work. All the problems relate to of steel jointing also will be generally review along with its recommendation on how to solve it.

1.2 Objective Reports

Objective of this practical training report is to identify more precisely on how steel jointing are installed at site. Other objectives are:

- a. To study the method of steel jointing using the welding method (welding SMAW machine)
- b. To identify welding method used for a few type of steel connection

1.3 Scope of Report

Scope of study for this report are practically review on methodology of installing an steel jointing. Besides getting more knowledge on components function and tools needed to complete the whole step of installation, it also will help to provide crucial information why steel is used as a beam that hold the load from above compared to other material used in construction field these days.

Therefore, this scope of study is done only under project named, KL-Kepong Oleomas Sdn. Bhd., which is to "Propose to Developed Additional Factory from 'Oleo Chemical' that included the SME Dry Plant, cooling room, SME Wet, Storage & Tower Room, Pipe Rack, Hydrogenation 7 storey and ME Distillation 6 Storey" is located at Section 5, Fasa 2D, Pulau Indah Industrial Park, Jalan Sungai Pinang 5/18, 42920 Pulau Indah, Selangor, Darul Ehsan. The actual owner of this land for KL-Kepong Oleomas Sdn. Bhd. project is KL-Kepong Oleomas Sdn. Bhd.

1.4 Methodology

1.4.1 Primary Data

Many methodology had been used to ensure this report completed, one of the method are reconnaissance. This project is developed a "Propose to Developed Additional Factory from 'Oleo Chemical' that included the SME Dry Plant, cooling room, SME Wet, Storage & Tower Room, Pipe Rack, Hydrogenation 7 storey and ME Distillation 6 Storey" for KL-Kepong Oleomas Sdn. Bhd.. This project is one of the biggest project for Preserver Bina Sdn Bhd. Therefore, method statement is needed to ensure all the details work are supervised properly. Pictures is taken for this report to showing the precise work of installation of steel using two method as mentioned. This report interview session is need to be done to collect more information about installation of steel installation. This interview sessions is done with many individuals at Preserver Bina Sdn Bhd. Some of the interview individuals are site supervisor, engineer, and workers.

1.4.2 Secondary Data

Next is revision. All files, documents and drawing plan is needed as one of the methodology of this report. This documents and files is revised as revision to ensure that all the works are done according to its step. Most of the revision had been done from drawing plan, because that plan give completed view about design and specification of the steel jointing. Besides, some of the documents give more information about Preserver Bina Sdn Bhd profile and achievements. Therefore, revision is important to ensure this report is complete.

CHAPTER 2

COMPANY BACKGROUND

2.1 Introduction

Preserver Bina Sdn. Bhd. is one of the General contractors with a Steel fabrication factory. This company is specialize in construction including the Construction of factories and warehouse, Power generation, Petrochemical and Oleo Chemical Plants, Heavy Equipment Installation, Bridge and Infrastructural Steel Structures, Commercial Buildings and High-Rise Buildings, High-Ends show Units, Bungalows and Residential Building.

Preserver Bina Sdn. Bhd. had a multi-talented team of experts who works cohesively as a single force to provide technical expertise and consultancy. This company can design and tailor-make solutions according what clients needed. Besides have their own Steel Fabrication factory at No.22A, Jalan Tiara 5, Bandar Baru Klang, 41150, Klang, Selangor Darul Ehsan. Therefore, this company will match every factory specifications, locally and overseas.

In 17 April 2009, Preserver Bina Sdn. Bhd. had cooperated with its own partner business as known as Alubina Sdn. Bhd. to listed services included fabricated and installed an Aluminum components for General construction and Infrastructural projects as well as Residential divisions. Alubina Sdn. Bhd. services are backed by very experienced technicians and professional knowledge to ensure high quality products to fulfill client's needs.

2.2 Company Profile

Company Name :

:

:

:

:

PRESERVER BINA SDN. BHD. (610805-M)

Partner Name

ALUBINA SDN. BHD.

ROC Registration No:

853439-K

Incorporated on

17 April 2009

Paid-Up Capital

RM 100,000.00

Authorized Capital

RM 100,000.00

Address (Office)

Lot 8292, No.2, Tingkat 1, Jalan Istimewa, Kg.

Batu Belah, 41050, Klang, Selangor Darul

Ehsan

(Factory) :

Lot 4977 & 4978, Jalan Dahlia, Off Jalan Meru,

41050 Klang, Selangor Darul Ehsan.

Directors

Khoo Beng Aun, Wong Kok Meng, Soon Kian

Eng, Khoo Beng Seong

Bankers

:

:

United Overseas Bank (UOB)

Tel. No.

Fax No.

:

:

+603-33447013

Email Address

pbinasb@gmail.com

2.2.1 Information Establishment

Preserver Bina Sdn. Bhd. was incorporated in April 2003. This company is also known as a general contractor with a steel fabrication factory. Preserver Sdn. Bhd. had a long list of services. This company has registered as a Grade 7 Contractor with the Construction Industry Development Board (CIDB). After a decade, this company has secured the prestigious ISO 900 1:2009 Award.

Preserver Bina Sdn. Bhd. has successfully completed significant projects in general construction, Infrastructural projects and Steel Fabrication. Therefore, this company had won an awards and recognition by clients and the industry's authorities by tailor-making better solution, locally and overseas. For residential division's Preserver Bina Sdn. Bhd. specialize in bungalows, transforming homes, townships and gated communities. This includes designing and constructing the residential building. Preserver Bina Sdn. Bhd. have their own steel fabrication factory, with the latest machinery to maintain the high quality standards and to ensure the steel products is the in a best condition. With these standards Preserver Bina Sdn. Bhd. leaves their factory matches international specifications.

Besides that Alubina Sdn. Bhd. is also a business partner with Preserver Bina Sdn Bhd. Alubina Sdn. Bhd. is a leading contractor for Aluminum & Glazing works includes Aluminum Composite Panels, Glass Canopy, Curtain Wall, Skylight Glass Canopy, Box Louvers, Sun Louvers, Aluminum Windows, and Aluminum Doors. This partnership is incorporated almost 6 years with Preserver Bina Sdn Bhd. this partnership also had established itself as a reputable and reliable business partner in all related projects

Preserver Bina Sdn. Bhd. assures that the best performance to deliver results as promised and works towards win-win deals. This company ensures every output in a high quality standards, overall quality control, cost effectiveness, and efficiency will

speed up projects and meet the deadlines as promised. Preserver Bina Sdn Bhd aims to get better in future and stay ahead in the industry, so that they can remain the preferred choice in General Construction, Infrastructure projects and Steel

2.2.2 Company Awards

The Awards and accolades Preserver Bina Sdn. Bhd. has won over the years prove their capabilities. Among the significant ones are:

- 2 Awards from the Malaysia Architects Association (MAA) Excellence in Architecture – Winning Showroom Building PAM 2007 for the Ameera Residences Sales Gallery.
- Honorary Mention Showroom Building PAM 2007 Awards for excellence in Architecture for the ONE Menerung Showroom & BRDS Sales Gallery Project.
- Achieved 3,000,000 and 2,000,000 Man Hours Without A Lost Time Incident in its Coal Fired Power Plant from TAISEI CORPORATION (in 30th September 2007 and 21st February 2008 respectively).
- Special Recognition as a Specialist Sub-contractor for the SUNCON GROUP OF COMPANIES' Overseas Projects (Sunway Construction).
- Achieved 2,500,000 Man Hours Without Lost Time Accident Safety
 Performance For the Superstructure Works 3A University Technology
 Petronas, Tronoh, Perak. Recognition by NAMFATT-ZAQ JV (31st March
 2004)
- ISO 900 1:2008, CONSTRUCTION OF STEEL STRUCTURE.
- Preserver Bina also won numerous Recognition for Architectural excellence, outstanding reliability and superior performance from numerous other leading developers.

2.3 Company Objectives

Preserver Bina Sdn. Bhd. aims to get better and stay ahead from other companies in the industries, so that they can remain as the preferred choice in General Construction, Infrastructural projects and Steel Fabrication.

2.3.1 Mission

Preserver Bina Sdn. Bhd. dedication is to constantly improve in all aspects of operations more than just a daily lived philosophy. It's what keeps Preserver Bina Sdn. Bhd. ahead. This company goes the extra mile, design and delivers what clients expect, and it is backed by a great multi-talented team with ultimate potentials. Together this company will drive to take on the most challenging of projects.

Within a short span of less than a decade, this company has made it mission and become one of the most reliable forces in the industry, by mobilizing they edge of technical expertise to transform every projects assigned into a benchmark of excellence.

2.3.2 Vision

Preserver Bina Sdn. Bhd. aims to keep getting better and stay ahead.

2.4 Company Organizational Chart




Diagram 2.1: Company Preserver Sdn. Bhd. Organizational chart

2.5 List of Projects

2.5.1 Projects On-going

Table 2.5.1 List of On-Going Projects

D:1	Duningt	Contract	Completion
Bil	Project	Value (RM)	Date
	Nilam Tekad Sdn. Bhd.		
	Proposed Developed The		30.04.2013
	Process Plant & Warehouse		
1.	At Jln. Sg. Pinang 4/2 Pulau	700,000.00	
	Indah Industrial Zone, Pulau		
	Indah, Klang, Selangor, Darul		
	Ehsan.		
	DRB-Hicom Defence		
	Technologies Sdn. Bhd		
	Proposed Upgrading Of	265,000.00	07.04.2013
2.	Manufacturing Maintenance		
	Repair And Overhaul (MRO)	203,000.00	
	And Office Facalities At		
	Deftech Pekan, Pekan,		
	Pahang Darul Makmur.		
	Defense Services Sdn. Bhd,		
	Nilai		
	Proposed Upgrading Pf		· ·
3.	Manufacturing Maintenance	183,000.00	29.03.2013
3.	Repair & Overhaul (MRO)	165,000.00	27.03.2013
	And Office Facalities At		
	DSSB Nilai, Negeri Sembilan		
	Darul Khusus.		
Bil	Project	Contract	Completion
וועו	Troject	Value (RM)	Date

	Datin Sri Azian bt.Abdul		
	Talib		
	Proposed To Build A 3 Storey		
	Bungalow House With		
4.	Swimming Pool At Pt 2995	550,000.00	01.03.2013
	And Pt 2669 (Lot 6056), Jln.		
	7 Kemensah Height, Mukim		
	Ulu Kelang, Daerah Gombak,		
	Selangor Darul Ehsan.		
	Hicom- Automotive		
	Manufacturers (M) Sdn.		÷
	Bhd.		
5.	Proposed Development	250,000.00	12.12.2012
	· Volkswagen Facilities for		
	Hicom Automotive, Pekan,		
	Pahang Darul Makmur		

Sources: Preserver Bina Sdn. Bhd. (2012)

2.5.2 Projects completed

Table 2.5.2 List of completed projects

D'1	Dusingt	Contract	Completion
Bil	Project	Value (RM)	Date
	Pentamaster Perlis		
	Northern Corridor Factory		
1.	Proposed Single Storey	RM 22.60	June 2011
1.	Factory On Plot, Taman	Million	June 2011
	Teknologi Pauh, Kurong Anai		
	District, Perlis.		
	APM Spring- Pendamaran		
	Proposed Development of		
	Single Storey Factory, with an		
2.	Electric Sub-Station, a	460,000.00	30.03.2012
	Sewage Treatment Plant, at		
	Jln Raja Lumu, Kg Baru		
	Perdamaran, Klang Selangor		
	Port Dickson Learning		
	Centre (PDLC)		
	Proposed Development		
3.	Learning Center At Lot 1888,	380,000.00	12.02.2007
	Mukim Pasir Panjang, Daeran		
	Port Dickson, Negeri		
	Sembilan, Darul Khusus.		

D'I	Dualizat	Contract	Completion
Bil	Project	Value (RM)	Date
	Management Science		12.01.2012
	University (MSU)		
	Proposed Construction At		
4.	MSU (Management Science	2,700,000.00	
4.	University) At No.4 Persiaran	2,700,000.00	
	Olahraga, Seksyen 13, 40100,		
	Shah Alam, Selangor, Darul		
190	Khusus.		
	Valser Oil & Gas Factory,		
	Nilai		30.12.2011
	Proposed Valser HQ Office		
5.	And Factory At PT 1082 (Lot	400,000.00	
3.	3), Nilai Utama, Mukim	400,000.00	
	Sentul, Daerah Seremban,		
	Negeri Sembilan, Darul		
	· Khusus.		
	Samudera Kimia Industries		
	Proposed Construction At		30.10.2011
6.	Open Warehouse At Pt		
	49766, Jln Lengkuk	200,000.00	
	Keluli 2 (KU2). Mukim		
	Kapar, Daerah Klang,		
	Selangor Darul Ehsan.		

D:1	Project	Contract	Completion
Bil	Project	Value (RM)	Date
	Auto Part Manufacturers		
	Co. Sdn.Bhd.		01.08.2011
	Proposed Construction For		
7.	Office Renovation At Lot	150,000.00	
/.	600, Jln Raja Lumu, Kws. 12,	130,000.00	01.08.2011
	Kaw. Perindustrian		
	Pendamaran, Pelabuhan		
	Klang, Selangor, Darul Ehsan.		
	Barny Callebaut Factory		
	Proposed Factory At Lot 2,		30.17.2011
8.	Lebuh Sultan Muhammed 1,	350,000.00	
0.	Kaw. Perindustrian Bandar	330,000.00	
	Sultan Sulaiman Pelabuhan		
45	Klang, Selangor, Darul Ehsan.		
	Sipro Plastic Industries Sdn.	:	
	Bhd.		
	Proposed Construction Office		
	And Factory At Pt 7422, Lot		25.05.2011
9.	9399, Jln. Jasmine, Kaw.	100,000.00	
9.	Perindustrian Bukit	100,000.00	
	Beruntung, Mukim Serendah,		
	Section 20, Daerah Hulu		
	Selangor, Selangor Darul		
	Ehsan.		

D.1	Duringt	Contract	Completion
Bil	Project	Value (RM)	Date
1.2	Madam Esther Ng		
	Proposed To Build 1 Unit Of		25.03.2011
10.	2storey Bungalow At No.13,	250,000.00	
10.	Jalan BK 6B/13, Banfar	250,000.00	
/	Kinrara, Puchong, Selangor		
	Darul Ehsan.		
	Madam Lai Shuh Bin		
	Proposed To Build 1 Unit Of		
	2 Storey Bungalow At Jalan		15.01.2011
11.	Setia Nusantara U13/22C,	320,000.00	
	Setia Eco Park, Section U13,		
	Shah Alam, Selangor Darul		
	Ehsan.		
	Proposed To Build 4 Units 3		
	storey Semi-Detached House,		
12.	Lot 27695, 27696, 27697,	550,000.00	04.03.2011
12.	27698, Taman Gembira, Jalan	330,000.00	04.03.2011
	Kuchai Lama, Petaling Jaya,		
	Selangor, Darul Ehsan.		
	Proposed To Build Bungalow		
	1 Storey Above Street Level		03.01.2010
12	Which Contains A Swimming	250,000.00	
13.	Pool And Guard House At	230,000.00	
	Lot 27978, Junction Tunku,		
	Bukit Tunku, Kuala Lumpur.		

Sources: Preserver Bina Sdn. Bhd. (2012)

CHAPTER 3

INSTALLATION OF STEEL JOINTING USING WELDING METHOD

3.1 Introduction



Image 3.1 Steel Structure

Steel are one of important elements in construction fields. It shares the same root of function for better infrastructure value, strong structure, simple and light weight within a building. As we know steel have various type of design, function and others. But, this report will only review on the method of steel installation such as welding.

Through the method mentioned above, the completeness and strength of steel structures can survive for a long time without affecting other civil structures. Besides, bolts and nuts this is the familiar use of the world market. While welding is a method that is simple, but there are also dangerous because it requires a safety device

especially the eyes and hands. This is because the rate of electrical welding using very high voltage and light or sparks fire can harm the eyes and other body parts.

In addition, this report will comprehensive guide to all aspects of welding or bolts and nut work from initial planning to finish work. This report will also come out with complete guidance and understanding the tools needed to be used in every aspect of procedure to get a proper installation of steel in site using welding.

3.2 Background of project



Image 3.2 Site Project

Project name is Preserver Bina Sdn. Bhd. This project which is to to "Propose to Developed Additional Factory from 'Oleo Chemical' that included the SME Dry Plant, cooling room, SME Wet, Storage & Tower Room, Pipe Rack, Hydrogenation 7 storey and ME Distallation 6 Storey" is located at Section 5, Fasa 2D, Pulau Indah Industrial Park, Jalan Sungai Pinang 5/18, 42920 Pulau Indah, Selangor, Darul Ehsan.

It is contain 1 block of single-storey warehouse including workshop, 1 block of single-storey warehouse with Mezzanine floor and 5-storey Tipping tower, 1 block of

4-storey Administration building, 1 unit of Canteen/ Surau/ and Driver's room, 2 unit of Guardhouse and Weighbridge, 1 unit of TNB (Tenaga Nasional Berhad) building, 1 unit of Effluent Treatment Plant block, 1 unit of Recycleable Material block, 1 unit of Effluent Treatment Material block, 1 unit of Natural Gas Storage, 1 unit of Hydrogen Gas Storage, 1 unit of Refuse Chamber, and last but not least Parking lot for car and motorcycles with roofing.

3.3 CASE STUDY

3.3.1 Welding work procedure

Detailed welding procedures for typical structural welding of plates, shapes and tubular members are to be established and qualified in accordance with the specified standards / codes for WPQ, the requirements of AWS shall prevail. All non-prequalified welding procedure shall be submitted for the Engineer's approval. Upon receipt of Engineers Approval, these welding procedures with the relevant test data are to be submitted for approval. Submission shall be made on standard "Request for Alternate Material or method of Construction" forms in triplicate. The procedures for qualification are to stimulate as far as is practicable, the conditions and materials to be used for production welding. Limitation imposed by the essential variable of the procedure qualification is to be adhered to in production welding. Parameters in welding procedures specifications. Welding Procedures Specifications (WPS) shall contain the following parameters:-

- a) Material specification of the base metal to be joined by welding
- b) Welding process, manual or machine
- c) Plate thickness range for which the procedure is approved
- d) Geometry of welding groove showing allowable tolerances including sketch
- e) Welding position and direction for vertical welding

- f) Filler metal specifications, composition and size
- g) Temperature and time adopted for drying and baking of welding consumables before use
- h) Gas shielding Flow, mixture, composition
- i) Number and arrangement of runs and weld dimensions (Sketch)
- j) Welding current, voltage polarity
- k) Travel speed or electrode run-out length for each pass and range
- 1) Back-gouging and method
- m) Pre-heat and inter pass temperature
- n) Post weld heat treatment
- o) Other variables as specified in AWS D1.1

The essential variables in WPQ is the welding procedure qualifications are to be set up as new WPS and be re-qualified when and changes in the essential variable list in AWS D1.1 are affected. Inspection of weld for WPQ test:-

- a) Dimensions of test pieces shall be sufficient to provide for all the required tests as per specified codes / standards or as per AWS requirements.
- b) The inspection and test shall be to the required specifications or in the absence of these specifications to AWS D1.1

Procedure Qualification Records is the specific facts from the WPQ and the test results are to be submitted to the endorsement and then to QA/QC section for documentation.


3.3.2 Welder qualifications

All welders and welding operators are to be qualified in accordance with the requirements of the specified standards / codes qualification will be to AWS specification for welders' qualification. Tests to AWS specifications will be as required in actual production works. No welders are to be allowed to proceed with production welding work on a specific project unless he had been qualified to weld on the project. Welders and welding operators are to be re-qualified to the specified standards /codes. The records of welders' qualification test, including a reference to the corresponding WPS and the test results are to be submitted to the QA/QC Person In charge for endorsement and to QA/QC section for documentation

3.3.3 Consumables

Consumables used for production welding are to comply with the following unless client's requirements differ in which case the client's specified. Handling of Electrodes and flux:-

Electrodes



Images 3.3.3 Electrode

Table 3.3.3 Electrodes Dry Condition

Electrodes Drying Conditions				
Electrodes Drying Temperature Keep Period				
E 6013	70° - 100°C	30 - 60 minutes		

Welding rods shall be used immediately after opening. If leaving in the air for a long time (more than 4 hours for low hydrogen type and more than 8 hours for another type), welding rod shall be dried up again. Re-drying of electrodes shall be no more than one time. Electrodes that have been wet shall not be used. Welders shall take out only such an amount of welding rods that they can use and put into a clean case. All Hermetically sealed electrodes shall be stored in a cool dry area and before being used, take care not to mistake the type of electrode.

Wire and Flux

When flux is collected, take care not to enter foreign material, such as rust, dirt, etc. Flux being left more than eight hours in the sir shall be dried up again. Rusted wire must not be used. Custody condition of welding rod:-

Temperature :

: 16° to 38° C

Humidity

: Less than 50%

3.3.4 Permissible Conditions For Welding

Welding work shall not be permitted under the following circumstances are atmospheric temperature is lower than O F (- 17.8 C), the surface of weld joint is wet, the surface of weld joint is exposed to rain or snow or strong wind, welders are exposed to a bad weather condition (Mainly inclement weather), weld joints are not preheated sufficiently, electrodes or flux are not dried sufficient.

3.3.5 Preparation For Welding



Figure 3.3.6 welder with the safety tools

For the first is cleaning of weld joint. Each weld joint shall be cleaned and free of foreign material such as paint, oil, rust, dirt, mill scale, slag, moisture, etc. Gasnotches and scale due to gas cutting shall be removed by wire—brush and grinder. Next is drying up of weld joint. The weld joints shall be dried up (by using gas burner, if necessary) before welding, and shall be kept in dry condition throughout welding operation.

3.3.6 Edge Preparation

Edge preparation surface shall be ground smooth. Tolerance of groove angle, root opening and misalignment of butt joint shall be in accordance with the specified standards/ codes. Root opening of fillet weld joints. Root opening shall be less than 1.5mm. In case root opening is 1.5mm to 4.5mm; leg length shall be increased equally.

3.3.7 Preheating

In the case of both tack welding and final welding by manual arc welding, the temperature for preheating shall be selected from the following table based on the thickness plate of weld joints. In case the temperature of base metal is lower than 41°F (5°C), the weld joint shall be preheated more than 70°F (21°C). Preheating the temperature are minimum and temperature above the minimum shown is required for highly restrained welds.

3.3.8 Tack Welding

Assembles of weld joints shall be aligned and held in place by tack welding. In the case of assembling of important strength members, it is desirable that strong backs instead of tack welding shall be fitted to maintain proper alignment of weld joint. Edge surface shall be always cleaned and free of oil, paint, rust, moisture, etc. Any defects by tack welding such as undercut, blowhole, crack, etc. shall be avoided. Qualification for tack welding technique is tack welding shall also be executed by the qualified welders (For high tensile & Special plates) as per item 2. The electrodes for tack welding where the electrodes having smaller diameter (4mm dia. or 3.2mm dia.) than the electrodes to be used for final welding shall be applied to tack welding.

For length and pitch of tack welding bead, especially for avoiding tack welds from rapid cooling and causing a defect, tack welding bead shall be intermittent – welded 30mm long minimum for mild steel and 50mm long minimum for high strength steel. Preheating shall be executed for tack welding. Refer to section 7 about the temperature for preheating.

3.3.9 WELDING SEQUENCE AND 'WAITING'

All weld joints shall be welded in sequence so as to let shrinkage due to welding heat escape from joint. Best welding sequence shall be considered in order not to restrain shrinking within the same plane. Weld joint considered as most shrinkage shall be welded in advance and less shrinkage joint shall be welded last.

3.3.10 EXECUTION OF BUTT WELDING

Tab pieces shall be fitted up at both ends of butt weld joints so as to avoid any defect that is apt to come out at the starting point and the terminal point of welding bead. Back running (root running) of butt weld joint by means of manual metal arc welding shall be done after back chipping as far as sound penetration appears. A crack and slag inclusion should not be developed.

Back chipping shall be done by means of arc-air gouging. Back chipped groove where slag remains shall be ground and wire-brushed so as to remove slag completely. Pay attention to avoid bending especially to butt weld joints. All slag of primary layer shall be removed completely, then the next bead shall be run. The height of reinforcement of weld shall be as follows:-

Table 3.3.10 The height of reinforcement of weld

Base Metal Thickness	Reinforcement (Max)
T < 9.5mm	2.4mm
T > 9.5mm	3.2mm

3.3.11 Repairing Of Other Defects

All weld defects such as slag inclusion, blowhole, insufficient fusion, overlap, etc. shall be removed by arc-air gouging and welded again. Electrodes for repair welding shall be less than 4mm in diameter. Preheating shall comply with the requirements. There are two of repairing of harmful uniform bead and reinforcement:-

(a) Acceptable weld bead

Reinforcement of weld (Excess metal) shall comply with section AWS D1.1. Excess metal height of welded bead shall be limited to the extent as stated in item (i) above. Ruggedness of welded bead height shall be within plus or minus 3mm. Roughness or welded bead height shall be within plus and minus 1mm.

- (b) Weld beads deviated from the above requirements shall be corrected be means of grinding, etc.
- (c) Weld bead having insufficient width or height shall be welded additionally where necessary. Applicable diameter of welding rods shall be less than 4mm dia.. Preheating shall comply with the requirements.

3.3.12 Acceptance Criteria

Acceptance Criteria are to conform to the specified standard codes.

3.3.13 Inspection



Image 3.3.13 Painting or Finishing


Inspection on all production weldment are to be carried out in accordance to Client's requirements. Usually client is really the welder do the finishers like the picture above.

3.3.14 Documentation

All welding inspection records whether in-house or third party is to be submitted to the QA/QC Person In charge for endorsement.QA/QC section shall collect the inspection records duly endorsed by the QA/QC Person In charge for filing in the Project Inspection File.


3.3.15 Tools of Welding





Images 3.3.16 SMAW

Diagram 3.3.16 SMAW system setup



Images 3.3.16.3 Electrode

Shielded metal arc welding equipment typically consists of a constant current welding power supply and an electrode, with an electrode holder, a ground clamp, and welding cables (also known as welding leads) connecting the two.



Figure 3.3.16.1 Welder

A welder or welder operator is a tradesman who specializes in welding materials together. The term welder refers to the operator, the machine is referred to as the welding power supply. The materials to be joined can be metals (such as steel, aluminum, brass, stainless steel etc.) or varieties of plastic or polymer. Welders typically have to have good dexterity and attention to detail, as well as some technical knowledge about the materials being joined and best practices in the field.



Image 3.3.16.2 Face cover



Image 3.3.16.4 Hand Cover

Welding are also need the safety equipment for a welder. As shown above, these are the several safety tools such as face cover and hand cover to avoid the spark from the welding process.

CHAPTER 4

CONCLUSION AND RECOMMENDATION

4.1 Recommendations

4.1.1 Provide a sufficient tools and machineries

A proper work of installation will definitely need a proper skill of labour and sufficient tools and machineries to do it. As we know all these tools will need to be sufficient enough to make a work become more easy and fast. This is because, not only the installation of work will requires the tools and machineries but some time the workers will be divided into two groups which is one for installation and the other one will need to do some repairing and modifying works if requires to do so. If the tools and machineries are not providing sufficiently enough therefore, all the works that should be complete early will be delayed or postpones.

4.1.2 Provide more workers, which half is for fabrication work and the other half is for site installation work

In this company, I'm aware that the time schedules for workers are not properly organized by supervisor due to lack of workers recruited. This company should be more aware and provide more workers with a proper time schedule work. As we know this kind of work will need a two group of workers which can be divided into fabrication work at factory and site installation work at site. So with a proper time schedule work and sufficient workers the installation work now can be more ease and without any problems.

4.2 Conclusion

As a conclusion, from this case study the writer can literally discuss the details information about installation of steel using the welding method are more better and tougher. As we know steel erection likely welding is one of important element in any kind of projects that's using steel structure. The main function of this element is to provide better and maintain of steel structure for a long time.

But to provide this kind of proper steel erection, components and elements will become the greatest factor that may affect the main function of steel. For an example, the skills of workers must be consider so that the quality is better. Meanwhile, selecting the material used for weld will give a long lasting durability against corrosion and corrupt. Therefore, with this report content I can understand more about components and elements which will be used for this specific type of steel erection.

Moreover, during the observations almost 5 months at site work, the writer learn that some problems related to our works may come from other people who does it purposely or not, but sometimes with improper installation work from our workers itself could also bring problems or damages towards steel joint or erection. However, this report will help to understand all these problems and solved it by how to use welding for steel erection as well.

REFERENCES

BOOK

Badron Jahiman, (2007). Teknologi Binaan Bangunan, Versi Pertama, Malaysia: Selangor.

Frick Heinz, (1980). Ilmu Konstruksi Bangunan 1, Indonesia: Yogyakarta.

Foster Jack Stroud, (1973). Structure and Fabric, Part 1, London: 4 Fitzhardinge Street.

INTERNET

Scott adams (1974), petervaldivia. January ,27,2012,from http://www.petervaldivia.com/eso/index.php


JKR(2007) Jabatan Kerja Raya Negeri Terengganu, Disember,29,2011, from http://www.jkr.terengganu.gov.my/index.php?mod=viewinfotek&id_itk=7


INTERVIEW

Pani (2010-now), Steel Engineer Department, Preserver Bina Sdn Bhd.

Iranawati (2009-now), Steel Engineer Department, Preserver Bina Sdn Bhd.

APPENDIX





GENERAL NOTES AND LEGENDS OF STEEL STRUCTURES

- 1. THE FABRICATION AND INSTALLATION OF STEEL TRUSSES UNDER THIS CONTRACT SHALL COMPLY WITH THE CONSTRUCTION SPECIFICATION.
- 3. STEEL SHALL BE SELECTED TO SATISFY THE BRITTLE FRACTURE REQUIREMENTS IN SECTION 2.4.4 OP BS 5890-12000 AT THE SPECIFED MINIMUM SERVICE TEMPERATURES. THE PLATE THOMMESS 2. STRUCTURAL STEEL MEMBERS AND PLATES SHALL BE NEW PRODUCTS OF BS 4380 GRADE STEEL TUBING SHALL COMPLY TO BS 1775. 43A AS SPECIFIED IN THE DESIGNDRAWINGS UNLESS NOTED OTHERWISE. STEEL PIPE AND
- 4. THE CONTRACTOR SHALL UNDERSTAND THE DESIGN DRAWINGS PRIOR TO THE BEGINNING OF THE WORK, IF THERE ARE ANY OUESTIONS OR INCONSISTENCIES ABOUT MEMBER SIZES FOR STEEL MATERIAL CLASS OF IMPACT PROPERTIES, REFER TO STEEL SPECIFICATION FOR STEEL GRADES WITH PRODUCER GUARANTEED CHARPY IMPACT VALUES SHALL NOT EXCEED THE MAXIMUM THICKNESS CALCULATED ACCORDING TO THE PROVISIONS OF BS5050-12000 SECTION 2.4.4
- PLAN, ELEVATION AND DETAIL, HE SHALL SUBMIT THE QUERIES TO THE ENGINEER FOR EXPLANATION OR REVISION.

5. THE CONTRACTOR SHALL COMPLY WITH THE CONSTRUCTION SPECIFICATIONS AND SUBMIT INTERPRETING THE DRAWINGS. THE CONTRACTOR SHALL BEAR THE FULL RESPONSIBILITY AS A CONSEQUENCE OF MS

THE SHOP DRAWINGS SHALL INCLUDE MEMBER SIZES AND LOCATIONS, CONNECTION DETAILS, MATERIAL SPECIFICATIONS, WELD SYMBOLS, HIGH-STRENGTH BOLTS, SIZES AND THE CONSTRUCTION DETAIL PLANS/SHOP DRAWINGS BEFORE COMMENGING THE WORK THE WERBER SIZES OF ALL STEEL GIRDERS AND STEEL MEMBERS SHALL BE CALCULATED FROM THE VERTICAL & TRANSVERSE SLOPES OF THE TRUSS, ELEVATIONS AND CAMBERS WELDING AND INSTALLATION FOR ENGINEER'S APPROVAL TYPES OF CONNECTING MEMBERS, AND CONTACT SURFACE WORK, ETC. THE CONTRACTOR SHALL ALSO SUBMIT THE ESTIMATE OF STEEL DISTORTION DUE TO THE CONTRACTOR SHALL SUBMIT THE SHOP DRAWINGS FOR ENGINEER'S APPROVAL

6. THE CONTRACTOR SHALL MAKE THE IMPROVEMENT PLAN TO PREVENT RESIDUAL STRAINS, DISTORTION SHRINKAGE AND DEFECT OF THE WELD. THE CONTRACTOR SHALL SUBMIT INSURE GOOD WELD QUALITY PRIOR TO BESINNING OF WORKS. ADEQUATE WELD METHOD, AND WELDING PROCEDURES FOR ENGINEER'S APPROVAL TO

7. THE CUTTING AND WELDING WORKS OF THE STRUCTURAL MEMBERS SHALL BE DONE IN THE MANUFACTURER'S WELL EQUIPPED FACTORY, PRIOR TO DELIVERING THE MEMBERS ENGINEER IN WRITING TO THE FIELD FOR INSTALLATION, FIELD WELDING IS GENERALLY NOT PERMITTED EXCEPT WHERE FIELD WELD SYMBOL. A. IS INDICATED IN THE DRAWING, OR IS APPROVED BY THE

8. WHERE DESIGN DRAWINGS INDICATE NO WELD SYMBOL AND WELD SIZE AT THE CONNECTION, CONTRACTOR SHALL MAKE THE WELDING DETAILS IN THE SHOP DRAWINGS COMPLYING TO THE CONSTRUCTION SPECIFICATION AND SUBMIT TO THE ENGINEER FOR APPROVAL BEFORE COMMENCING THE WORKS.

OVER 12M. THE PLATE CAN BE BUILT UP FROM TWO SHORT PLATES WITH ONE WELDED SPLICE CAN.Y. THE WELD SHALL BE PLACED AT ALTERWATE LOCATIONS TO AVOID PLATE SPLICE AT A PARTICULAR SECTION. THE CONTRACTOR SHALL SUBMIT CUTTING FLAN TO ® COMBINING TWO SHORT PLATES TO A SINGLE PLATE IS NOT PERMITTED. UNLESS OTHERWISE NOTED AS GROOVE WELD JOINT IN THE DRAWINGS. FOR PLATE WITH LENGTH ENGINEER FOR APPROVAL PRIOR TO THE BEGINNING OF WORKS

10. THE CONTRACTOR SHALL CONSIDER CONSTRUCTION SCHEDULE, CONSTRUCTION PROGRESS JOB SITE ENVIRONMENT, ROAD CONDITIONS, TRAFFIC MAINTENANCE AND WEATHER EFFECT. HE SHALL SUBMIT INSTALLATION DETAIL PLAN FOR ENGINEERS APPROVAL. THE PLAN SHALL INCLUDE DETAIL SHOP DRAWINGS AND GALCULATIONS OF MEMBER TRANSPORTATION.
STORAGE PLAN, INSTALLATION METHOD AND SEQUENCE, MECHANIC FUNCTION AND LOCATION. OF INSTALLATION, AUXILIARY SUPPORTS, AND CONSTRUCTION SAFETY PROTECTION

11. THE METHOD ON THE ASSEMBLAGE AND INSTALLATION OF THE TRUSSES SHALL BE DETERMINED BY THE CONTRACTOR WHICH DEPENDS ON THE FACTORS OF EQUIPMENT WEIGHT DURING INSTALLATION. IF CONTRACTOR USE ALTERNATIVE METHOD TO INSTALL THE BEGINNING OF THE WORK. DURING INSTALLATION, AND CAMBER CALCULATION FOR THE ENGINEER'S APPROVAL PRIOR AT SUFFICIENT INTERVALS TO CREATE NO STRESS IN THE MEMBER UNDER ITS OWN OF THE TRUSSES. CHORD MEMBER SHALL BE SUPPORTED BY THE TEMPORARY SUPPORTS GIRDERS OR NOTED OTHERWISE. TEMPORARY SUPPORT SHALL TAKE THE SELF-WEIGHT AND CAPACITY, DEAD LOAD CAMBER AND DEADLOAD STRESS IN THE DESIGN ARE CALCULATED ON THE FINISHED CONDITION OF THE TRUSS EXCEPT FOR THE COMPOSITE THE CONTRACTOR SHALL SUBMIT INSTALLATION PROCEDURES, MEMBER STRESSES

12. THE CONTRACTOR SHALL PAINT THE STEEL AND STRANDS COMPLYING TO THE CONSTRUCTION SPECIFICATION HE SHALL SUBMIT THE SPECIFICATION OF THE PAINT TO THE ENGINEER FOR PRIOR APPROVAL

13. ALL DIMENSIONS ARE IN MA UNLESS OTHERWISE NOTED IN THE DESIGN DRAWINGS.

14, ORDINARY BOLTS OF GRADE 4.6 AND GRADE 8.8 SHALL COMPLY TO BS 4190 HIGH-STRENGTH FRICTION GRIP BOLTS SHALLCOMPLY TO BS 4385.

15, CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF BS 5950

17, METHOD STATEMENT OF STEEL STRUCTURE ERECTION, DESIGN AND CALCULATION FOR 16, WELDING SHALL BE IN ACCORDANCE WITH THE LATEST APPLICABLE BS REQUIREMENTS RELATED TEMPORARY WORKS INCLUDING OA / OC PROCEDURES MUST BE SUBMITTED

ENGINEER'S REVIEW PRIOR TO PHYSICAL WORKS ON SITE.

18. DESTRUCTIVE AND NON-DESTRUCTIVE TESTS TO STRUCTURAL STEELWORKS IS DEENED INCLUDED IN THE STRUCTURAL STEEL FABRICATION SCHEDULE.

20. IN THE EVENT OF ANY CONFLICT OR INCONSISTENCIES BETWEEN THE STRUCTURAL STEEL SPECIFICATION AND THE PARTICULAR SPECIFICATION FOR STEEL STRUCTURE IN 19. FIRE PROTECTION REQUIREMENTS TO ALL STRUCTURAL STEELWORKS SHOULD STRICTLY COMPLY TO RELEVANT BRITISH STANDARD OR ARCHITECTURAL / BOMBA REQUIREMENT.

THE CONTRACT DOCUMENTS, THE PARTICULAR SPECIFICATION FOR STEEL STRUCTURE

ALL SECTIONS SHALL CONFORM WITH BS 4 AND BS EN 10034 UNLESS NOTED OTHERWISE
ABBREVIATIONS.

AND WITH PRICE COLUMN
UNIVERSAL BEAM
UC UNIVERSAL COLUMN
RSG ROLLED STEEL LOSE
RNG ROLLED STEEL LOSE
RNG ROLLED STEEL LOWSECTION
SHS RECTANGULAR HOLLOW SECTION
CHS CRULAR HOLLOW SECTION
RSA ROLLED STEEL MORE
GFA COLD FORMED MAGE
UNLESS OTHERWISE MOTE
FROW COMMINIOUS FILLET WELD
FROM FULL EPISHTRATION BUTT WELD
FOR CONTRACTOR OF THE PRICE FOR THE PRICE FO

PART PENETRATION BUTT WELD
SIZE OF PART PENETRATION BUTT WELD IN mm

22 MEMBER NOTATIONS. TOP LEVEL
TOP OF STEEL LEVEL
SETTING OUT POINT

LENGTH VARIES

BEAM, COLUMN CHANNEL AND JOIST UB 305 X 305 X 97 WEIGHT (kg/m)
 NOMINAL SIZE
 SECTION SHAPE

. UNLESS NOTED OTHERWISE ALL FILLET WELDS SHALL BE FULL PROPILE WITH A MINIAUM. LEG LENGTH OF 6mm. WELDING CONSUMABLES SHALL PRODUCE DEPOSITED WELD. METAL HAVING MECHANICAL PROPERTIES NOT INFERIOR TO THE MINIALOF THE PARENT METALS.

24. ALL WELDING IS TO COMPLY WITH BS EN 1011-1 AND BS EN 1011-2.

25. UNLESS NOTED OTHERWISE ALL BUTT WELDS SHALL BE FULL PENETRATION.

28. WELDERS SHALL BE TESTED IN ACCORDANCE WITH BS EN 287-1 APPROPRIATE TO THE TYPE OF WELDING THEY ARE REQUIRED TO PERFORM

27. JOINT DESIGNATION

1) SYMBOLS FOR JOINT TYPES

BIC	TC	BC	T	C	8
BUTT T- OR CORNER ICINT	T-OR CORNER JOINT	BUTT OR CORNER JOINT	INIOL-I	CORNER JOINT	BUTT JOINT

2) SYMBOLS FOR BASE METAL THICKNESS AND PENETRATION

UNLIMITED THICKNESS-COMPLETE JOINT PENETRATION	UNIL
LIMITED THICKNESS-COMPLETE JOINT PENETRATION	LIMI

3) SYMBOLS FOR WELD TYPES

10	9	00	7	O)	51	4	3	2	-
FLARE-BEVEL-GROOVE	DOUBLE-J-GROOVE	SINGLE-J-GROOVE	DOUBLE-U-GROOVE	SINGLE-U-GROOVE	DOUBLE-BEVEL-GROOVE	SINGLE-BEVEL-GROOVE	DOUBLE-V-GROOVE	SINGLE-V-GROOVE	SQUARE-GROOVE

4) SYMBOLS FOR WELDING PROCESSES IF NOT SHIELDED METAL ARC WELDING

SUBMERGED ARC WELDING GAS METAL ARC WELDING FLUX CORED ARC WELDING	F	G	s
	FLUX CORED ARC WELDING	GAS METAL ARC WELDING	SUBMERGED ARC WELDING

5) WELDING PROCESSES

SAW	FCAW	GMAW	AALCANO
SUBMERGED ARC WELDING	FLUX CORED METAL ARC WELDING	GAS METAL ARC WELDING	STIELDED METAL ARC WELDING

6) WELDING PROCESSES

VERTICA OVERHE	FLAT
ALL VERTICAL OVERHEAD	

a : NOT PREQUALIFIED FOR GAS METAL ARC WELDING USING SHORT CIRCUITING TRANSFER AND GTAW

MATERIAL STATES CONTINUES.

JOINT IS WELDED FROM ONE SIDE ONLY.

: CYCLIC LOAD APPLICATION LIMITS THESE JOINTS TO THE HORIZONTAL WELDING

 SMAW DETAILED JOINTS MAY BE USED FOR PREQUALIFIED GMAW : BACKGOUGE ROOT TO SOUND METAL BEFORE WELDING SECOND SIDE.

f: MINIMUM WELD SIZE(E) AS SHOWN IN 5.5 AS SPECIFIED ON DRAWING

(EXCEPT GMAW-S) AND FCAW.

h : DOUBLE-GROOVE WELDS MAY HAVE GROOVES OF UNEQUAL DEPTH, BUT THE g : IF FILLET WELDS ARE USED IN STATICALLY LOADED STRUCTURES TO REINFORCE GROOVE WELDS IN CORNER AND T-JOINTS, THESE SHALL BE EQUAL TO 1/4T1, BUT NEED NOT EXCEED 10mm, GROOVE WELDS IN CORNER AND T-JOINTS OF EQUAL TO 1/4T1, BUT NOT MORE THAN 10mm CYCLICALLY LOADED STRUCTURES SHALL BE REINFORCED WITH FILLET WELDS

DEPTH OF THE SHALLOWER GROOVE SHALL BE NO LESS THAN ONE-FOURTH

I : DOUBLE-GROOVE WELDS MAY HAVE GROOVE OF UNEQUAL DEPTH, PROVIDED OF THE THICKNESS OF THE THINNER PART JOINED. THESE CONFORM TO THE LIMITATIONS OF NOTE E. ALSO THE WELD SIZE (E)

THE ORIENTATION OF THE TWO MEMBERS IN THE JOINTS MAY VARY FROM 135 TO 180' FOR BUTT JOINTS OR 45' TO 90' FOR T-JOINTS. APPLIES INDIVIDUALLY TO EACH GROOVE.

k : FOR CORNER JOINTS. THE OUTSIDE GROOVE PREPARATION MAY BE IN EITHER

WELDING OPERATIONS WITHOUT EXCESSIVE EDGE MELTING. CHANGED AND ADEQUATE EDGE DISTANCE IS MAINTAINED TO SUPPORT THE OR BOTH MEMBER, PROVIDED THE BASIC GROOVE CONFIGURATION IS NOT

I : WELD SIZE (E) IS BASED ON JOINTS WELDED FLUSH.

m : FOR FLARE-V-GROOVE WELDS AND FLARE-BEVEL-GROOVE WELDS TO RECTANGULAR TUBULAR SECTIONS, r SHALL BE AS TWO TIMES THE WALL THICKNESS. : FOR FLARE-V-GROOVE WELDS TO SURFACES WITH DIFFERENT RADII 1, THE SMALLER 1

SHALL BE USED

8) WELDING SYMBOL

BASIC	BASIC WELDING SYMBOL	NBOL	ADC	ADDITIONAL WELDING SYMBOL	NG SY
TYPE	m	JOBWAS	7	NAME	SYMBO
SQUARE	SINGLE	-		The state of the s	1
GROOVE WELD	DOUBLE	+		DACKING BAK	+
V SHAPE	SINGLE	k		SPACER	4
GROOVE WELD	DOUBLE	*	T		1
BEVEL	SINGLE	K	WEL	WELD ALL AROUND	0
GROOVE WELD	DOUBLE	+	T		
J SHAPE	SINGLE	k	T.	LIELD MELD	1
GROOVE WELD	DOUBLE	+	CE	FLUSH	1
USHAPE	SINGLE	k	RFA		
GROOVE WELD	DOUBLE	*	su	CONVEX)
FLARE-BEVEL	SINGLE	K	ELD	CONCAVE	
GROOVE WELD	DOUBLE	+	w	CONCOVE	(
FLARE V SHAPE	SINGLE	K		CHISEL	C
GROOVE WELD	DOUBLE	76	RK		
FILLET WELD	SINGLE	7	wo	GRIND	G
	DOUBLE	∇	TRA	MILER	
PIUGORSI	DI WELD]	EXT		3
TOO ON OF ON MEETO	טו אינדנט		/ELD	HAMMER	I
BACK WELD	ELD	D	v	FREE	71

NSTRUCTION DRAWING

TO HEATHER The Party and Desired to

The same of

RSP Elightenne

PALINE MEDIA


DONG YANG


COIFFEE THE CONTRACTOR

BLC ME WHITE SEE


GENERAL NOTES STEEL STRUCTURE-1

ti . . (Dan b | man b .






3.0



TYPICAL BUTT WELD PREPARATIONS - FULL PENETRATION
THESE DETAILS ARE A TYPICAL SELECTION QNLY CONFORMING WITH THE RECOMMENDED PREPARATIONS
IN 85 5135. WELD PREPARATIONS SHOULD NOT BE DETAILED ON ENGINEERS DRAWINGS BUT ARE
REQUIRED ON WORKSHOP DRAWINGS


	REQUIRED ON WORKSHOP DR	AWINGS			411615	ROOT FACE
	WELD & SYMBOL	DETAIL	THICKNESS T	GAP G	ANGLE	RUUT FACE
-	OPEN SQUARE, BUTT	G	mm	mm.		m m
	TI I		0 – 3	0-3	_	-
			3 - 6	3		
		,				
	OPEN SQUARE BUTT BACKED	6 1	3 - 5	5		_
		4 T 1	5 - 8	8	-	-
			8 - 16	10		-
		3-6-	0 10	.0		
	SINGLE V BUTT	a				
	<u> </u>		5 - 12	2	60°	1
		R. T.	>	2	60°	2
	4		12	,	7	
-		Q				
	SINGLE V BUTT BACKED	Yammy I		6	45°	0
		G	> 10			
	- }	R+	10	10	20°	0
		3 mm MIN = Z mm MAX				* 8
-	DOUBLE V BUTT	Q — 2 min max				
		Y G Y				
		R + T }	> 12	3	60°	2
	{	There	12			
		Ta .				
1	ASYMMETRIC	Q 2T				
-	DOUBLE V BUTT	- ± 3 T				
		Z T	> 12	3	60°	2
- 1		Ma 4	12			
	1	<u>a</u>				
	SINGLE J BUTT					
	· 1	5/ T 5	> 20	-	20°	5
		R	20	,		
		5				
1	SINGLE U BUTT	<u>a</u> 1				
	1	VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	, 11			-
-		R + +5 T }	> 20	_	20°	5
	1					
}	SINGLE BEVEL BUTT					
1	SINGLE BEVEL BOTT					
1		S RI T	5 - 12	3	45°	1
	4		> 12	3	45	2
		G ,	12			
	DOUBLE BEYEL BUTT	⊢ a		40.01		
		R.L.	>	3	. 45	. 2
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	I TI	12			
		-G				
(


TYPICAL PREPARATIONS FOR HOLLOW SECTIONS





Welding positions

FILLET WELDS










GROOVE WELDS



FLAT POSITION


HORIZONTAL POSITION

Plates Vertical

VERTICAL POSITION


Plates Vertical






Plates Horizont

FLAT IG




Pipe Shall Be Turned or Rolled White Welding Axis of Pipe Horizontal

HORIZONTAL 2G




Axis of Pipe Vertical

5G POSITION



Pipe Shall Not Be Turned or Rolled While Welding Axis of Pipe Horizontal

6G POSITION



Inclined Axis With Pipe Stationary

