

PREDICTION OF CONSOLIDATION
FROM REDUCED CONSOLIDATION
TESTING TIME

MOHD HANAFFI BIN AYOP
(Advanced Diploma in Civil Engineering)

November, 1980

under the supervision of

(Mr. Muhammad Mahibul Alam)

SUBMITTED IN THE PARTIAL FULFILLMENT OF THE REQUIRMENTS
FOR THE AWARD OF ADVANCED DIPLOMA IN CIVIL ENGINEERING

CONTENTS

Acknowledgement

Preface

Notation Index

CHAPTER 1

1.1 Introduction

1.2 Literature review

CHAPTER 2

2.0 General Description

2.1 Scope

2.2 Soil Samples

2.2.1 Undisturbed Samples

2.2.2 Remoulded Samples

2.3 Laboratory Testing

2.4 Equipment/Apparatus

CHAPTER 3

3.0 Consolidation Theory

3.1 Consolidation and Settlement

3.2 Consolidation Model Concept

3.3 Dimensionality of Consolidation

3.4 Terzaghi's Theory of Consolidation

3.5 Basic components of Consolidation

CHAPTER 4

4.0 Consolidation Analysis

4.1 Estimation of Final Consolidation

4.1.1 Conventional One Dimensional Method

4.1.2 S.B Tan Method

4.2 Prediction of Secondary Consolidation from the
result of Primary Consolidation

ACKNOWLEDGEMENT

The author would like to convey his heartiest thanks to those who have helped to make this project worthwhile.

The author wishes to express his deep and sincere gratitude to Mr. Muhammad Mahibul Alam, project supervisor for his valuable guidance, keen interest in the work and encouragement throughout the preparation of this project. The author is highly in debt to Mr. Wan Mahmood B. Abd. Majid, Coarse Tutor in Civil Eng'g Department, for making available the facilities for carrying out this project.

Thanks are also extended to Mr. Shamsudin Awang and Mr. Mohd Som Marwi for fabricating the necessary equipment throughout the experimentation.

Lastly, the author would like to thank to his project partner, Mr. Nasuha Isa, for his cooperation and ideas throughout implementing of this project.

PREFACE

This experimental project describes the results of consolidation test carried out on two different nature of testing procedure, that is a 'reduced consolidation testing time' and 'normal consolidation testing time'. The correlation between the two said testing procedure is being determined. This is an attempt to make a study on possibility of reducing the normal consolidation testing time.

Properties of soil related to consolidation are being investigate and their relation to consolidation are being sought. The results of total consolidation using S.B TAN Method, which is a simpler approach for determination of total consolidation are being discussed.

Apàrt from consolidation test alone, the investigations also maãe used of the seive analysis test, hydrometer test, specific gravity test, atterberg limit test and moiture content test.

The sample used for this project are of disturbed sample taken from various boreholes at Kota Bahru, Kelantan and of undisturbed sample taken^{of} the compound of Sewage Plant, ITM.

CHAPTER 1

1.0 INTRODUCTION

The construction of any structures such as multi-storey buildings, bridges and dams ^{require} a thorough soil investigation prior to its construction. Soil investigation is hence necessary to be carried out in order for the Engineers to determine and designing appropriate and proper sub-structure. The degree of investigation required however depends on the importance of the building in term of money invested and its functionality.

The properties of the soil which chiefly required such investigation are those which govern its reaction to stress changes, therefore.

1. Strength of the soil (shear properties)

2. Consolidation properties

The investigation of shearing resistance (strength of soil) is mainly required for the analysis of stability whilst the study of consolidation is mainly importance to settlement problems.

Settlement is the most common reason for failure of foundations and it is therefore of great important to understand the mechanic of it. Soil are aggregates of mineral particles that cover extensive portion of earth surface. When forces are applied to such soil masses it produces a relative displacements between the particles. Such behaviour will determine the consolidation incurred or the settlement that a given structure will experience. The amount and rate of such settlement will depends on the nature of soil underlying such structures. For example, settlements of structures built above soft clay may take place slowly but may reach to a large magnitudes.