

CHARACTERISTIC OF FLEXURAL CRACKS IN REINFORCED  
CONCRETE BEAM UNDER LOW CYCLE DYNAMIC LOAD



BY:

MD RASUL MOHAMAD NOR  
SITIHAW A HAMZAH

JUNE 2006

## **ACKNOWLEDGMENT**

The authors would like to convey their sincerest gratitude to the management of Universiti Teknologi MARA (UiTM) and Institute of Research, Development and Commercialisation (IRDC) for providing the financial support, without which the work described herein would not have been possible. Technical assistance of Mr Mat Som Marwi, Mr Razman Arshad, Mr Zu Iskandar Kamarudin and Mr Burhanuddin Adnan, deserved the highest remark. Their endurance and experience had contributed immensely to the completion of the experimental. The special thanks also go to the final year degree students, Mohd Nazrul Afizan Isa, Mohd Ismade Ismail, Nooriman Mohamad, Ahmad Hamidi Abidin and Rosli Ngah who had been involved in this project from beginning.

# TABLE OF CONTENT

ACKNOWLEDGMENT	i
TABLE OF CONTENTS	ii
LIST OF ABBREVIATIONS	iv
LIST OF FIGURES	v
LIST OF TABLES	vi
ABSTRACT	1
CHAPTER 1: INTRODUCTION	2
1.1 Introduction	2
1.2 Problem Statement	4
1.3 Objectives	4
1.4 Scope of Work	5
CHAPTER 2: LITERATURE REVIEW	7
2.1 Introduction	7
2.1.1 Reinforced Concrete	8
2.1.2 Serviceability Limit States	8
2.2 Loading Type	9
2.2.1 Static Load	9
2.2.2 Dynamic Load	10
2.3 Elastic Theory for Stresses in Members Due to Flexure	11
2.3.1 Effective Modulus of Elasticity	11
2.3.2 Elastic Theory Assumption	12
2.4 Need of Deflection Control	14
2.4.1 Sensory Acceptability	14
2.4.2 Serviceability of the Structure	14
2.4.3 Effect on Non-structural Elements	15
2.4.4 Effect on Structural Elements	15
2.5 Calculation of Deflections	15
2.5.1 Immediate deflection	16
2.5.2 Long Term Deflection	18
2.6 Cracking in Reinforced Concrete Beams	21
2.6.1 Causes of cracking	22
2.6.2 Types of cracking	23
2.6.3 Factors affecting crack widths	24
2.6.4 Mechanism of flexural cracking	25
2.6.5 Evaluation of crack spacing and crack width	31
2.7 Conclusion	33

## **ABSTRACT**

Reinforced concrete has been widely used in Malaysian construction industry. Both residential and industrial buildings have been constructed using reinforced concrete and at present, many more high-rise structures are constructing with it. Dynamic load on reinforced concrete structure has been widely studied especially on bridges. However, with the recent seismic activity surrounding Malaysia's continent, it has been an interest to determine the dynamic response of reinforced concrete structure in building. This investigation focused on reinforced concrete beam of grade 30 with water cement ratio 0.3, tested under dynamic load influence. A total of 9 beams of size 125mm x 150mm x 1400mm were cast and tested. Deflections and crack patterns during serviceability and ultimate limits were investigated. The investigation shows that the beam deflected between 0.608 mm to 2.527 mm when subjected to 1 million and 3 million cycles during serviceability and ultimate limits. Flexural crack initiated at mid span both under static and dynamic load influence.

# CHAPTER 1: INTRODUCTION

## 1.1 Introduction

Cracking must be controlled and deflections must not be excessive for a concrete structure to be serviceable. The concrete structure must also not vibrate excessively to reduce the occurrence of cracking. Concrete shrinkage plays a major role in each of these aspects of the service load behaviour of concrete structures.

The design for serviceability is the most difficult and least well-understood aspect of the design of concrete structures. Service load behaviour depends primarily on the properties of the concrete and these are often not known reliably at the design stage. Moreover, concrete behaves in a non-linear and inelastic manner at service loads. The non-linear behaviour that complicates serviceability calculations is due to cracking, tension stiffening, creep, and shrinkage. Of these, shrinkage is the most problematic. Restraint to shrinkage causes time-dependent cracking and gradually reduces the beneficial effects of tension stiffening. It results in a gradual widening of existing cracks and, in flexural members, a significant increase in deflections with time.

The control of cracking in a reinforced or prestressed concrete structure is usually achieved by limiting the stress increment in the bonded reinforcement to some appropriately low value and ensuring that the stress increments after cracking and maximum spacing requirements for the bonded reinforcement. However, few existing code procedures, if any, account adequately for the gradual increase in existing crack widths with time, due primarily to shrinkage, or the time-dependent development of new cracks resulting from tensile stresses caused by restraint to shrinkage.