

Analysis of Grade of Service (GoS) In Mobile Communication Using GoS Calculator

This thesis is presented in partial fulfillment for the award of the
Bachelor of Engineering (Hons.) Electronics (Communication)

UNIVERSITI TEKNOLOGI MARA (UiTM)

SHAH ALAM, MALAYSIA

(JANUARY 2014)



**MOHD DANIAL BIN ROZAINI
FACULTY OF ELECTRICAL ENGINEERING
UNIVERSITI TEKNOLOGI MARA
40450 SHAH ALAM,
SELANGOR DARUL EHSAN
MALAYSIA**

ACKNOWLEDGEMENT

“In the name of ALLAH S.W.T, The Most Gracious and The Most Merciful. Peace be upon the Holy Prophet, Muhammad S.A.W.”

Alhamdulillah, with the help and guidance of the Al-Mighty, I have managed to produce this piece of work, despite of my own weakness and lack of design experience. I would like to take the opportunity to express my gratitude to my beloved supervisor Assoc. Prof. Norhayati Ahmad for her initial suggestions, advice, guidance and invaluable help throughout the development of the project. Special thanks to my father and mother for giving me the moral support, encouragement and financial support. I would also like to extend my thanks to my friends who have shared their knowledge and help me a lot in doing this project.

Thank you.

Mohd Danial Bin Rozaini
Faculty of Electrical Engineering
Universiti Teknologi MARA (UiTM)
Shah Alam, Selangor Darul Ehsan
Malaysia

ABSTRACT

This project implemented Grade of Service (GoS) calculator using MATLAB software in order to calculate the probability of a call being blocked or delayed. The aim of this project is to analyze the data that we get from the calculator by using three different formulas. The calculator used Erlang B formula to obtain the value of GoS and to get more accurate value; extended Erlang B formula was applied. From the calculated values, comparison between Erlang B and extended Erlang B was made. The probability that a call is queued and the average call waiting time, also known as the Average Speed of Answer (ASA) was calculated using Erlang C formula. The various values obtained from Erlang C calculator can tell how long subscribers need to wait before they can make a call during peak hours. All the calculated values were graphically plotted using Microsoft Excel.

TABLE OF CONTENTS

CONTENTS	PAGE
Declaration	i
Dedication	ii
Acknowledgement	iii
Abstract	iv
Table of Contents	v
List of Figures	viii
List of Tables	ix
List of symbols / Abbreviations	x
CHAPTER 1: INTRODUCTION	
1.1 Introduction	1
1.2 Background of study	
1.2.1 Grade of Service	1
1.2.2 Erlang B	2
1.2.3 Extended Erlang B	3
1.2.4 Erlang C	4
1.2.5 MATLAB GUIDE	5
1.3 Problem statement	7
1.4 Objective	7
1.5 Scope of work	8
1.6 Organization of thesis	8
CHAPTER 2: LITERATURE REVIEW	
2.1 Blocking probability	10
2.2 Dropped call	11
2.3 Heavy call traffic in peak hour	12
2.4 Increase in signaling load	12
2.5 Wrong configuration in mobile network	13

2.6	Possible solutions for improving the voice quality	
2.6.1	Increase the number of different route for same call	14
2.6.2	Call blocking performance of NRBCA scheme in cellular networks	14
2.6.3	NCPB in improved ADQOS for wireless multimedia communications using HCA	15
2.6.4	A channel allocation algorithm for hot-spot cell in wireless networks	16
2.6.5	Minimization of call blocking probability using auxiliary stations	17

CHAPTER 3: METHODOLOGY

3.1	Introduction	18
3.2	Flow chart	19
3.2.1	Research project	20
3.2.2	Design project	20
	3.2.2.1 Erlang B formula	20
	3.2.2.2 Extended Erlang B formula	21
	3.2.2.3 Erlang C formula	22
3.2.3	Graphical user interface	23
3.2.4	How does a GUI work	24
3.2.5	Procedure to create a GUI	26
3.2.6	GUI for Erlang B calculator	28
	3.2.6.1 Erlang B calculator coding	29
3.2.7	GUI for Extended Erlang B calculator	30
	3.2.7.1 Extended Erlang B calculator coding	31
3.2.8	GUI for Erlang C calculator	32
	3.2.8.1 Erlang C calculator coding	33