

**STRENGTH ANALYSIS OF DOWEL JOINTED  
RUBBERWOOD (*Hevea brasillensis*) CHAIR SIDE FRAME**

By

**MUHAMAD FAIRUZZAIRI B. ABDUL HAMID**

**Thesis Submitted in Partial Fulfillment Of the Requirement for the  
Degree of Bachelor of Science in Furniture Technology  
in the Faculty of Applied Science,  
Universiti Teknologi MARA**

**October 1999**

## ACKNOWLEDGEMENT

Syukur Alhamdulillah to Allah s.w.t cause of the strength and opportunity that You give to me in doing this study.

Grateful acknowledgement is also made to many people who have had a hand in the preparation of this thesis.

First of all, I would like to thanks Mr. Roslan B. Ali as my advisor, by giving me the procedure, encouragement and the related knowledge for this study, in order to produce good topic for academic usage.

To my entire buddy, I am really grateful to thank to all of you for your co-operation in completing this paper.

And not forgetting to my parents especially my mom, for their endless love and encouragement, I Love You.

## TABLE OF CONTENT

Acknowledgement.....	ii
LIST OF TABLES.....	v
LIST OF FIGURES.....	vi
LIST OF ABBREVIATIONS.....	vii
ABSTRACT.....	viii
ABSTRAK.....	ix
CHAPTER	
1 INTRODUCTION.....	1
2 LITERATURE REVIEW	
Finite Element analysis.....	3
Dowel Joint.....	6
Classification of Chair Support System and Variation of Load in These System.....	9
The Development of Performance Test Standard.....	16
Rubberwood.....	18
3 MATERIAL AND METHOD	
The Chair Model.....	20
Functional Static Loads acting on the Chair Model.....	21
Strength Analysis of the Chair Side Frame Using Finite Element Method.....	23
Dowel Pin Joint.....	26

4	RESULT AND DISCUSSION.....	32
5	CONCLUSION AND RECOMMENDATION.....	40
	REFERENCES.....	42
	APPENDICES.....	44
1.	a) Projected Availability of Rubberwood in Peninsular Malaysia from 1990-2000.....	45
	b) Projected Availability of Rubberwood Logs for sawing in Peninsular Malaysia for the Years 1990- 2000.....	47
2.	British Standard; B.S. 4875: Part 1: 1985, Strength and Stability of Furniture Testing.....	48
3.	Node Coordinate for ANSYS 50 Program with Different Location of the Stretcher.....	56
4.	Calculation of Dowel and Boring Dimension of the Test Specimen (T-type Withdrawal Strength Test)...	57

# **STRENGTH ANALYSIS OF DOWEL JOINTED RUBBERWOOD (HEVEA BRASILIENSIS) CHAIR SIDE FRAME**

By

**MUHAMAD FAIRUZZAIRI B. ABDUL HAMID**

OCTOBER 1999

The purpose of this study is to develop a method to analyze the strength impact of chair members with different load and location of stretcher. The main objective of this research are to determine stress in each element and the amount of rotation of each joint or mode by using Finite Element Method (FEM). The results showed that the critical moment occurs at the joint which is connected the back post to the seat. The loads that acting at the front post and seat are linearly increased when the position of the stretcher decrease, but, the load at the back post will decreased. This situation lead us to think that the most suitable stretcher position to support the maximum moment at the seat is, wherever possible to place it closely to the rail and as lower as possible to restrain the higher moment at the back post to the rail joint. From this analysis, we can optimize the dimension of each members form for ideal condition for furniture and optimize the condition of test with minimize design joint. Beside that, we also can determine or develop a method to analyze the strength impact of chair members with different load and location of stretcher, which can produce suitable and efficient design and shorter development times.