# DEPARTMENT OF BULDING FACULTY OF ARCHITECTURE, PLANNING AND SURVEYING UNIVERSITI TEKNOLOGI MARA (PERAK)

## **DECEMBER 2019**

It is recommended that the report of this practical training provided

 $\mathbf{B}\mathbf{y}$ 

## Muhammad Fakhrul Fu'ad Bin Amir Ridza

## 2017208798

## Entitled

## Plasterboard Gypsum Ceiling Finishes At Tijani Ukay, Ampang

be accepted in partial fulfilment of the requirement for obtaining the Diploma In Building.

Report Supervisor	: [En. Wan Akmal Zahri bin Wan Zaharuddin]
Practical training coordinator	: [En. Muhammad Naim Bin Mahyuddin ]
Program Coordinator	: [Dr. Dzulkarnaen Bin Ismail ]

## DEPARTMENT OF BULDING

## FACULTY OF ARCHITECTURE, PLANNING AND SURVEYING

## UNIVERSITI TEKNOLOGI MARA

(PERAK)

## **DECEMBER 2019**

#### STUDENT'S DECLARATION

I hereby declare that this report is my own work, except for extract and summaries for which the original references stated herein, prepared during a practical training session that I underwent at IDW Design & Build Sdn Bhd for duration of 20 weeks starting from 5<sup>th</sup> August 2019 and ended 20<sup>th</sup> December 2019. It is submitted as one of the prerequisite requirement of BGN310 and accepted as a partial fulfilment of the requirements for obtaining the Diploma In Building.

Name : Muhammad Fakhrul Fu'ad Bin Amir Ridza

UiTM ID No : 2017208798

Date :20<sup>th</sup> December 2019]

#### **ACKNOWLEDGEMENT**

Alhamdulillah, praise to Allah, the Most Merciful, the Most Graceful.

I would like to extend my heartfelt gratitude for the guidance, advice and help rendered through the period of training by the following group of amazing individuals. First and foremost, I would like to thank IDR. Lokman Hakim Ahmad Subki and IDR. Rabiatul Adawiyah Rasol for the opportunity given, to conduct my training in his esteem company. His team of professional comprising of Muhd Nur Asyraf Rasol and Atiqah Mohammad Hanfiah enabled me to learn and develop my skill, understanding, knowledge and feel real time in project. They are responsible toward streamlining and assessing my training. Also, I would like to thank all the UiTM lecturers that have taught and nurtured me in becoming a better student and person.

I would also like to thank my deepest appreciation to the lecturers who are directly involved during my training stint. To Mr. Wan Akmal Zahri Bin Wan Zaharuddin, Supervising Lecturer, Mr. Muhammad Naim Bin Mahyuddin, Practical training coordinator and Dr. Dzulkarnaen bin Ismail, programme chairman. I value the time, effort, encouragement and ideas that they have contributed toward the successful completion of my training, this report and the valuable knowledge that have been shared over the last few semesters.

Last but not least, my special thanks to my beloved parents for their sacrifices over the years.

Thank you so much.

i

#### ABSTRACT

Malaysia is one of the developing countries. Building construction is the process of constructing a building or infrastructure and typically involves mass production of similar items without a designated purchaser, while construction typically takes place on location for a known client. This report presents summary of research project for plasterboard gypsum ceiling finishes at Residential Tijani Ukay, Ampang. The prime objective of ceiling finishes is to make sure that the performance of the building can be continued to the most throughout its design life plus to give aesthetics value for interior building. The objectives of this report is to identify the construction method of plasterboard ceiling and determine the equipment and machineries that used for construction. The method of study used are interview, case study and literature review that sure helped a lot in making this report. To illustrate, the construction industry makes a vital contribution to the competitiveness and prosperity of the economy. A modern and efficient infrastructure is a key driver of productivity, and the construction industry has a major role in delivering the built infrastructure in an innovative and cost effective way.

# TABLE OF CONTENTS

Acknowledgement
Abstractii
Table of contentsiii
List of tableiv
List of figuresv
List of appendixvi
CHAPTER 1.0 INTRODUCTION
1.1 Background and Scope of Study2
1.2 Objectives
1.3 Methods of Study
CHAPTER 2.0 COMPANY BACKGROUND4
2.1 Introduction of Company
2.2 Company Profile
2.2.1 Company Director
2.2.2 Company Address
2.2.3 Company Detail
2.2.4 Company Location Plan
2.2.5 Company Vision
2.2.6 Company Mission
2.2.7 Official Logo & Symbol
2.3 Organization Chart
2.4 Site Organization Chart
2.5 List of Projects
2.5.1 Complete Project
2.5.2 Project in Progress
CHAPTER 3.0 CASE STUDY
3.1 Introduction of Project
3.1.1 List of Consultant

3.2	Case Study	18
3.2.1	Plasterboard gypsum Ceiling	18
3.2.2	Tools And Equipment	24
3.3	Method Statement	32
CONC	CLUSION 4.0	43
4.1	Conclusion	43
REFE	RENCES	.45
APPE	NDIX	46

# LIST OF TABLE

	Page
Table 2.0: Completed project	11
Table 2.1: Project in progress	12
Table 3.0: Ongoing projects	14
Table 3.1: Grand total renovation works	15
Table 3.2: List of consultants	16
Table 3.3: Bill of quantities	19

# LIST OF FIGURES

	Page
Figure 1.1 : Ceiling finishes component	1
Figure 2.1.2: IDW Design & Build Sdn Bhd staff	4
Figure 2.1.2: Scope of design	6
Figure 2.2.1: Location Headquarter	7
Figure 2.2.2: Future IDW Headquarters	8
Figure 2.2.3: Company Logo	10
Figure 3.1.1: View with client	13
Figure 3.1.2: Site location	14
Figure 3.2.1: Plasterboard gypsum ceiling construct area	18
Figure 3.2.2: Installing ceiling	20
Figure 3.2.3: Plaster of Paris	21
Figure 3.2.4: Wallboard	22
Figure 3.2.5: L-box	23
Figure 3.2.6: Beam laser	24
Figure 3.2.7: Screw	24
Figure 3.2.8: Putty trowel scraper	25
Figure 3.2.9: Plaster trowel	25
Figure 3.2.10:Plaster tray	26
Figure 3.2.11:Mild steel framing	26
Figure 3.2.12:Tray	26
Figure 3.2.13:Stopping compound	27
Figure 3.2.14:Cordless screwdriver	27
Figure 3.2.15:Side cutting pliers	28
Figure 3.2.16:Measuring tape	28
Figure 3.2.17:Spirit level	29
Figure 3.2.18:Carpenter pencil	29
Figure 3.2.19:Frame scaffolding	30
Figure 3.2.20:Plasterboard saw	30
Figure 3.2.21:Marking string line	30
Figure 3.2.22:Paint tray	31
Figure 3.2.23:Roller paint	31
Figure 3.3.1 :Floor covering process	32
Figure 3.3.2 :Dismantle existing plasterboard	33
Figure 3.3.3 :Determine floor level using beam laser	34
Figure 3.3.4 :Beam laser	34
Figure 3.3.5 :Ceiling framework	35
Figure 3.3.6 : Ceiling component	36
Figure 3.3.7 : Tying channel and hanger	37
Figure 3.3.8 :Installing plasterboard	38
Figure 3.3.9 :6" x 8" 1-box	39
Figure 3.3.10:Gap between plasterboard	39
Figure 3.3.11:Mixing compound and water	40
Figure 3.3.12: After completed filling the gap with stopping compound	40

Figure 3.3.13:Paint used for ceiling	41
Figure 3.3.14: Applying paint on ceiling	42
Figure 3.3.15:Celing is completely constructed	42

# LIST OF APPENDIX

	Page
Appendix A: Master layout plan (ground plan)	47
Appendix B: Master layout plan (first floor)	48
Appendix C: Master layout plan (second floor)	49
Appendix D: Reflected ceiling plan (ground floor)	50
Appendix E: Reflected ceiling plan (first floor)	51 52
Appendix F: Reflected ceiling plan (second floor)	53
Appendix E: Plug point plan (ground floor)	54
Appendix G: Plug point plan (first floor)	55
Appendix H: Plug point plan (second floor) Appendix I: Wall finishes plan (ground floor)	56
Appendix J : Wall finishes plan (ground floor)  Appendix J : Wall finishes plan (first floor)	57
Appendix K: Wall finishes plan (second floor)	58
Appendix L: 3D design	59
Appendix M: After construction	72

## **CHAPTER 1.0**

#### **PREFACE**

#### 1.1 INTRODUCTION




Figure 1.1: Ceiling finishes component

Finishing materials improve the appearance of buildings. There are different types of finishes and methods applied during the construction process of a house, residential, commercial building or any type of building projects.

Perhaps the best way to define building finish is to say that it comprises those nonstructural parts of the building. The finishes are divided into EXTERIOR finish (located principally on the outside of the structure) and INTERIOR finish (located inside). The work involved in the installation of nonstructural members on the structure is called finish carpentry(Blakemore & J.Wiley, 2006)

A ceiling is an overhead interior surface that covers the upper limits of a room. It is not generally considered a structural element, the ceiling finish or product

is attached to the ceiling battens under the roof framing and is generally a plasterboard of some form. Typically, we see ceilings as the flat plane above us that hides the roof or floor framing (Clive Edwards, 2005). They are usually made of plasterboard on a light timber frame attached to the roof or floor framing.

There are many types of ceiling finishes that can be used such as plasterboard, suspended ceiling, ply and batten ceiling. So the architect must choose wisely. Architect must know whether the chosen ceiling finishes is suitable with the environment, temperature and use of the space. This report will explain detail about the plasterboard ceiling for the ceiling finishes.

#### 1.2 OBJECTIVE

The objectives of this report are as follow:

- i. To explain the definition of gypsum plasterboard in ceiling finishes.
- ii. To identify machineries and equipment that is being used in the ceiling installation.
- iii. To investigate the method of construction for ceiling finishes.

#### 1.3 SCOPE OF STUDY

In this report, it will present about finishes. The case study for this report was located at one of the main purpose for this report that will be represented in this report is the method of installation for finishes at ceiling until completion. Secondly, this report will give some knowledge about the material of the finishes and the conformity of the material with the area.

#### 1.4 METHOD OF STUDY

Various methods are used to obtain information for completing the Practical Training Report. The methods used are as follows:

#### 1. Observation

Overall methodology of this report is actually based on observations conducted while at the construction site. Observations that have been made are recorded and photographed as evidence while doing a report. Observations are done on site with me taking the view and snapped every parts in the phone and notes are made. This method is also able to know the ways and methods of work done at construction site.

#### 2. Interview

Interviews are a very efficient and effective way to get information effectively. Interviews will be conducted by the experienced employees and staff. This is because they have a lot of knowledge and experience work at construction site as site supervisor. The interview is one of the direct ways to get more useful information from the respondents interviewed. Such as to interview directly the workers for around six to seven minutes for each methods.

#### 3. Books

Book is a very useful to get knowledge and information available about construction work. This is because the information contained in the book is more relevant information and cannot change the truth information that have contained at the books. The information in the book can provide some guidelines to complete the Practical Training Report successfully

#### 4. Internet

Internet is one of the easiest and quick ways to obtain the necessary information and info. By just surfing the internet and open a web page that is required, the information actually can be obtained quickly and accurately depending with other ways to get information

## **CHAPTER 2.0**

# COMPANY BACKGROUND

# 2.1 INTRODUCTION OF COMPANY





Photo 2.1.1: IDW Design & Build Sdn Bhd staff Source:IDW Design & Build Sdn Bhd

IDW Design & Build Sdn Bhd was established in 2006 and was formerly known as INFINITE DESIGNWORK. IDW Design & Build Sdn Bhd is an interior design company that focuses design excellence through responsible development and technological innovation. A unique skill base enables the company to achieve success in various commissions.

As an Associate Member of Malaysian Society of Interior Design (MSID) and Malaysian Institute of Interior Design (MIID), IDW is committed to promote legal practice of interior design and support the environmentally sustainable transformation in every project we undertake.

The way IDW Design & Build Sdn Bhd work is in innovative concepts enabling the creation of an optimal standard of living with and inside the structure that has been designed. The design is not as an end for itself, but serve the needs of human beings. IDW Design & Build Sdn Bhd consist of staffs and teams that enable the composition of creative, innovative and communicative individuals who share a fascination for their work, and a readiness to become emotionally involved with each project as it develops. Meeting the daily challenge of competition, in both large-scale and small-scale context and succeeding in work only possible with a team that is capable of enthusiasm, and which is built on a basic of friendship and mutual trust.

IDW Design & Build Sdn Bhd provides professional interior design service covering the below scope of work:

- a) Clients meeting for design requirement
- b) Conceptualization and schematic design for design development
- Presentation to client using computer aided colour visual perspective, shop drawing and cost estimations.
- d) Tender documentations and calling of tenders
- e) Project management and administrations. Project weekly meeting, inspection to completion.
- f) Defect checking.
- g) Project hand over.

- h) IDW Design & Build Sdn Bhd role include:
- a) Institutional building
- b) Urban design
- c) Commercial office
- d) Industrial developments
- e) Niche residential design
- f) Hospitality









Photo 2.1.2 : Scope of design Source: IDW Design & Build Sdn Bhd

## 2.2 COMPANY PROFILE

# 2.2.1 Company Director

- IDR Lokman Hakim Ahmad Subki
- IDR Rabiatul Adawiyah Rasol

## 2.2.2 Company Address

• IDW DESIGN & BUILD SDN BHD NO 36A, JALAN KRISTAL J7/J, SEKSYEN 7, 40000 SHAH ALAM , SELANGOR

## 2.2.3 Company Detail

Company Name : IDW DESIGN &BULD SDN BHD

Telephone :

Email : <u>hello@idw.design</u>

# 2.2.4 Company Location Plan




Figure 2.2.1: location headquarters Source: googlemap.com

## 2.2.5 Company Vision

Towards quality driven, hundred million interior design company in Malaysia. IDW ethos, is driven by the pursuit of a profound bespoke interior design, impeccable project management and utmost satisfaction of clientele.

## 2.2.6 Company Mission

Our success is to enhance client experience with continuous and profound professional project management that ensure IDW remain at the forefront in bespoke interior design industry.




Figure 2.2.2: Future IDW headquarters Source: IDW Design & Build Sdn Bhd

To become Asia largest interior design service provider who set up Asia's yearly design trend from their own design magazine brand "posh" and furniture store "IDW designer warehouse" as enters year of 2026.

## 2.2.7 Official Logo & Symbol




Figure 2.2.3: Company logo Source: IDW Design & Build Sdn Bhd

## IDW symbol:

IDW itself intends as Infinite Design Work. It refers to a quantity without bound or end. People have developed various ideas throughout history about the nature of infinity.

#### 2.3 ORGANIZATION CHART



## 2.4 LIST OF PROJECTS

# 2.4.1 Completed Project

Table 2.0: Completed project

NO.	CLIENT	LOCATION	AMOUNT
1	Feiyue International Ltd.	Suite 7.04, Level 7, Wisma Goldhill, No. 67 Jalan Raja Chulan 50200 Kuala Lumpur.	RM 273,143.41
2	Sabrina Bakery Sdn. Bhd	Jalan PJS 3/34 Taman Sri Manja, 46000 Petaling Jaya, Selangor.	RM 52,464.33
3	Stealth Solution Sdn Bhd	Unit B - 3a - 01, Arena Mentari, No 1, Jalan Pjs 8/15, Dataran Mentari, Bandar Sunway, 46150 Petaling Jaya, Selangor	RM 350,572.83
4	Al – Hijrah Media Corporation	Kompleks Pusat Islam Malaysia 50480 Kuala Lumpur.	RM 895,980.74
5	Silawati's Residence	No. 3, 10 Residensi, Jalan Senangin 2c, Seksyen 17, Shah Alam.	RM 310,131.28

Source: Source: IDW Design & Build Sdn Bhd

## 2.4.2 Project in Progress

Table 2.1: Project in progress

NO.	CLIENT	LOCATION	AMOUNT
1	Shazlina's Residence	No. 7, PJU 7/19 Mutiara Damansara, 47800 Petaling Jaya.	RM 261,416.39
2	Farhani's Residence	No. 50, Jalan Elektron U16/75, Denai Alam, 40160 Shah Alam, Selangor.	RM 210, 611. 70
3	Amir's Residence	No. 14, Jalan Gunung Nuang U11/39, Seksyen U11, Bukit Bandaraya, 40170 Shah Alam.	RM 216, 648. 60
4	Saliza's Residence	No. 7, Jln Awan Larat U8/74, D'Puncak, Bukit Jelutong, 40150 Shah Alam, Selangor.	RM 117,000.00

Source: Source: IDW Design & Build Sdn Bhd

## **CHAPTER 3.0**

## **CASE STUDY**

## 3.1 INTRODUCTION OF PROJECT

IDW Design & Build Sdn. Bhd. is currently executing a renovation project which is proposed new interior design for Tijani Ukay, Ampang that is Mr. Shahrizal's office and covered on design area such as bedrooms, wet and dry kitchens, dining area, living area. This project is located at No 1, Jalan Tijani 3/B, Taman Tijani Ukay, 68000 Ampang, Selangor. IDW Design & Build Sdn. Bhd commenced this renovation project on 18<sup>th</sup> September 2019 and expected to complete the project referring to master work program by month of 15<sup>th</sup> November 2019. The total cost for the renovation works for this project is approximately RM613,00,00 not including special request or variety order by client.



Photo 3.1.1: View with client



Figure 3.1.2: site location Source: googlemap.com

These are the descriptions for the ongoing projects:

Table 3.0: ongoing project

NO.	CLIENT	LOCATION	AMOUNT
1	Shazlina's Residence	No. 7, PJU 7/19 Mutiara Damansara, 47800 Petaling Jaya.	RM 261,416.39
2	Farhani's Residence	No. 50, Jalan Elektron U16/75, Denai Alam, 40160 Shah Alam, Selangor.	RM 210, 611. 70
3	Amir's Residence	No. 14, Jalan Gunung Nuang U11/39, Seksyen U11, Bukit Bandaraya, 40170 Shah Alam.	RM 216, 648. 60
4	Saliza's Residence	No. 7, Jln Awan Larat U8/74, D'Puncak, Bukit Jelutong, 40150 Shah Alam, Selangor.	RM 117,000.00

Source: Source: IDW Design & Build Sdn Bhd

The description of renovation total cost is stated below:

Table 3.1: Grand total renovation works

	Project:		
	PROPOSED NEW INTERIOR DESIGN FOR RAHIMAH'S	KE2IDENCE	
	MAIN WORKS		
		Date:	4 FEB 2019
		Ref. No.:	IDW/RR/BQ/REV00
		Revision:	4
		Copy for:	Client/Contractor
TEM	DESCRIPTION	NO.	AMOUNT (RM)
	General Notes		
	The description stated in the Bills of Quantities are not comprehensive		
	and reference shall be made to;		
	Specification of Materials and Workmanship     General Conditions and Preliminaries and		
	3) Preambles/ Method of measurement	I	
	The rates and prices inserted shall be deemed to have allowed for		
	compliance with the above stipulation and other documents forming part of the Contract.		
Α	WORK SUMMARY		
1	ID WORKS		444,212.7
	TOTAL ID WORKS		444,212.7
В	PROJECT MANAGEMENT CONSULTANT (PMC) FEES		
1	The service rendered by the consultant is 10%. Final services fees will be	1007	44 401 0
	prior upon completion of project final account.	10%	44,421.2
2	Design Package Paid		(5,000.0
	ST	6%	2,665.2
	TOTAL ID FIES		42,086.5
	TOTAL MAIN ID WORK +ID FEES	STUDIO CONTROL	486,299.2


Source: Source: IDW Design & Build Sdn Bhd

## 3.1.1 List of Consultant

Table 3.2: List of consultants

No	Consultant	Company name	Address
1	Client/owner	Tuan Mohamad Shahrizal Bin Mohammadn Idris	No 1, Jalan Tijani 3, Tijani Ukay, 68000 Ampang, Selangor
2	Interior design consultant	IDW Design & Build Sdn Bhd	No 36a, jalan kristal j7/j, seksyen 7, 40000 shah alam, selangor
3	Contractor	IDW BUILDER	No 36a, jalan kristal j7/j, seksyen 7, 40000 shah alam, selangor

Source: IDW Design & Build Sdn Bhd



#### 3.2 CASE STUDY

## 3.2.1 Plasterboard gypsum Ceiling

In general, plaster is a building material used for the protective or decorative coating of walls and ceilings and for moulding and casting decorative elements. In English "plaster" usually means a material used for the interiors of buildings, while "render" commonly refers to external applications. Plaster can be relatively easily worked with metal tools or even sandpaper, and can be moulded, either on site or to make pre-formed sections in advance, which are put in place with adhesive. Plaster is not a strong material; it is suitable for finishing, rather than load-bearing, and when thickly applied for decoration may require a hidden supporting framework, usually in metal. The plaster is manufactured as a dry powder and is mixed with water to form a stiff but workable paste immediately before it is applied to the surface. The reaction with water liberates heat through crystallization and the hydrated plaster then hardens. (Gillian Perry, 1999)

Plasterboard gypsum ceiling has been designed to construct on all area and there is specific area which living room and dining area that include a structural element which is l-box. Refer to the reflected layout plan which that indicates ceiling design and lighting points (refer appendix D)




Figure 3.2.1: Platerboard gypsum ceiling construct area

Arrows indicate the 1-box mentioned shaped square and rectangle following the T5 lamp in the reflected ceiling plan. L-box is located at the dining & living area. What is L-box? L-box is light holder which usually used for boundary of room or to terminate section of the drop ceiling. The cost is computed by per foot run.

Table 3.2: bill of quantities

	Charles and the second state of the second			The second second
2 To supply & install light box.	ft/run	75.00	14.40	1,080.00
	Production of the last of the			

Basically, most of the plaster types, they all work in a similar way. There are several common types of plaster in market which is gypsum

#### 1. GYPSUM PLASTER



Figure 3.2.2: Installing ceiling

For this project, gypsum plaster is used for the entire ceiling finishes. Gypsum is used for various purposes, this hemihydrate gypsum became known as PLASTER OF PARIS. Upon addition of water, after a few tens of minutes plaster of paris becomes regular gypsum (dehydrate) again, causing the material to harden for casting in construction. Plasterers often use gypsum to simulate the appearance of surfaces of wood, stone, or metal, on movie and theatrical sets for example. Nowadays, theatrical plasterers often use expanded polystyrene, although the job title remains unchanged. Plaster of Paris can be used to impregnate gauze bandages to make a sculpting material called plaster bandages. It is used similarly to clay, as it is easily shaped when wet, yet sets into a resilient and lightweight structure. This material is widely used for construction compared with lime plaster.



Figure 3.2.3: Plaster of paris Source: googlemap.com

There are benefits of using gypsum plaster which is for builders and developers or for end customer:

## 1. FOR BUILDERS AND DEVELOPER:

- a. Green material
- b. Shrinkage crack free surface (smooth finish)
- c. High productivity which is reducing plastering time by 70%
- d. Reduce dead load on structure
- e. Durable and light weight
- f. Cleaner site because direct application bagged product and requires no curing

## 2. FOR END CUSTOMERS:

- a. No shrinkage crack on wall or ceiling
- b. Reduction in the time required for plastering
- c. Perfectly lined, levelled, smooth surface
- d. Saving on electricity used for air conditioning as gypsum has very low thermal conductivity.

Next, plasterboard ceiling is a rigid composing a gypsum sandwiched between durable lining paper outer facing. For ceiling applications, the following types can be used to add aesthetic value:

## i. WALLBOARD

9.5, 12.5 and 15 mm thickness 900 and 1200 mm width and lengths of 1800 and 2400 mm. Longer boards are produced in the two greater thickness and a vapour check variation is available. Edges are either tapered for taped and filled joints for dry lining or square for skimmed plaster or texture finishes. (Roy Chudley 2014)



Figure 3.2.4: Wallboard

To deduce, these are the same type specification of gypsum plaster board that has been used for construction in this site. Plasterboard should be fixed breaking joint to the underside of floor or ceiling joists with zinc plated (galvanised) nails or dry — wall screws at 150 mm max. spacing. The junction at ceiling to wall is reinforced with glass fibre mesh scrim tape or a preformed plaster moulding.

## ii. L-BOX

There are primary benefits attribute to the l-box which is the first is aesthetic because l-box improves on the attractiveness of any interior space. The second is related to the air conditioning where l-box reduces the overall volume in the room leading to significant energy cost. Although having l-box installed may be expensive. But the costing depends largely on design, and there are designs that are more affordable.





Figure 3.2.5: L-box

# 3.2.2 Tools And Equipment

Table 3.4: table tools and equipment

NO	EQUIPMENT/PLANT	FUCTION
1	Figure 3.2.6: Beam laser	As a benchmark to set the ceiling level
2	Figure 3.2.7: Screw	To tie object with cordless screwdriver






8 compound that use to fill in gap on plasterboard ceiling Figure 3.2.13: Stopping compound 9 Tighten screws to a specified torque without damage or over-tightening Figure 3.2.14: Cordless screwdriver



12		Used to check horizontal level in brickwork, plastering, flooring.
12	Figure 3.2.17: Spirit level	
13	NOS-I-NOOM SARPING TO * NACIENING PENCIL * 1006 IN	For marking purpose
	Figure 3.2.18: Carpenter pencil	

	Use when working at height.
Figure 3.2.19: Frame scaffolding	To cut off plasterboard by piece.
Figure 3.2.20 : Plaster board saw  Figure 3.2.21: marking string line	Temporary marking to set up ceiling framework.



#### 3.3 METHOD STATEMENT

This is method statement installation of plasterboard ceiling at Mr. Shahrizal's Residence located at No.1, Jalan Tijani 3/B, Taman Tijani Ukay, 68000 Ampang, Kuala Lumpur.

#### **STAGE 1: FLOOR COVERING**



Figure 3.3.1: Floor covering process

Before ceiling works are constructed, there is preliminary work needs for execution at first which is floor covering. For this project, canvas with 45 feet long is used as a floor covering. Two rolls of canvas are used to cover up the whole construction area. This step is taken to reduce the risk of damaging and to protect client's property because of renovation work by contractor. This process takes 1 day to complete with 2 general workers. The installation method for floor covering is canvas is lay on the ground roll to the end of the area. By using a paper cut, canvas is cut at the end and taped using masking tape to avoid canvas from moving or removed.

# STAGE 2: DEMOLISHING AND DISMANTLE PLASTERBOARD CEILING

Next stage is demolishing and dismantle phase, existing plasterboard gypsum ceiling need to be demolished and dismantled due to changes on design for this area. There are two items need to be demolished which are mild steel framing and existing plaster board ceiling. This process takes two days and three manpower which are 1 ceiling fixer and 2 general worker and equipment or tools used in this process are plasterboard saw, side cutting pliers, claw hammer.



Figure 3.3.2: Dismantle existing plaster board

Dismantle method for plasterboard gypsum ceiling is by using plasterboard saw, plasterboard ceiling is cut by piece to easier for the worker to demolish the ceiling. Next, mild steel framing is dismantled follow the design that been proposed by using side cutting pliers.

## STAGE 3: LEVELLING FOR CEILING INSTALLATION



Figure 3.3.3: Determine floor level using beam laser

After that, whole ceiling in the area needed to be at the same level to let air-cond concealed and wiring get the some space to let maintenance work. To get the ceiling precisely levelled, the ceiling needs to be leveled by beam laser and marking with string line. This process takes 1 day to complete with 2 manpower which are 1 ceiling fixer and 1 general worker.




Figure 3.3.4: Beam laser Source: imextools.co.uk

Beam laser attached on the wall by screws to indicate ceiling level perfectly.

## **STAGE 4: STEEL FRAME INSTALLATION**



Figure 3.3.5: Ceiling framework

Usually framework for plasterboard gypsum ceiling is mild steel, mild steel widely use in market because source is easily to find and always available. This steel framing is the main structure to support load which is plaster board.




Figure 3.3.6: Ceiling component Source: Alan blanc. 1994

Figure shows the diagram steel framing component used on ceiling. This stage takes 2 days to be done and requires 1 ceiling fixer and 1 general worker. Tools and equipment used are side cutting pliers, measuring tape, cordless screwdriver, beam laser, screw and scaffolding. Based on stage 3 after setting out the ceiling level using beam laser.

Installation of steel framework needs to be executed by step:

- 1. Wall angle needs to be screwed on parallel wall above beam laser which are ceiling level.
- Hanger is attached to the void and the additional fixing point are placed at the maximum of 1200 mm centres in each direction. Final check and make sure each fixing is tightened.

3. Apply channel up to hanger with one edge resting on channel and clamp to hold position when its level and in position fix with screw. Continue the installation until have rows of channel all fixed.



Figure 3.3.7: Tying channel and hanger

### STAGE 5: PLASTERBOARD & L - BOX INSTALLATION

Plasterboard is the crucial part in this installation which are used to cover up void, concealed or wiring from being exposed. Plasterboard dimension comes with 9mm thickness, 1220mm width and 2440 length. The duration for the installation takes 4 day to finish installation works. Installation requires 1 ceiling fixer and 2 general worker and tools that in used is cordless screwdriver, tray, measuring tape, plasterboard saw, scaffolding, putty trowel scraper, plaster trowel and stopping compound.



Figure 3.3.8: Installing plasterboard

There are several steps to install plasterboard on steel frame which are:

- 1. Board up to steel framework and begin to install with screw through the plasterboard and channel.
- 2. Screw work is continued on the plaster board at a maximum of 300mm centres continue fitting all plaster board until framework is completely covered.
- 3. Along the way, 1-box with size 6"x 8" is fixed around the drop ceiling and attach and screwed to the framework with tightened.



Figure 3.3.9: 6" x 8" 1 box Source: www.baileyplaster.com

4. After plasterboard completely covered, there is gap between the plasterboard which needs to be filled up with stopping compound.




Figure 3.3.10: Gap between plaster board

- 5. Stopping compound prepared and applied at this gap to fill up that area:
  - i. Pour clean water into tray.
  - ii. Add stopping bonding to clean water at a ratio of  $2^{1}/_{4}$  parts of plaster to 1 part water. Allow to soak for approximately 2-3 minutes before use
  - iii. Lastly, apply stopping bonding to plasterboard gap equally to get smooth surface



Figure 3.3.11: Mixing compound and water



Figure 3.3.12: After completed filling the gap with stopping compound

 This process continues until all plasterboard fixed to framework and covered all construction area.

## **STAGE 7: PAINT WORKS**

To give even surface on ceiling due to colour mixture of stopping compound and plasterboard or to cover up, dirt must be painted. Usually for ceiling painting, Maxilite Plus paint is widely used and available everywhere. For this kind of work white (15245) paint is used for painting work for interior ceiling.




Figure 3.3.13: Paint used for ceiling

To complete the task, two manpower were needed that are one painter and one general worker and this task takes 1 day to complete. Equipment used for whole process are roller tray and roller paint.

There are few steps for applying paint on ceiling:

- Ceiling needs to be clean at first from dust or grease spot that can ruin smooth surface.
- 2. Mix the paint thoroughly with handheld stirrer for a few minutes with consistency. This will prevent the oil pigments from separating.
- 3. Pour paint into roller tray and apply roller paint with dip the tip of 2" white paint and covered all area on the ceiling.



Figure 3.3.14: Applying paint on ceiling



Figure 3.3.15: Ceiling is completely constructed

4. Lastly, after underlaid paint on ceiling. Paint needs to be left dry by allowing the paint to set up overnight.

## **CONCLUSION 4.0**

## 4.1 CONCLUSION

Overall after involvement in the construction of Residential Tijani Ukay, Ampang located at No 1, Jalan Tijani 3/B, Tijani Ukay, 68000 Ampang, Selangor, ceiling is one of the main component as a must have in every building due to safety, protection and aesthetic value for building identity itself. A proper care for the material is a must so that it would not cause problem in the future. Few precautions was established when ceiling is constructed on some area that need to be considered for structures around the space if there are any consequences in the future.

One of the main precautions that had been applied at Residential, Tijani Ukay is the ceiling must be in a good condition and arranged accordingly to the correct place based on master layout plan. This small mistake needs to be avoided because it might cause a long term period problem, especially in a few years due to weakness of material used.

In completing this report, the method of installation of plasterboard ceiling is explained in detail. The construction of plasterboard ceiling starting on site with delivering material, floor covering, demolishing and dismantle plasterboard ceiling, levelling for ceiling installation, steel frame installation, plasterboard and 1- box installation. After that, installation on site is made. The installation process, site need to be cleaning to facilitate further work.

Many tools and equipment such as, beam laser, stopping compound, scaffolding and others was used while the construction. This equipment and tools will give new experience and knowledge for student practical. The surroundings of site construction full with equipment like nail, hammer, and screw. This situation will create intention to learn something new and develop this skill using these equipment for benefit.

For safety and health, it can be concluded that construction site area is safe to enter. Although, there are certain worker not wearing personal protective equipment (PPE) and protective clothing, there are no injuries or fatal cases that occur during the construction work process.

Therefore, it is recommended to all parties to take safety precaution regarding the installation of reinforcement concrete slab to minimize other contribution factor in building defect and human injury.

## REFERENCES

## BOOKS,

- 1. Roy Chudley, & Roger Greeno. (1998). Building Construction Handbook. Oxford: Elsevier Ltd. All Right Reserved.
- 2. Blakemore, R.G History of Interior Design Furniture: From ancient Egypt to Nineteenth-Century Europe. J. Wiley, 2006, p. 4.
- 3. Clouse, Doug. "The Handy Book of Artistic Printing: Collection of Letterpress Examples with Specimens of Type, Ornament, Corner Fills, Borders, Twisters, Wrinklers, and other Freaks of Fancy". Princeton Architectural Press, 2009. P. 66.

## **APPENDIX**



Appendix A: master layout plan ( ground floor)






Appendix B: master layout plan (first floor)






Appendix C: master layout plan ( second floor)




Appendix D: reflected ceiling plan (ground floor)




Appendix E: reflected ceiling plan (first floor)

51



Appendix F: reflected ceiling plan (second floor)



D E

Appendix G: plug point plan (ground floor)



Appendix H: plug point plan (first floor)

PRINTEGET 100 0 NUM

TOTAL BOFT 2500 W SOFT


PLUG POHIT PLAN

RAHIMAH / IDW / PPP / FF / 02 / REV04





Appendix I: plug point plan (second floor)





Appendix J: wall finishes plan (ground floor)





Appendix K: wall finishes plan (first floor)





Appendix L: wall finishes plan (second floor)

Appendix M: 3D design













RAHIMAH BESIDENTIAL

REV 09704:7019







RAHIMAH SESIDENTIA

REV 09/04/2019





RAHIMAH RESIDENTIAL

REV-04764-7019





RAHIMAH BESIDENTIA

REV 07/04/2019





RAHIMAH RESIDENTIAL

REV 173304-2019





RAHIMAH RESIDENTIA

REV 07/04/2019

DESIGN & BUILD SDN BHD













RAHIMAH RESIDENTIAL REV JAZUS





RAHIMAN RESIDENTIAL

REV 04/03 J 19

DW DESIGN & BUILD SDN BHD



RAHIMAH RESIDENTIAL

01 O 30/04 (1010)





PARIMAN RESIDENTIAL

REV 097(64) 2/01/4


DW DESIGN & BUILD














RAHIMAH RESIDENTIAL

REV 07/04/2015











Appendix M: after construction





