

**IMPLEMENTING GABOR FILTER FOR FINGERPRINT
RECOGNITION SYSTEM USING
FPGA VERILOG HDL**

**Thesis presented in partial fulfillment for the award of the
Bachelor in Electrical Engineering (Hons)
UNIVERSITI TEKNOLOGI MARA**



**ROSSHIDI HEZRIMI B TAHARIM
Faculty of Electrical Engineering
UNIVERSITI TEKNOLOGI MARA
40450 Shah Alam, Malaysia
DECEMBER 2008**

ACKNOWLEDGEMENT

In the name of god, most beneficent, most merciful, All the praised and thanks to Allah most almighty, lord of the universe and peace be open to His messenger Muhammad, the last of the prophets. We are very gratitude to the Almighty God for the strengths, wisdom, patience, motivation, creativity and ability bestowed upon no to complete this project. This project could not have emerged in its present without the helpful suggestions and combine work made by many people during its preparation. There are many people who have done their part to shape the excellent result.

I, **ROSSHIDI HEZRIMI B TAHARIM, (2005387153)** wish to take the opportunity to say thank for the commitment of all people that involve accomplishing this project. My sincerest appreciation must be extended to En. Abdul Hadi Abdul Razak, the supervisor for the final year project for his commitment and comment. He also explains briefly on the arrangement of the project. Besides, he also gives guidelines, idea and feedback for all steps from start until the end of the project. In addition he also advised me on the characteristic that should be included in my project and about the marking scheme for me to prepare and meet the requirements.

My sincere appreciations to my family for giving me the encouragement and morale support. They also provide me financial support that I need most upon to complete this report. I would like to thank to En. Karimi Abdul Halim for his help and advise. I also like to thank our friend for their help and assistance. Thank to fellow faculty members and students. Also, I like to thanks to all members for their comment and helps.

ABSTRACT

This paper presented the implementations of Gabor filter for fingerprint recognition using Verilog HDL. This work demonstrated the application of Gabor Filter technique to enhance the fingerprint image. The incoming signal in form of image pixel will be filter out or convolute by the Gabor filter to define the ridge and valley regions of fingerprint. This was done with the application of a real time convolve based on Field Programmable Gate Array (FPGA) to perform the convolution operation. The main characteristic of the proposed approach were the usage of memory to store the incoming image pixel and the coefficient of the Gabor filter before the convolution matrix take place. This FPGA filter can be categories as reconfigurable filter as the characteristic of the Gabor filter can be change by changing the coefficient stored in the memory.

TABLE OF CONTENTS

CONTENTS	PAGES
Declaration	iii
Dedication	iv
Acknowledgment	v
Abstract	vi
Table of Content	vii
List of Figures	x
List of Tables	xii
Abbreviation	xiii
CHAPTER 1 : INTRODUCTION	1-3
1.1 Background Study	1
1.2 Objective	2
1.3 Problem Statement	2
1.4 Scope of Project/limitations	2
1.5 Dissertation Layout	3
CHAPTER2 : LITERATURE REVIEW	4-16
2.1 Fingerprint	4
2.2 Gabor Algorithm	6
2.3 Gabor Filter/Digital Filter	10
2.4 Matrix Convolution	10
2.5 Floating-point Binary Number Representation	12
2.5.1 Single Precision	12
2.5.2 Double Precision	13
2.5.3 The Conversion Procedure	13
2.5.3.1 Floating-point To Decimal	13
2.5.3.2 Decimal to Floating-point	15

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND STUDY

The increasing demand for reliable human large scale identification in governmental and civil applications has boosted interest in scientific testing of biometric systems. Biometric is an emerging technology that is used to identify people by their physical and/or behavioural characteristic that inherently requires that one to be identified is physically present at the point of identification. Fingerprint identification is one of the most used and important biometrics. Fingerprints offer advantages when compared with other biometrics. For instance, iris reader fail when one wears contacts lenses or cannot maintain either their eyes open for a while or in front of intense luminosity. Gait and voice recognition can be imitated and there are similar patterns. Because of its uniqueness, the fingerprint has been used widely.

Fingerprint enhancement is a necessary process for fingerprint verification process. The most important measurement element in fingerprint recognition process is the texture of the fingerprint. Fingerprint enhancement is a necessary process for practical fingerprint verification. The main reason is because the imperfect live-scan fingerprint-sensors with the current technology[1]. The most popular for live-scan fingerprint touch sensors are optical and capacitive devices. However, these kinds of fingerprint touch sensor need to be cleaned periodically. So fingerprint enhancement technique employs contextual filter which their characteristics adapted depending on local text need to be implemented.

Fingerprint enhancement using Gabor filter is one of highly computational complexity in fingerprint verification process[1]. Gabor filter have a complex valued convolution kernel and a data format with complex values is used. So implementing Gabor filter is very significant in fingerprint verification process[2]. Designing Gabor filter will help enhancing the quality of fingerprint image. In fingerprint recognition, Gabor filter optimally capture both local orientation and frequency information from a fingerprint image. By tuning a Gabor filter to specific