


I0000029297

MARA INSTITUTE OF TECHNOLOGY

THESIS *ABU BAKAR*



SHAH ALAM

FINAL YEAR PROJECT REPORT
ADVANCED DIPLOMA IN CIVIL ENGINEERING

Bahagian Rujukan & Perkhidmatan Pembaca
Perpustakaan Tun Abdul Razak
Institut Teknologi MARA
40450 Shah Alam
Selangor Darul Ehsan.

**A STUDY ON AN ALLUVIAL CLAY
CONSOLIDATION INDICES DUE TO
PRELOADING - CASE STUDY**

FOTOSTAT TIDAK DIBENARKAN

by

ABU BAKAR NAS'SHA'ABAN BIN AYEB

92 056 487

AKNOWLEDGEMENTS

This report would not have been possible without the guidance, assistance and involvement of many other people.

First of all, thanks to Ir. Mohd Ali b. Hj. Jelani for his willingness to be my advisor and his guidance toward the completion of this report.

Thanks to, Ir. Zainab Mohammed for her initial involvement, En. Rahman Mahmud , Ir. Roslan Hassan, Dr. Ideris Zakaria and En. Jamaluddin for their assistance and willingness to audit and polish this report.

To the ever helpful En. Hafiz, En. Razman, En. Shamsudin and En. Mat Som who were involved in the sampling and testing exercise, thank you.

To all my friends and classmates for their support, especially Mohd. Ruzi Yaakob and Khairul Anuar Kamaruddin for their involvement in this study and not forgetting Nik Rulazman Nik Rusdy and Lijah Hassan for allowing me to use their computer and printer, thanks.

Thanks also to my 'secretary', Pn. Rubiah Juman for her involvement and her moral support and understanding when the times were rough.

Last but not least, my deepest gratitude to the management of Syed Mohammad, Hooi dan Binnie Sdn. Bhd. for allowing me to pursue my ambition and their financial support throughout.

To all these people and those involved in one way or other, I am forever indebted for their efforts on my behalf.

TABLE OF CONTENTS

	PAGE NO.
AKNOWLEDGEMENTS	i
TABLE OF CONTENTS	ii - v
LIST OF FIGURES	vi
LIST OF TABLES	viii
LIST OF SYMBOLS	ix
SYNOPSIS	x
CHAPTER 1.0 INTRODUCTION	1
1.1 General	1
1.2 Problem Statement	2
1.3 Objectives of the Proposed Study	3
1.4 Scope of Study	4
CHAPTER 2.0 LITERATURE REVIEW : CONSOLIDATION BEHAVIOUR OF SOIL	8
2.1 General	8
2.2 Theory of Consolidation	9
2.3 Phases of Consolidation	10
2.4 Consolidation and Compression Parameters	11
2.4.1 Coefficient of Consolidation, c_v	12
2.4.2 Coefficient of Compressibility, a_v	13

SYNOPSIS

A series of consolidation tests is carried out to determine the consolidation characteristics of alluvial clay underlying an area in Pelabuhan Kelang , Selangor D.E. The area was originally a swamp and the existing conditions of the area could be categorised as follows:

- i) preloaded area for 30 years,
- ii) reclaimed area for 7 years,
- iii) land fill area for 1 year and
- iv) swamp.

Overburden pressure over the original swamp was estimated between 20 and 30 kPa and water level ranged from 0.70m to 0.90m with tidal effects. The alluvial clay can be classified as silty clay of high plasticity and is normally consolidated.

Consolidation test results showed that the preloaded areas were highly compressible with low permeability. Correlations between consolidation indices and preloading duration were acceptable indicating that preloading would reduce settlement.

From variation of compression parameters, it is anticipated that differential settlements would occur if existing conditions of the Site are not considered during the design and construction stages.

1.0 INTRODUCTION

1.1 General

The rapid progress of development in Malaysia in recent years has resulted to wider usage of its coastal areas. This can be seen with the growth of numerous new projects in the coastal areas either in the West or East Malaysia especially in the west coast of the peninsula.

Projects such as golf courses, holiday resorts and new industrial areas are being implemented and these projects would later resulted to provision of other infrastructures such as roads, schools, offices, etc. In the end, a new township would be developed in these areas to cater for the needs of these developments.

The coastal part of west coast of the peninsula are extensively underlain by very soft normally consolidated clay called alluvial clay as shown in Figure 1.1. Generally, alluvial clays are known for its high compressibility and low strength characteristics.

In order to develop these soft clay areas, various consideration should be given and one of them is the effect of consolidation of the underlying soft clay on structures built above it. Settlement of structures due to consolidation is not unusual. However, excessive occurrence of these phenomena has to be avoided and anticipated before the construction of structures.

Preloading is one of the various techniques which have been introduced to overcome or minimize the settlement of soft clay such as alluvium . This technique has