

TIMBER DRYING USING COMPARTMENT KILN

BY:

SITI NOOR ADAWIEAH BINTI BESAR

**Final Project Paper Submitted In Partial Fulfillment for the
Diploma In Wood Industry,
Faculty of Applied Sciences,
Universiti Teknologi MARA,
November 2005**

ACKNOWLEDGEMENT

Firstly, I would like to take this opportunity to express my special thanks to ALLAH S.W.T for blessing and strength rendered to me to complete my project paper entitled **Timber Drying Using Compartment Kiln**

I also like to express my deepest appreciation to my advisor Associate Prof. Abdul Jalil Bin Ahmad for helping me and showing me the correct ways of performing my project paper. He gives full commitment and helps me to do all works.

Beside that, I would like to thank all my friends for continuous support and encouragement towards the completion of this project paper. Also to my parent, thank you so much for their moral support and guidance. I believe without their help, I would not be able to finish this final project. May ALLAH bless you.

Thank you so much to all.

TABLE OF CONTENTS

TITLE	PAGES
PROJECT TITLE.....	i
APPROVAL SHEET.....	ii
DEDICATION.....	iii
ACKNOWLEDGEMENT.....	iv
LIST OF PLATES.....	vii
LIST OF FIGURES.....	viii
ABSTRACT.....	ix
ABSTRAK.....	x
CHAPTER	
I INTRODUCTION	
1.1 GENERAL.....	1
1.2 JUSTIFICATION.....	2
1.3 OBJECTIVES.....	3
II 2.1. FACTORS THAT INFLUENCE DRYING RATE	
2.1.0 How wood dries	4
2.1.1 Lumber thickness.....	6
2.1.2 Specific gravity and weight of wood.....	7
2.1.3 Methods of Determining Specific Gravity.....	8
2.2.DRYING KILN AUXILIARY EQUIPMENT	
2.2.1 Equipment for determining temperatures.....	10
2.2.2 Equipment for determining air movement.....	17
III TEMPERATURES OF OPERATION	
3.1 Low Temperature Kilns.....	19
3.2 Conventional Temperature Kilns.....	19
3.3 Elevated Temperature Kilns.....	20
3.4 High Temperature Kilns.....	20

IV	OPERATIONAL TECHNIQUES.....	21
V	DRYING DEFECTS	
	5.1 Surface checks.....	27
	5.2 End Checks and Split.....	29
	5.3 Collapse.....	31
	5.4 Honeycomb.....	33
VI	CONCLUSIONS AND RECOMMENDATIONS.....	35
	REFERENCES.....	36
	VITA.....	37

TIMBER DRYING USING COMPARTMENT KILN

BY:

SITI NOOR ADAWIEAH BINTI BESAR

November 2005

ABSTRACT

Drying depreciation can be described as *diminution in quality* which develops during the drying process and reduces the value of the timber to a greater or lesser extent. On the other hand, the drying process is a quality improvement as wet forest-fresh timber is a raw material which is refined during the drying process and only then becomes a workable material.