

**ELECTRICAL AND OPTICAL PROPERTIES OF  
NANOSTRUCTURED TITANIUM DIOXIDE (TiO<sub>2</sub>)  
THIN FILM ANNEALED AT DIFFERENT  
TEMPERATURES**

This thesis is presented in partial fulfillment for the award of the Bachelor of  
Electrical Engineering (Honours)

**UNIVERSITI TEKNOLOGI MARA**

**MALAYSIA**



MOHD AZLI BIN ABDULLAH  
2006154045  
B. ENG (Hons.) ELECTRICAL  
Faculty of Electrical Engineering  
UNIVERSITI TEKNOLOGI MARA MALAYSIA (UiTM)  
Shah Alam, Selangor Darul Ehsan.  
NOVEMBER 2009

## **ACKNOWLEDGEMENT**

Assalamualaikum warahmatullahi wabarakatuh.....

With the name of ALLAH S.W.T. who gives us the strength and energy to us for completes this report. Thankful to ALLAH S.W.T. for giving me opportunity to complete this Final Year Project 2 (EEE 690) successfully. Thank you to all personnel's, which were willing to spend their valuable time for helping me to complete this project. I also would like to express our deep sense of gratitude and appreciation to my project's supervisor , Mrs. Puteri Sarah binti Mohamad Saad for her consistent help, guidance, inspiration and giving me spirit as well as prevision of her valuable time encourage and patience during the period of completing this project. I am very grateful to my supervisor and will never forget everything she had done for me and I appreciate it lot.

I also wish to express my deep gratitude to my co-supervisor, Assc. Prof. Dr Mohamad Rusop, Mr. Musa, Mrs Asiah, Mr Hafiz and my colleagues for very useful suggestions, guidance, and advices for the completion and success of this research.

Finally, I would like to express deepest gratitude to my parents, who always give the courage and support to me. And also to all of my friends, the moment that we shared together is unforgettable. They have all been a constant source of strength and inspiration. I hope the knowledge that I gathered and the experience I gained from this project will help us to face the real challenge in working environment.

**THANK YOU VERY MUCH TO ALL OF YOU**

Mohd Azli Bin Abdullah  
Solar Cell Laboratory  
Faculty of Electrical Engineering  
Universiti Teknologi MARA  
November 2009

## **ABSTRACT**

Nanostructured Titanium Dioxide (TiO<sub>2</sub>) thin film has been synthesized using sol-gel method and deposited onto glass substrates using spin coating technique. These thin films then annealed at various temperatures. The electrical, optical and structural characterizations of the as deposited and annealed films were carried out using IV measurement with 4-point probe equipment, UV-Vis spectroscopy, atomic force microscopy (AFM) and scanning electron microscopy (SEM). From this study, it is known that, electrical properties were influenced by changes of annealing temperature. Resistivity of thin films was found to decrease as the annealing temperatures increase. Based on the readings from UV-Vis spectroscopy, it is found that transmittance properties of TiO<sub>2</sub> thin films increased as annealing temperatures increase. This result is supported by surface topography and morphology of the thin films which indicate grains size increasing as temperature increases.

# TABLE OF CONTENTS

|  |          |
|--|----------|
| DECLARATION .....                                | I        |
| DEDICATION .....                                 | II       |
| ACKNOWLEDGEMENT .....                            | III      |
| ABSTRACT .....                                   | IV       |
| LIST OF FIGURES .....                            | V        |
| LIST OF TABLES.....                              | VII      |
| LIST OF SYMBOLS AND ABBREVIATIONS.....           | VIII     |
| <br>   |          |
| <b>CHAPTER 1 .....</b>                           | <b>1</b> |
| INTRODUCTION .....                               | 1        |
| 1.1. Project Background .....                    | 1        |
| 1.2. Project Overview .....                      | 3        |
| 1.3. Problem Statement.....                      | 3        |
| 1.4. Objectives of Project.....                  | 4        |
| 1.5. Scope of Work.....                          | 4        |
| 1.6. Organization of the Thesis .....            | 5        |
| <b>CHAPTER 2 .....</b>                           | <b>6</b> |
| LITERATURE REVIEW .....                          | 6        |
| 2.1. Introduction.....                           | 6        |
| 2.2. Crystalline Phase of TiO <sub>2</sub> ..... | 7        |
| 2.2.1. Rutile.....                               | 7        |
| 2.2.2. Anatase.....                              | 8        |
| 2.2.3. Brookite.....                             | 9        |
| 2.3. Photoactivity of TiO <sub>2</sub> .....     | 10       |
| 2.4. Application Of Titanium Dioxide .....       | 11       |
| 2.4.1. White Pigment.....                        | 11       |

# CHAPTER 1

## INTRODUCTION

### 1.1. Project Background

Many factors limit the efficiency of photovoltaic cells. Silicon is cheap, for example, but in converting light to electricity it wastes most of the energy as heat. The most efficient semiconductors in solar cells are alloys made from elements from group III of the periodic table, like aluminum, gallium, and indium, with elements from group V, like nitrogen and arsenic.

In the race to make solar cells cheaper and more efficient, many researchers are betting on new designs that exploit nanostructured material. Using nanotechnology, researchers can experiment with and control how a material generates, captures, transports, and stores free electrons properties that are important for the conversion of sunlight into electricity.

Two nanotech methods for engineering solar cell materials have shown particular promise. One employs quantum dots--nanosize crystals--that strongly absorb visible light. These tiny semiconductors inject electrons into a metal oxide film, or "sensitize" it, to increase solar energy conversion. Another strategy uses thin films of metal oxide nanoparticles, such as titanium dioxide, doped with other elements, such as nitrogen. Both doping and quantum dot sensitization extend the visible light absorption of the metal oxide materials.

One of semiconductor materials that have been used widely by researchers and physicist is Titanium Dioxide. Titanium dioxide has arisen much attention of chemists and physicists due to the capability of utilization in numerous industrial applications. Among the several oxides of metals, titanium dioxide ( $\text{TiO}_2$ ), a high-k dielectric with excellent biocompatibility and good photocatalytic performance, has been considered to be a