

JOINING WOOD AS A BASIC CONSTRUCTION FOR FURNITURE

By

Mohd Irwan Bin Sukeri

**Final Project Paper Submitted in Partial Fulfillment for the
Diploma in Wood Industries, Faculty of Applied Science
Universiti Teknologi MARA**

April 2001

ACKNOWLEDGEMENT

First and foremost my prayer and glory be to Allah S.W.T. The most merciful, for given me the strength and ability towards the completion of my final project paper entitle “Joining Wood As A Basic Construction For Furniture”. I also to thank for my beloved friends for their continuous support.

I would also to offer my special thanks to my advisor for this final project, Puan Siti Ruzaimah Harun for helping me at every phase of the study, who are so generous in leading me their helping hands and showing me the correct ways of performing my final project. I would like to express my most sincere thanks to her.

I also to extent my appellation to those who are involved either directly or indirectly in completing this project. I believe, without their helps I would not be able to complete this final project.

TABLE OF CONTENTS

	Page
APPROVAL SHEET	ii
DEDICATION	iii
ACKNOWLEDGEMENT	iv
LIST OF FIGURES	vi
ABSTRACT	vii
ABSTRAK	viii
CHAPTER	
1 INTRODUCTION	1
2 THE ELEMENTS OF JOINTS	3
2.1 Stress System.....	3
2.2 Grain Direction.....	4
2.3 Dimensional Change.....	4
2.4 Surface Condition.....	5
3 BASIC TYPES OF JOINTS	7
3.1 Worked Joints.....	8
3.1.1 Dovetail Joints.....	17
3.1.2 Miter Joints.....	18
3.1.3 Doweled Joints.....	19
3.2 Fastened Joints.....	22
3.2.1 Nails.....	23
3.2.2 Woodscrews.....	29
3.3 Adhesive Joints.....	31
4 STRENGTHENING JOINTS	42
5 CONCLUSIONS	52
REFERENCES	53
VITA	54

LIST OF FIGURES

Figures		Page
1	Some typical joints under loading stress.....	6
2	Basic types of joints.....	7
3	A mortise and tenon (resistance to compression, shear and racking).....	10
4	A mortise and tenon (the bearing surface of the shoulder).....	11
5	A mortise and tenon (reduce the stress on the joint).....	12
6	A mortise and tenon (radial/longitudinal grain direction).....	13
7	A mortise and tenon (dimensional restraint).....	14
8	The multiple tenon is preferable to a single wide tenon.....	15
9	The tenon was split radially and tangentially before assembly....	16
10	The dovetail (a standard carcass joint).....	18
11	Nails (function of its diameter, its driven length and the grain direction and density of wood).....	24
12	A common nails used in furniture.....	26
13	Nails (driven perpendicular to the grain).....	27
14	Nails (lateral loading fails).....	28
15	The five phases of a glue joint.....	34
16	Dowel used for alignment and strength.....	42
17	Layout lines on surface of joint.....	43
18	Homemade jig.....	43
19	Dowel jig on edge, face of material the same direction.....	44
20	Dowel center.....	44
21	Cut-off nail.....	45
22	Spline in a miter joint.....	46
23	Hardboard or plywood spline in an edge-to-edge joint.....	46
24	Hardboard spline in a skeleton frame.....	46
25	Feather across a miter joint.....	47
26	Feather cut after joint is cut and glued.....	47
27	Feather glued in place.....	48
28	Resulting attractive feather joint.....	48
29	Triangle and square glue blocks glued in place.....	49
30	Corner block glued and screwed in place.....	50
31	Square cleat drilled for screws.....	50
32	Cleat with screws holding adjacent parts.....	51

JOINING WOOD AS A BASIC CONSTRUCTION FOR FURNITURE

By

MOHD IRWAN BIN SUKERI

April 2001

Joining wood is the important thing in furniture manufacturing industries. The elements and types of joints can influence joints wood must be depressed in furniture manufacturing. Also, the strength of joints depends on wood joints. Generally, joining wood is the base of furniture manufacturing that could produce unique and high technology furniture.