# THERMOPLASTIC COMPOSITE FROM *MACARANGGA HOSEII* – POLYPROPYLENE

by

## YUSAIRI BIN YAAKUB

Final Project Paper Submitted in Partial Fulfilment for the Diploma in Wood Industry, Faculty of Applied Science, Universiti Teknologi Mara

April 2002

#### ACKNOWLEDGEMENT

First of all, I would like to take this opportunity to express my special thanks to Allah S.W.T for His Blessing and Strength rendered to me to complete my final project entitle "Thermoplastic Composite from *Macarangga hoseil*". I would like to offer my special thanks to my beloved mother and father. Said because of her pray for me always.

I would like to offer my special thanks to my project advisor, Mr. Amran Bin Shafie, because of his guide and lesson and also helping me at every phase of the study. He is so generous in lending me helping hands and showing me the correct ways of forming my tasks. I would like to express my most sincere thanks to him.

Lastly, I also to extend my appreciation to those who are involved either directly or indirectly in completing this project. I believe, without their helps, I would not be able to complete this final project.

iii

## TABLE OF CONTENTS

## TITLE

#### PAGE

APPROVAL SHEET	i
DEDICATION	ii
ACKNOWLEDGEMENT	iii
LIST OF TABLES	vi
LIST OF FIGURE	vii
LIST OF PLATES	viii
ABSTRACT	ix
ABSTRAK	

# CHAPTER

1.0 IN	TRODUCTION	1
1.1	Problem Statement	2
1.2	Objective	2
2.0 LI	TERATURE REVIEW	3
2.1	Mahang kapur ( <u>Macarangga</u> <u>hoseii</u> )	3
2.2	Composite	4
2.3	Lignocellulosic Composite	5
2.4	Polypropylene	6
2.5	Thermoplastic Composite	8
2.6	Hot Melt Blending	9
2.7	Potential of Lignocellulosic Thermoplastic	
	Composite	10

3.0 M	ATERIAL AND METHODS	12
4.0 R	ESULT AND DISCUSION	20
4.1	Strength and Physical Properties	20
4.2	Effect of Filler Loading	21
5.0 C	ONCLUSION AND RECOMMENDATION	25
REFI	ERENCES	26
VITA		28

#### ABSTRACT

# THERMOPLASTIC COMPOSITE FROM <u>Macarangga hoseii</u> -POLYPROPYLENE

By

#### YUSAIRI BIN YAAKUB

APRIL 2002

The research for thermoplastic composite from *Macarangga hoseii* been done. The test for bending, tensile and thickness swelling and water absorption been done for make sure *Macarangga hoseii* is more comfortable in making thermoplastic composite. The making of thermoplastic composite from *Macarangga hoseii* is followed from 5%, 10%, and 15% of wood dust from *Macarangga hoseii*. The result showed that 10% of wood dusts of Macarangga hoseii are most suitable. This because from bending test showed that 10% of wood dust is very strength compare to 5% and 15%. Using more polypropylene (PP) can give chance to the fiber bound each other with PP. The thickness swelling (T/S) and water absorption showed that the water absorb into 5% lower than 10% and 15%. Generally, using 10% of *Macarangga hoseii* is the most suitable quantity for mix with PP to make the thermoplastic composite.