Manufacture Of Thermoplastic From MDF Waste

By Siti Sabariah Binti Mat Hassan

Final project Submitted in Partial Fulfillment For The Diploma In Wood Industries, Faculty Applied Science, University Technology Mara.

October 2003

ACKNOWLEDGEMENT

First and foremost my prayer and glory be through Allah s.w.t. The most merciful, for given me the strength and ability towards the completion of my project paper entitle 'Manufacture of Thermoplastic From MDF Waste'. I also want to thank to my friends for their continues support.

I would like to appreciate my special thank for my advisor 1 Associate Prof. Dr. Jamaludin Kasim for his help and guide. I will never forget it as long I live in this world. I also want to say thank you so much for my advisor 2 Mr. Ahmad Fauzi because he also helped me in giving the comments finished this project.

I also want to extent my appellations to those who are involved either directly or indirectly in completing this project. I believe without their help, I would not be able to complete this final project.

III

TABLE OF CONTENTS

DEDICAT ACKNOW LIST OF LIST OF LIST OF	VLEDGEMENT FIGURES TABLE PLATES ABBREVIATIONS CT	I II IV V VI VII VIII IX
CHAPTE		
		1-2
1.1 OBJEC	CTIVES	3
CHAPTE 2.0 LITER	R TWO ATURE REVIEW	
2.1	MDF manufactures	4-5
2.1.1	Raw materials	5
2.1.2	Fiber preparation	5-6
2.1.3	Resin binder addition	6
	Forming	6-7
2.1.5	Pressing	7-8
	Finishing operations	8
2.1.7	Waste in MDF Products	8
	Thermoplastics	9
2.2.1	Composite	9-10
	Plastics	10-11
	Polypropylene (PP)	11
2.3	Effect of Coupling Agent (Maleic Anhydride Polypropylene) MAPP	11-12

		PAGE
3.0 MAT 3.1 3.1.1 3.1.2	ER THREE ERIALS AND METHOD Physical and Strength Properties Testing Tensile Test Bending Test Thickness Swelling and Water Absorption Test	13-23 24 24-25 26-28 29-30
	E R FOUR JLT AND DISCUSSION	31-40
	ER FIVE CLUSION	41
REFERE	NCES	42
APPEND	ICES	43-60
VITA		61

MANUFACTURE OF THERMOPLACTIC FROM MDF WASTE

By

Siti Sabariah Bt. Mat Hassan

October 2003

ABSTRACT

Research for thermoplastic composite manufacture from MDF waste has been done. MDF waste was selected as a main raw material that is found from Robin MDF Sdn. Bhd. Polypropylene was used as a bounder between MDF waste and used in the thermoplastic composite manufactured. The high strength of MDF is achieved by the addition of a synthetic resin binder. The typical density range of 660-860 kg/m³ for MDF overlaps the 560-800 kg/m³ range for the higher density grade of medium board but the resin binder added to MDF gives it a major strength advantage over medium board. 5%, 10% and 15% MDF waste has been choosing for this research. The tests that already done in the research were bending, tensile and the immersion test. As a result, 5% MDF waste is more suitable. It refers to the result at higher bending, tensile and the immersion test. Therefore, as a result, details research about MDF waste should been carry out, which is can increase more uses in wood industries.