# PREFABRICATED WOOD I-JOIST FROM JOINTED LAMINATED VENEER LUMBER (LVL) AS FLANGE AND WEB

By

MAZLIAH BINTI MADUN

Final Paper Project Submitted in Fulfillment of the Requirement for the Diploma in Wood Industries in the Faculty of Applied Science University Teknologi MARA

OCTOBER 2002

### ACKNOWLEDGEMENT

I would likes to express my deepest appreciation and sincere gratitude to my advisor, En. Wan Mohd Nazri bin Wan Abdul Rahman lecturer Diploma in Wood Industry, and my friends Md. Nazri Samin bin Mohd Shargawi, Nasrul bin Abdul Malik and Mariani binti Mamat for their unfailing help, support and guidance throughout the progress of this study.

These sincere thanks to Assoc. Prof. Dr. Jamaludin bin Kasim as our head program with advice and give suggestion in this study. To En. Sadey and En. Anuar for their guidance and helping when we done this study at DIP workshop. My greatest appreciation also to CHG Plywood, Cheras and FRIM (Forest Research Institute Malaysia) for the cooperation rendered that made the study possible.

The author also wishes to thank my entire friend DIP 06 October 2002 who in one way or another contributed supports and this opinion to completion of my study.

Finally, the special wishes goes to my beloved mother, sisters and brothers for their moral and financial support throughout the years of my study although they don't what is I-joist for.

May Allah S.W.T bless us all.

## TABLE OF CONTENTS

		Page
APPROVAL SHEET DEDICATION ACKNOWLEDGEMENTS LIST OF TABLES LIST OF FIGURES LIST OF PLATE LIST OF ABBREVIATIONS ABSTRACT ABSTRAK		iii iv v viii ix x xi xii
CHAPTER		
I	INTRODUCTION 1.0 Introduction 1.1 Problem Statement 1.2 Objective	1 1 2 2
П	LITERATURE REVIEW  2.1 I-Joist Geometry  2.2 The Used of I-Joist  2.3 I-joist In Residential Structure  2.4 Component of I-Joist  2.4.1 Laminated Veneer Lumber LVL from Rubberwood  2.5 Used of Joint in the I-Joist System  2.5.1 Scarf Joint  2.5.2 Butt Joint  2.6 Mode of Failure during Static Bending  2.7 Glue, Phenol Resorcinol Formaldehyde (PRF)	3 3 5 7 8 9 9 10 10 10
ш	MATERIALS AND METHODS  3.1 Factorial Experiment 3.2 Cross-Section of I-Joists 3.3 Preparation of I-Joist. 3.4 Butt Joints. 3.5 I-Joist Flanges from LVL (rubberwood) 3.6 I-Joist Fabrication. 3.7 Destructive Testing of I-Joist Samples 3.8 Calculation of Moment of Inertia (I) for I-Joist 3.9 Section Modulus (Z)	13 13 14 15 16 17 19 20 22 25

	3.10 Calculation of MOE and MOR of I-Joist	26
IV	RESULTS AND DISCUSSION  4.1 Modulus of Rupture (MOR), Modulus of Elasticity (MOE) and Mode of Failure	28 28
	<ul><li>4.2 Comparison of I-Joist Study Sample with FRIM Sample</li><li>4.3 Comparison of I-Joist Study with Wan Mohd Nazri Sample</li></ul>	32 35
v	CONCLUSION AND RECOMMENDATIONS 5.1 Conclusion. 5.2 Recommendations	38 38 38
BIBLIOG	RAPHY	40
VITA		42

# PREFABRICATED WOOD I-JOIST FROM LAMINATED VENEER LUMBER (LVL) AS FLANGES AND WEB

By

### **MAZLIAH BINTI MADUN**

October 2002

Wood I-joist is a system that consists of flange and web component. Both components have work together as a system in order to match the strength property of a laminated veneer lumber (LVL). The objective of the study is to obtain strength properties of prefabricated wood I-joist made from butt jointed web (LVL: Heavea brasiliansis) and flanges that used PRF (Phenol Resorcinol Formaldehyde) adhesive as a joint binder. The I-joist was combining with synthetic materials, resulting in lightweight, strong and environment-friendly building material. The average of modulus of rupture (MOR) for the study of 22.6 MPa and the average value of modulus of elasticity (MOE) was 7887.61 MPa. As the conclusion to this study, LVL web and flanges as an I-joist system cannot perform as a system.