MECHANICAL AND PHYSICAL PROPERTIES USING RESAK SAWDUST AS FILLER IN THE MANUFACTURING OF THERMOPLASTIC

BY

MOHD KHAIRUL EFFENDY BIN RAZALI

Final Project Paper Submitted in Partial Fulfillment for the Diploma in Wood Industry, Faculty of Applied Sciences, Universiti Teknologi MARA

MARCH 2005

ACKNOWLEDGEMENT



First of all I am thankful to Allah s.w.t. in giving me strength and determination in finishing this final project report.

I would like to thank Prof. Madya Dr. Jamaludin b. Kasim, my advisor and also my tutorial lecture, thanks a lot for your guidance, advice and support to complete this final project. Special thanks to the En. Amran B. Shafiee and Miss. Junaiza Bte. Ahmad Zaki for providing valuable help and information for this project.

I also want to thank to the other people that have been involved in making this report especially to my classmate (batch Mei 2002 - Mac 2005) for their help, co-operation and comment that they had give to me. I also want to wish to my beloved parents for giving me support through the process of this project.

Thank you also to the assistance at the Polymer Laboratory UiTM Shah Alam, En. Ismail, who is gives a lot of information, knowledge and support to my group for making the sample of the Thermoplastic.

TABLE OF CONTENT

	Page
APPROVAL SHEETS	i
DEDICATION	ii
ACKNOWLEGEMENT	iii
LIST OF FIGURES	iv
LIST OF PLATES	v
LIST OF ABBREVIATIONS	vi
ABSTRACT	vii
ABSTRAK	viii
REFERENCES	ix
VITA	X

CHAPTER

Page

I	1.0 Introduction	1
	1.1 Problem Statement	2
	1.2 Objective	3
П	Literature Review	
	2.0 Thermoplastic Composite	4
	2.1 Characteristic of The Species	6
	2.2 Polypropylene	7
	2.2.1 General Description	7
	2.2.2 Resin Identification Code	8
	2.2.3 Uses of Polypropylene	9
	2.3 Tensile Stress-Strain	10
III.	Material and Method	
	3.0 Material Preparations	12
	3.1 Blending Process	13
	3.2 Composite Manufacturing	14

	3.3 Evaluation of Thermoplastic Composite	18
	3.3.1 Bending Testing	18
	3.3.2 Tensile Testing	18
	3.3.3 Water Absorption and Thickness swelling	19
	3.3.3.1 Formula of Water Absorption	19
	3.3.3.2 Formula of Thickness Swelling	19
IV.	Result and Discussion	
	4.1 Moisture Content	25
	4.2Water Absorption	26
	4.3 Thickness Swelling	27
	4.4 MOE For Tensile	28
	4.5 MOR For Tensile	29
	4.6 MOE For Bending	30
	4.7 MOR For Bending	31
v.	Conclusion	32

MECHANICAL AND PHYSICAL PROPERTIES USING RESAK SAWDUST

AS FILLER IN THE MANUFACTURING OF THERMOPLASTIC

BY

MOHD KHAIRUL EFFENDY BIN RAZALI

MAC 2005

ABSTRACT

This study was conducted to determine the suitability of Unscreened and Fines using sawdust of Resak as filler in the making process of thermoplastic composite and to determine its physical and mechanical properties. The sawdust and Polypropylene (PP) were blended in Dispersion Mixer Machine and then moulded into a composite in a mould. Based on the results, it was found that the higher percentage of filler content that we used, the value of strength properties is decrease. The strength properties of thermoplastic also increase with the size of particle used. Water absorption also increases when filler content increase. I concluded that using Fines as filler is suitable in the making process of thermoplastic composite.