STUDY ON THE ELECTRICAL PROPERTIES OF ZINC OXIDE (ZnO) THIN FILM PREPARED BY SOL-GEL SPIN COATING

Thesis is presented in partial fulfillment for the award of the Bachelor of Engineering (Honors) in Electrical Engineering UNIVERSITI TEKNOLOGI MARA



AISHA ADIBAH ABD HALIM Faculty of Electrical Engineering UNIVERSITI TEKNOLOGI MARA 40450 SHAH ALAM SELANGOR, MALAYSIA MAY 2008

ABSTRACT

This thesis focuses on the effect of annealing temperature to electrical, structural and optical properties of deposited Zinc oxide (ZnO) thin films. ZnO solutions are deposited onto glass and silicon substrates using sol-gel spin coating technique. Deposited films are annealed at various temperatures from 300°C to 500°C. The electrical properties characterized by Current-Voltage (I-V) measurement shows that the resistivity decreased as annealing temperature increased. The structural properties are characterized using Scanning Electron Microscopy (SEM) and X-ray Diffraction (XRD). SEM and XRD analysis indicated denser surface morphology and better crystallinity at higher temperature. The optical properties characterized by UV- spectrophotometer (UV-vis) indicated the transmittance is over 40% in the visible region range from 400 to 800nm and fully absorption at 300nm.

ACKNOWLEDGEMENT

In the name of ALLAH, most gracious and most merciful. Thank a lot for giving me strength in completing this project.

Firstly I wish to express my gratitude towards my supervisor Pn. Hashimah Hashim, my Co-supervisor, Dr Mohamad Rusop Mahmood, as well as Mohamad Hafiz Mamat, for allowing the chance to work under their guidance, criticism, advices and full support in completing this thesis. This project would not success without their strenuous and time consuming efforts.

Hereby I would like to express my deepest thank to my parent and family for their understanding, morale and financial support and encouragement upon completing this thesis.

Special thank to all master students for their help and time, to answer my question in order to gain more knowledge on semiconductor technology. I also wish to thank Dr. Zaiki b. Awang for providing SEM measurement technology, technicians; Mr. Mohd Zaidi b. Marlan, Mr. Mohd Azlan b. Jaafar and Mr. Hisham b. Mahamad who had wittingly or unwittingly helped me in many ways and consistency in preparing the laboratory equipment.

Finally, thank to my course mate and friends who willing to stand my anger and motivated me upon completing this thesis and project. Thank you for all your support and consistence.

TABLE OF CONTENTS

DECLARATION	i
DEDICATION	ii
ABSTRACT	iii
ACKNOWLEDGEMENT	iii
TABLE OF CONTENTS	v
LIST OF TABLES	viii
LIST OF FIGURES	X
LIST OF ABBREVIATION	xi

CHAPTER 1

INT	RODU	CTION	••
	1.1	INTRODUCTION	1
	1.2	PROJECT OVERVIEW	2
	1.3	OBJECTIVES	3
	1.4	SCOPE OF WORK	3
	1.4	ORGANIZATION OF THESIS	4

CHAPTER 2

	LITERATURE REVIEW
5	2.1 ZINC OXIDE
6	2.2 DIODE PN JU
IUM9	2.2.1 PN JUNCTIO
9 BIAS	2.2.2 PN JUNCTIO
BIAS11	2.2.3 PN JUNCTIO
	2.3 SOL GEL ME
E15	2.4 SPIN COATIN
ATING FLUID ONTO THE SUBSTRATE.15	2.4.1 DEPOSITIO

CHAPTER 1

INTRODUCTION

1.1 INTRODUCTION

Zinc oxide (ZnO) is n-type semiconductor with direct band gap energy of 3.37 eV at room temperature and a free-exciton binding energy of 60 meV [4,5]. The property of ZnO is dependent partly on the crystallinity, crystallographic orientation, crystallite size and morphology.

Interest in the research effort on ZnO is driven by various applications in blue and ultraviolet (UV) light emitters [1, 3], solar cell windows [7, 8], photovoltaic device [10], gas sensor [9] and surface acoustic wave device [11]. ZnO is well known for its transparency when made into thin films and is expected to find wide use as transparent electrodes for many devices, such as electrochromic displays (ECDs), electroluminescent displays, and liquid crystal displays (LCDs) and solar cells.

ZnO thin films have been prepared by a variety of techniques, such as R.F. magnetron sputtering [16,17], reactive magnetron sputtering, chemical vapor deposition [18,19], ionbeam evaporation, electron-beam evaporation, spray pyrolysis [20,21], laser ablation and sol-gel process [22,2].

Among the different techniques available, the sol-gel method seems to be the most attractive due to ease of coating on the desired shape and area, easy control of the doping level, solution concentration and homogeneity without using expensive and complicated equipment when compared to other methods.