



**EXPERIMENTAL INVESTIGATION INTO CONVECTIVE HEAT
TRANSFER OF NANOFLUID AT THE ENTRANCE REGION
UNDER LAMINAR FLOW CONDITIONS**

**MOHAMMAD FIRDAUS BIN CHE MAT
(2006882168)**

A thesis submitted in partial fulfillment of the requirements for the award of Bachelor
Engineering (Hons) (Mechanical).

**Faculty of Mechanical Engineering
Universiti Teknologi Mara (UiTM)**

MAY 2009

ACKNOWLEDGEMENT

First and foremost, I would like to thank Allah s.w.t for giving me the faith and strength to finally complete this project successfully.

I would like to express my gratitude and appreciation for my project supervisor, Mr Baljit Singh a/l Bathal Singh for his supervision, continue support, generous guidance, advice and encouragement throughout the whole process of completing this project. Thank you for having the faith in me and trusted me all the way.

I also would like to express my appreciation to En Fadli from the Thermodynamic laboratory, En Faizal also from the Thermodynamic laboratory, and also En Faiz from Welding Laboratory for their guidance and assistance on the experiments done at the laboratory.

A big appreciation to my family for giving me a lot of support and always be there whenever I needed them.

Lastly, I would like to thank to all my friends for lending their hand to help me in any way.

Without all of their help and support, I wouldn't be able to complete this final year project successfully.

Thank You very much.

ABSTRACT

Nanofluids are suspensions of metallic or nonmetallic nanopowders in base liquid and can be used to increase heat transfer rate in various applications. Because of its enhanced heat transfer capability as compared to normal based fluids such as water, its was offered the engineer opportunities for development in heat transfer and thermodynamic areas. This project reports an experimental investigation of work on the convective heat transfer of nanofluids flowing through a copper tube in the laminar flow regime compare with water. The nanoparticles that use in this experiment was made of Aluminium Nitrate ($\text{Al}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$) and Tin Chloride Hydrated (SnCl_2). These nanoparaticles is then mixed with water (H_2O). Experimental results proved that the enhancement of heat transfer coefficient is due to the nanoparticles present in the fluid. Heat transfer coefficient increases by increasing the concentration of nanoparticles in nanofluid which use 0.6% vol, 1.0% vol and 1.6% vol of water. The use of the nanoparticles that mixed with water can significantly enhance the convective heat transfer in the laminar flow regime. The increase in heat transfer coefficient due to present of nanoparticles is much higher than the prediction of single phase heat transfer correlation used with nanofluid properties.

