



**A CASE STUDY OF CHILLED WATER AIR-CONDITIONING SYSTEM IN
UiTM PENANG**

**MD ZAINIZAM BIN NGADIMAN
(2016666094)**

A thesis submitted in partial fulfilment of the requirements for the award of Bachelor
of Mechanical Engineering (Manufacturing) (Hons.)

**Faculty of Mechanical Engineering
Universiti Teknologi MARA (UiTM)**

JULY 2019

ACKNOWLEDGEMENT

In the name of Allah, the Most Gracious and the Most Merciful

Firstly, I would like to thank Allah for permission to set up this final year project in accordance with the requirements and time frame. I would like to express our appreciation to my supervisor which is Sir Bakri B. Ali for their continued support, generous guidance, help, patience and encouragement in the duration of the thesis preparation until its completion.

I would like to thank the Facility Management Department, UiTM Penang who for providing the necessary support, information, and permission to conduct for the research. I would like to thank the lecturer FKM in UiTM Penang for sharing expertise, and sincere and valuable guidance and encouragement extended to me. Thanks also to all friends who provide help and support during my studies in UiTM Penang.

I take this opportunity to record our sincere thanks to the management UiTM who permitted study leave and supported for continuing the study at degree level.

Finally, my gratitude goes to beloved parents, who always gave encouragement and pray for my success in education. Also, those who are not directly contributing to this project, your kindness meant to me. Thank you very much.

ABSTRACT

Many office buildings in Malaysia including Universiti Teknologi MARA (UiTM) Penang were installed with the air-conditioning system to provide comfort for the occupants. The examples of air-conditioning types system used were a split unit, chiller system and many more. In UiTM Penang, chiller system that has a capacity of 2100 refrigerant tonnage is used to cool the building such as Faculty of Mechanical Engineering (FKM). The recommended degrees for thermal comfort zone are between 23°C to 25°C. However, in some areas in FKM building, there is an air-conditioning problem where comfort zone cannot be achieved. Thus, the purpose of the study is to investigate the heat loss and head loss for chilled water piping between the chiller plant and AHU room. Besides that, the total cooling capacity is calculated and compared to the installed air-conditioning. Most of the air-conditioning system installed in the building has complied with the design requirement, but the result shows that most of the chilled water temperature produced is high and not achieved to set point setting in the chiller system which is 7.5°C. The water supply pressure from the chiller plant maintained at 6.3 bar for each day. The heat loss occurred in chiller plant is acceptable because lower than design requirement which is 8.3°C. The head loss in the chiller plant is maintained on 2.3bar. The average heat loss between the chiller plant and AHU room is 1.25°C while the head loss is 1.3bar. There are three options proposed to improve the air-conditioning system in the FKM building. The selected option is to install a new chiller system near to FKM building with the new piping layout but using the existing AHU/FCU.

TABLE OF CONTENTS

ACKNOWLEDGEMENT	ii
ABSTRACT.....	iii
TABLE OF CONTENTS.....	iv
LIST OF TABLES.....	vii
LIST OF FIGURES	viii
LIST OF ABBREVIATIONS.....	xi
CHAPTER 1	1
INTRODUCTION	1
1.1 Background.....	1
1.2 Problem Statement.....	5
1.3 Objectives	6
1.4 Scope of the project	6
1.5 Arrangement of Thesis	7
CHAPTER 2	8
LITERATURE REVIEW	8
2.1 Introduction	8
2.2 Definition.....	8
2.3 Basic Air-conditioning Cycle.....	9
2.3.1 Compressor.....	9
2.3.2 Condenser.....	10
2.3.3 Metering Device.....	10
2.3.4 Evaporator	10
2.4 Types of Air-Conditioning System.....	11
2.4.1 Window unit.....	11
2.4.2 Split Unit System	12
2.4.3 Package Unit System.....	14
2.4.4 Chilled Water System.....	14
2.4.5 District Cooling.....	16

2.5	Thermal Comfort for Office Buildings.....	17
2.6	Total Cooling Load Calculation	18
2.7	System Design Criteria and Conditions.....	20
2.8	Chilled Water Pipe.....	21
2.8.1	Hydronic System Design.....	21
2.8.2	Water Distribution Systems	21
2.8.3	Principle of Water flow.....	22
2.8.4	Thermal Insulation	22
2.8.5	Water Flow Rate.....	22
2.8.6	Pipe Sizing.....	23
2.8.7	Heat Loss.....	24
2.8.8	Friction Head Loss (H_L).....	26
2.8.9	Static Head (H_s).....	28
2.9	Distribution System Design.....	28
2.9.1	Types of Piping System.....	29
2.9.2	Piping System Design	29
2.9.3	Layout Drawing.....	30
2.9.4	Section identification.....	30
2.9.5	Pump Head	31
2.9.6	Water Pump Calculation	32
CHAPTER 3	33
METHODOLOGY	33
3.1	Introduction	33
3.2	Flow chart of methodology.....	34
3.2.1	Preliminary	35
3.2.2	Literature Review.....	35
3.2.3	Information Gathering/Data Collection	35
3.2.4	Data Analysis	37
3.2.5	Cooling Load Estimation	37
3.2.6	New Installation Design.....	37
3.2.7	Discussion	37
3.2.8	Conclusion.....	38
3.3	Summary.....	38
CHAPTER 4	39
RESULT & DISCUSSION	39
4.1	Introduction	39