



**INFLUENCE OF CARBON ADDITION ON  
SINTERING BEHAVIOUR IN ULTRAFINE WC-Co  
POWDER**

**AIDILRIZAM BIN AZMI**

**(2013952219)**

**BACHELOR OF MECHANICAL ENGINEERING  
(MANUFACTURING) (HONS.)  
UNIVERSITI TEKNOLOGI MARA (UiTM)  
JANUARY 2017**

“I declare that the content present in this thesis are my own work which was done at Universiti Teknologi MARA (UiTM) unless stated otherwise. The thesis has not been previously submitted for any other degree.”

Sign : .....

Date : .....

**Aidilrizam bin Azmi**

UiTMNo : 2013952219

“I declare that I read this thesis and in my point of view this thesis is qualified in term of scope and quality for the purpose of awarding the Degree of Mechanical Engineering (Manufacturing) (Hons.)”

Signed : .....

Date : .....

**Ir. Dr. Salina binti Budin**

Faculty of Mechanical Engineering

Universiti Teknologi MARA (UiTM)

13500 PermatangPauh

Pulau Pinang

## **ACKNOWLEDGEMENT**

Bismillahirrahmanirrahim,

In the name of Allah, most Gracious, most Merciful.

First and foremost, I would like to thank to Almighty Allah for his blessing and guidance which enabled me to accomplish this final year project. Without his grace this opportunity could not become reality. I am feeling oblique in taking the opportunity to sincerely thanks to Ir. Dr. Salina binti Budin for her guidance constant support during the period of the project. On many occasions, her knowledge and insight were invaluable.

I would hereby like to express my profound sense of gratitude to Advanced Materials Research Centre (AMREC), SIRIM Berhad for giving me the opportunity to use the facilities and carry out my final year project in this company. Equally thankful I am to Dr Mohd Asri Selamat (Head of Engineering Material Section) for his invaluable guidance and supervised. I have learnt and experienced in handling equipments, machines, job skills, interpersonal skills.

## **ABSTRACT**

Tungsten carbide cobalt, WC-Co composites are essentially aggregates of particle of tungsten carbide bonded with cobalt metal via solid-state sintering. Ultrafine-grained WC-Co composites have potential to replace standard materials for tools and wear parts because of their tremendous mechanical properties especially on hardness and toughness. However, one of the crucial aspects in fabrication fine-grained WC-Co using powder metallurgy route is during sintering stage. Inappropriate sintering temperature may contribute to lower mechanical properties. Lower sintering temperature will lead to incomplete sintering while too high sintering temperature constituting the driving force for the grain growth process. The aim of this investigation was to study the optimum sintering temperature of WC-Co with carbon addition. In this work, ultrafine-grained powder of WC was used and sintering is conducted at liquid-solid-state in gas environment of 95% nitrogen and 5% hydrogen. Samples were fabricated through powder metallurgy route and sintered at three different temperatures which is 1350 °C, 1400 °C and 1450 °C and held for 1 hour. The effect of carbon addition in WC-Co composite towards the mechanical properties; density, hardness, transverse rupture strength, and microstructure formation at varies sintering temperature were examined using standard test procedures. The results signify that the fabricated samples produced higher density and hardness compared to commercial WC-Co cutting tools.