UNIVERSITI TEKNOLOGI MARA



PERFORMANCE TEST OF PLUG FLOW ANAEROBIC DIGESTER USING ANIMAL WASTE

NAFHATUN JALILAH BINTI MOHAMED AZRI

B.ENG (HONS) (CIVIL) UNIVERSITI TECHNOLOGY MARA 2006

PERFORMANCE TEST OF PLUG FLOW ANAEROBIC DIGESTER USING ANIMAL WASTE

by

NAFHATUN JALILAH BINTI MOHAMED AZRI

Report is submitted as the requirement for the degree of Bachelor Engineering (Hons) (Civil)

UNIVERSITI TEKNOLOGI MARA MAY 2006

DECLARATION

I, Nafhatun Jalilah Mohamed Azri, 2003479871 confirm that the work is my own and that appropriate credit has been given where reference has been made to the work of others.

ACKNOWLEDGEMENT

First and foremost I would like to thank Allah S.W.T. for His blessings throughout the process of finishing this proposal.

I would like to take this opportunity to express my greatest gratitude and appreciation to the project supervisor, Dr. Shanker Kumar Sinnakaudan for his advices, guidance, cooperation and support in making this proposal.

I would also like to thank all parties who had encouraged and help me to accomplish this proposal directly or indirectly. To the farms' owners, En Razak Din and En Mohamad for their cooperation. Not forget, supportive helped from the Highway laboratory technician, En Mohd. Azrul Aswad and my coursemate, Hannah Priscilla Egon and Norhasmie Nawang.

Last but not least, my special thanks go to my family and friends for their encouragement and support. Thank you.

ABSTRACT

The performance of plug flow anaerobic digester is studied in this research. Laboratory-scale digesters are operated to obtain the maximum biogas production as affected by 2 factors, (1) the type of animal waste (cow dung, goat dropping, and mixture of cow dung and goat dropping), and (2) the proportion of water and animal waste. 1:3, 1:6 and 1:10 proportion of waste to water were used in the experiment. In this research, 2 set of experiments are performed for each type of animal waste which are, (1) test for samples that were placed at the closet area (laboratory), (2) test for sample that were placed at the open space. From this research, it is expected to come out with the optimum waste concentration as a guideline digested configuration