

**DEVELOPMENT OF REBAR
CORROSION DAMAGE
QUANTIFICATION USING NON -
DESTRUCTIVE TEST FOR BRIDGE
DECK STRUCTURES**

**MUHAMMAD MU'TASIMBILLAH BIN
ROSLAN**

**Bachelor of Engineering (Hons) Civil
(Infrastructure)**

**UNIVERSITI TEKNOLOGI MARA
JANUARY 2019**

**DEVELOPMENT OF REBAR CORROSION DAMAGE
QUANTIFICATION USING NON -DESTRUCTIVE TEST FOR
BRIDGE DECK STRUCTURES**

By

MUHAMMAD MU'TASIMBILLAH BIN ROSLAN

This report is submitted as a
partial requirement for the degree of
Bachelor of Engineering (Hons) Civil (Infrastructure)

UNIVERSITI TEKNOLOGI MARA

JANUARY 2019

DECLARATION BY THE CANDIDATE

I declare that the work in this thesis was carried out in accordance with the regulations of Universiti Teknologi MARA. It is original and is the results of my own work, unless otherwise indicated or acknowledged as referenced work. This topic has not been submitted to any other academic institution or non-academic institution for any degree or qualification.

I, hereby, acknowledge that I have been supplied with the Academic Rules and Regulations for Under Graduate, Universiti Teknologi MARA, regulating the conduct of my study and research.

Name of Candidate : Muhammad Mu'tasimbillah bin Roslan

Candidate I.D. No. : 2016669614

Programme : Bachelor of Engineering (Hons) Civil (Infrastructure)

Faculty : Faculty of Civil Engineering

Thesis Tittle : Development of Rebar Corrosion Damage Quantification Using Non - Destructive Test For Bridge Deck Structures

Signature of Candidate:

(Muhammad Mu'tasimbillah bin Roslan)

Date : JANUARY 2019

ABSTRACT

The rapid expansion of Malaysia's maritime activities has increased the demand of several concrete made infrastructures. The corrosive nature of the seawater and the air surrounding it poses a great threat to rebars embedded in concrete which compromises structural integrity. Rebar corrosion via electrolysis was used to corrode steel rebar using Faraday's equation. This study is about the quantification of non-destructive test (NDT) to quantify corrosion damage of rebar so that rehabilitation works can start earlier with less costs. Three different NDT method were used in this study which is Ground Penetrating Radar (GPR), Half Cell Potential and Resistivity meter. RADAN 7 and SPSS were used to analyse readings. GPR results gained were satisfactory with R^2 values of 0.93 for both amplitude and attenuation relation with corrosion rebar damage. Visual hypothesis was also confirmed via B-scanning with imaging aid from RADAN7 software. HCP results produced reasonable corrosion versus HCP relations with R^2 values of 0.78 and 0.96 after outlying category of results were omitted. Resistivity was found to be unreliable in the study with random and inconsistent data, and no decent relations of quantification were able to be made.

ACKNOWLEDGEMENT

All praise to Allah swt, God Almighty for allowing this study to run and exposing our team to a variety of new experiences and knowledge. For knowledge is the light bestowed by Him and we as His loyal subjects nurture from his blessing

I would also like express my deepest gratitude to our supervisor, Mr Syahrul Fitry for guiding us along this study and helping us understand the many complex new field of knowledges that we were exposed to during the duration of our research.

A thousand thanks also to Mohammad Jibril and Nurul Ameera, my research companions who came through either during thick and thin. Without their help and support this research would be totally impossible

Finally, I would like to thank UiTM and all its staff members for facilitating our research despite the many unordinary requests made by our part. We deeply hope that our study has a positive impact towards the NDT industry and will lead on to a better future.