

**UNIVERSITI TEKNOLOGI MARA**

**TREATMENT OF PALM OIL MILL SECONDARY  
EFFLUENT (POMSE) USING SOLAR FENTON  
OXIDATION WITH IRON-CONTAINING SLUDGE**

**NORAZIEMAH BINTI MOHD ARIFF**

**Project paper submitted in partial fulfillment of the requirements  
for the degree of  
Bachelor in Environmental Health and Safety (Hons.)**


**Faculty of Health Sciences**

**JULY 2013**

## Declaration by Student

Project entitled Treatment of Palm Oil Mill Secondary Effluent (POMSE) using solar Fenton oxidation with iron-containing sludge is a presentation of my original research work. Wherever contributions of others are involved, every effort is made to indicate this clearly, with due reference to the literature, and acknowledgement of collaborative research and discussions. The project was done under the guidance of Assoc. Prof. Dr Hazilia binti Hussain as Project Supervisor. It has been submitted to the Faculty of Health Sciences in partial fulfillment of the requirement for the Degree of Bachelor in Environmental Health and Safety (Hons).

Student's Signature:



Noraziemah binti Mohd Ariff  
2009684156  
900611015046

Date: 19 JULY 2013

## ACKNOWLEDGEMENT

First and foremost, I would like to take this opportunity to express my gratitude to Allah S.W.T for His guidance along the period of the time called life also with His blessing and merciful that gives me the opportunity to complete this final year project.

I would like to express my sincere appreciation to my supervisor Assoc. Prof. Dr Hazilia binti Hussain for her dedicated guidance, valuable ideas, tireless efforts and on-going support throughout this project.

Special appreciation to Pn. Qistina Omar, Pn. Nurul Nazilah and Miss Norlaily for their guidance and to all the lab assistants, including Pn. Maziah, En. Erdzuam, En. Azwat and others for helping me in preparation of equipment and share their opinion. Words of thanks would never be enough. This project would not be able to be completed in time without their endless cooperation and guidance.

Thanks to all my fellow friends especially Mohd Fauzi Baharom, Fadilah Mohammad Aris and Nurul Shairah Ahmad Shahrifun for their support and motivations in completing this research study.

Last but not least, I would like also to express my love and appreciation to my lovely parents, En. Mohd Ariff bin Hj. Abd. Ghani and Pn. Mariani binti Hj. Mohd Amin as well my sibling who sacrificed much for this current effort and supporting me in reaching my goals.

## TABLE OF CONTENTS

<b>TITLE PAGE</b>		
<b>ACKNOWLEDGEMENT</b>	ii	
<b>TABLE OF CONTENTS</b>	iii - v	
<b>LIST OF TABLES</b>	vi	
<b>LIST OF FIGURES</b>	vii	
<b>LIST OF APPENDICES</b>	viii	
<b>LIST OF ABBREVIATION</b>	ix	
<b>ABSTRACT</b>	x - xi	
<b>CHAPTER ONE: INTRODUCTION</b>		
1.1	Background Information	1 – 3
1.2	Problem Statement	3
1.3	Study Justification	4
1.4	Study Objectives	
	1.4.1 General Objective	4
	1.4.2 Specific Objectives	4
1.5	Study Hypothesis	5
1.6	Conceptual Framework	6 – 7
1.7	Conceptual and Operational Definitions	
	1.7.1 Conceptual definition	8
	1.7.2 Operational definition	9
<b>CHAPTER TWO: LITERATURE REVIEW</b>		
2.1	Terminologies	
	2.1.1 Advanced oxidation process (AOP)	10
	2.1.2 Fenton Oxidation System	11
	2.1.3 Fenton's Reagent System	11 - 13
	2.1.4 Photo-Fenton	14



## Abstract

### Treatment of Palm Oil Mill Secondary Effluent (POMSE) Using Solar Fenton Process with Iron- Containing Sludge

Noraziemah binti Mohd Ariff

**Purpose:** A study was conducted to determine the effect of solar radiation in Fenton process on Palm Oil Mill Secondary Effluent (POMSE) and the efficiency of the process was assessed based on COD and color removal. The usability of recovery and reuse iron containing sludge as a source of iron was also determined. **Methodology:** POMSE sample was collected from a palm oil mill located in Kuala Kubu Baru, Selangor. The solar Fenton process was conducted in batch mode at laboratory scale. The solar energy was employed in the Fenton process. The POMSE was characterized in terms of pH, COD, color, suspended solid and total iron. The experimental work consists of two stages where the first stage was oxidation reaction at different reaction times which are 30 and 60 minutes. The experiment was followed by second stage which is oxidation process using iron recovered from Fenton sludge as a source of iron instead of fresh iron. This stage was repeated for five times. The supernatant and sludge were characterized after treatment process. **Result:** The result for pH, color, COD, total iron and suspended solid of POMSE were 8.10, 315 ADMI, 206 mg/L, 0.7 mg/L and 149 mg/L respectively. The COD and color removal for 30 minutes reaction time were 43% and 93% respectively. For 60 minutes reaction time, the COD and color removal were 66% and 84% respectively. There is no significant difference on reaction times for the treatment process with  $p$ -value= 0.378 and 0.423 ( $p$ -value > 0.05). The Fenton sludge was characterized in terms of specific gravity, moisture content, VSS, TSS and metal content which is iron (Fe). The ability of iron sludge as iron source also was observed through performance of color and COD removal. The color removal percentage ranged from 30% to 67% for 30 minutes reaction time and 3% to 84% for 60 minutes reaction time. The COD removal was 7% for 30 minutes and 21% for 60 minutes. There was no COD removal occurred from recycle 2 to recycle 5 using recovered iron. **Conclusion:** Solar Fenton process was found to be efficient in treating the wastewater based on removal of COD and color. The iron recovery from sludge generated in Fenton oxidation was feasible according to the removal of color but further study is needed on iron recovery sludge.

**Keywords:** *Fenton, palm oil mill secondary effluent, solar Fenton, iron recovery Fenton sludge, Chemical Oxygen Demand, color*