

**EVALUATION OF HEAT TRANSFER THROUGH WALL IN  
MALAYSIA- A CASE STUDY OF UiTM TEST CELL**

**ZAIDATUL SALWA BINTI MAHMUD**

**Final Year Project Report Submitted in  
Partial Fulfilment of the Requirements for the  
Degree of Bachelor of Science (Hons.) Physics  
in the Faculty of Applied Sciences  
Universiti Teknologi MARA**

**MAY 2010**

## **ACKNOWLEDGEMENT**

Alhamdulillah thanks to Allah, the almighty God for giving me the opportunity to finish this research within the given time successfully.

Upon completion of this project, I would like to express my gratitude to everyone who has given me all the supports. My heartfelt thanks go to my beloved supervisor Dr Nor Zaini Ikrom Zakaria for giving me all the knowledge and advices throughout the research.

Sincere thank you to my colleges and beloved family for all the supports, love and strength in completing this project.

Finally, I would like to express my appreciation to those who were helping me in this research, directly or indirectly. Thank you very much.

Zaidatul Salwa Binti Mahmud

## TABLE OF CONTENTS

	Page
<b>ACKNOWLEDGEMENT</b>	<b>iii</b>
<b>TABLE OF CONTENTS</b>	<b>iv</b>
<b>LIST OF TABLES</b>	<b>vi</b>
<b>LIST OF FIGURES</b>	<b>vii</b>
<b>LIST OF ABBREVIATIONS</b>	<b>ix</b>
<b>ABSTRACT</b>	<b>x</b>
<b>ABSTRAK</b>	<b>x</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1. Background	1
1.2. Problem statement	2
1.3. Significance of study	2
1.4. Objectives of study	2
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>3</b>
2.1. Introduction	3
2.2. Climate of Malaysia	4
2.3. Heat Transfer Mechanism	10
2.4. Time Lag	10
2.5. Effect of Wall Orientation	13
2.6. Wall Material Properties	15
2.7. Thermophysical Properties of Building Materials	16
2.8. Thermal Transmittance, U-value	18
2.9. Surface Air Film Resistance	19
2.10. Calculating Thermal Transmission, $Q_w$	20
2.11. OTTV	22
2.12. Thermocouple	23

## **ABSTRACT**

### **EVALUATION OF HEAT TRANSFER THROUGH WALL IN MALAYSIA - A CASE STUDY OF UiTM TEST CELL**

This is a study to evaluate the heat transfer through walls of different building orientation in the local climate. A test cell located in the campus of UiTM Shah Alam is used as case study. Data of the internal and external surface temperature for walls at the for orientations of North, South, East and West were measured using thermocouple type T. there were recorded on automated data logging system at an interval of 10 minutes for a duration of 5 days. The heat transfer for each wall orientation were calculated and compared. The building OTTV was also calculated and checked for the MS compliance. And finally the thickness of the east and west wall to minimize heat gain were calculated and proposed. The results show that the maximum heat gain through North and South walls are 159.9 W at 2.30 pm on the 1<sup>st</sup> day, and 169.25 W at 12.40 pm on the 2<sup>nd</sup> day respectively. The MS for building OTTV is  $50\text{W m}^{-2}$  and for this test cell the value is  $0.97\text{W m}^{-2}$ . The calculated wall thicknesses of brick material are 0.228m for east wall and 0.345m for west wall.

# CHAPTER 1

## INTRODUCTION

### 1.1. Background

One of the main high internal heats for typical Malaysia buildings is the wall envelope. It is important that energy management is well conducted to ensure that maximum benefit would be derived from the insulation of the building envelope (M. Department of Standard, 2007). Heat transfer through building envelope is determined by the thermophysical properties of the envelope, and the internal and external environmental condition. This study focuses on the heat transfer through vertical wall for different orientation in tropical climate. Twin Energy Efficiency Test Cells are used. The walls are heavyweight walls. Type T thermocouples are connected to data logger, Data Taker DT80 and Graphtec. Data was taken with 10 minutes interval for 10 days in natural ventilated mode. The values for thermal transmittance, U-value is gained by calculation.