

DESIGN OF TAPERED SLOT VIVALDI ANTENNA ARRAY USING FR4 SUBSTRATE

Thesis is presented in partial fulfillment for the award of the
Bachelor of Engineering (Hons.) Electrical
UNIVERSITI TEKNOLOGI MARA (UiTM)

%0^>ZL&*

MUHAMAD RIDZUAN BIN MOHAMAD IBRAHIM
FACULTY OF ELECTRICAL ENGINEERING
UNIVERSITI TEKNOLOGI MARA
40450 SHAH ALAM,
SELANGOR, MALAYSIA

MAY 2011

ACKNOWLEDGEMENT

All praise is to Allah S.W.T, The Most Gracious and The Most Merciful that has given me the strength, ability and patient to complete this Final Year Project.

I would like to convey my deepest gratitude, appreciation and thankful to my lovely project supervisor, Pn. Norhayati Binti Hamzah, who have been really determine to make sure that I am getting the most important information about my final project and for his invaluable suggestion, guidance, advise discussions and willing in sharing the knowledge towards for the completion and success of this project.

I also like to thanks most of the technicians from Microwave Technology Center Laboratory, for rendering their professional skills to help me in VNA test measurement and lab assistant in microwave laboratory that help me during setting up and testing the antenna using Antenna Training System.

Also to express my appreciation to my family, especially to my father and mother for give me a lot of support until I finish my study. And to thanks to my friends who has support and given their free time to help me especially for all Electrical Engineering student major in Communication and Cadet Officer of SISPA. May ALLAH S.W.T bless and reward them for their generosity.

ABSTRACT

These degree theses discuss the performance and behavior of Vivaldi antenna array for the ultra-wideband (UWB) frequency ranges. The design construction and characterization of the Vivaldi antenna by using two (2) different design but same array which is 1X2 arrays. The difference is the design of tapered slot wide end where the wide end of the tapered slot of the first design (TSA1) was to meet one another and another design (TSA2) is by adding space between wide end of the array. Then these antennas were constructed using FR4 substrates by using CST microwave software. The Vivaldi antenna produced that can be operated at X-band and using substrate that available and cheap.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	TITLE	i
	APPROVAL	ii
	DECLARATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	TABLE OF CONTENTS	vi
	LIST OF FIGURES	ix
	LIST OF TABLES	xi
	LIST OF SYMBOLS AND ABBREVIATIONS	xii
1	INTRODUCTION	1
	1.1 INTRODUCTION	1
	1.2 AIM AND OBJECTIVE	2
	1.3 SCOPE OF WORK	2
	1.4 ORGANIZATION OF THESIS	3
	LITERATURE REVIEW	4
	2.1 INTRODUCTION	4
	2.2 INTRODUCTION OF VIVALDI ANTENNA	5
	2.3 TAPERED SLOT ANTENNA	7
	2.3.1 Influence Of The Exponential Curve	8
	2.3.2 Influence Of The Antenna Dimensions	9
	2.4 FR4 SUBSTRATE	10
	2.5 IMPORTANT PARAMETERS OF ANTENNA	12

2.5.1	Radiation Pattern	12
2.5.2	Return Loss	13
2.5.3	Gain	14
2.5.4	Voltage Standing Wave Ration	14
2.5.5	Efficiency	15
2.5.6	Bandwidth	15
METHODOLOGY		16
3.1	INTRODUCTION	17
3.2	ANTENNA DESIGN PROCESS	17
3.3	DESIGN EQUATION AND STRUCTURE	18
3.3.1	Equation in designing Process	18
3.3.2	Antenna Array Structure Design	19
3.4	DESIGN AND SIMULATION PROCESS	20
3.5	DESIGN SPECIFICATION AND SUBSTRATE	21
MATERIAL		
3.5.1	Design Specification	21
3.5.2	Substrate Material Specification	21
3.6	PROTOTYPE DEVELOPMENT	22
3.7	PRACTICAL MEASUREMENTS	24
3.7.1	Vector Network Analysis (VNA)	24
3.7.2	Antenna Training Measurement System (ATMS)	25
RESULT AND DISCUSSION		26
4.1	INTRODUCTION	26
4.2	RETURN LOSS	26
4.3	VOLTAGE STANDING WAVE RATIO (VSWR)	28