

**MONOPOLE ANTENNA WITH ELECTROMAGNETIC BAND GAP (EBG)  
FOR WIRELESS LAN APPLICATION**

**Thesis is presented in partial fulfillment for the award of the  
Bachelor of Engineering (Hons.) Electronic (Communication)  
UNIVERSITI TEKNOLOGI MARA (UiTM)**



**MAS IQBAL BIN MAS LOCKMAN OUSIN  
FACULTY OF ELECTRICAL ENGINEERING  
UNIVERSITI TEKNOLOGI MARA  
40450 SHAH ALAM,  
SELANGOR, MALAYSIA**

## **ACKNOWLEDGEMENT**

Alhamdulillah Thanks to Allah for the strength and blessing me throughout the entire research and completion of this thesis. Peace upon our prophet Muhammad S.A.W. who has given light to mankind.

I am highly indebted to my supervisor Puan Norhayati Hamzah for her guidance and constant supervision as well as for providing necessary information regarding the project and also for their support in completing the project. I also would like to express my gratitude towards my co-supervisor, Nabila binti Ripin for her kind co-operation and encouragement which help me in completion of this project.

Lastly, I would like to express my special gratitude and thanks to all persons for giving me such attention and time. My thanks and appreciations also go to my university in developing the project by providing equipments for the project to be done.

## ABSTRACT

This paper provides a study on designing Monopole Antenna with and without Electromagnetic Band Gap (EBG) technique. The antennas were designed and simulated using the Computer Simulation Technology (CST) microwave studio. The substrate of the antenna was fabricated using a substrate of FR4 with dielectric constant and height of 4.30 and 1.6 mm respectively. The conventional monopole antenna is added with 3X3 array matrices squares which is size is 3 mm x 3 mm stands with electromagnetic band gap (EBG) structures. The results show that the monopole antenna with EBG structures has better performance. The constructions of electromagnetic band gap (EBG) structures contribute better basic parameter of the monopole antenna such as return loss, bandwidth and size reducing. The minimum specification of return loss from simulated result is -10dB cutoff.

## TABLE OF CONTENT

CHAPTER	TITLE	PAGE
	APPROVAL	i
	DECLARATION	ii
	ACKNOWLEDGEMENT	iii
	ABSTRACT	iv
	TABLE OF CONTENT	v
	LIST OF FIGURS	viii
	LIST OF TABLE	x
	LIST OF ABBREVIATION	xi
1	INTRODUCTION	1
	1.1 INTRODUCTION	2
	1.2 OBJECTIVE	4
	1.3 SCOPE OF PROJECT	4
	1.4 PROBLEM STATEMENT	4
	1.5 THESIS OUTLINE	5
2	LITERATURE REVIEW	6
	2.1 INTRODUCTION	7
	2.2 BRIEF THEORY	7
	2.2.1 Patch Antenna	7
	2.2.2 Electromagnetic Band Gap (EBG)	8
	2.3 ANTENNA FUNDAMENTAL	9
	2.3.1 Gain and Directivity	9
	2.3.2 Radiation Pattern	10

# CHAPTER 1

## INTRODUCTION

### 1.1 INTRODUCTION

The method of electromagnetic band gap (EBG) was found in late 1980's and became one of the most advancing sectors in the electromagnetic arena. This method allows manipulating the propagation of electromagnetic waves to next stage that cannot be achieved before. Besides, it promises the other way to overcome the limitation of current technology of electromagnetic and it is estimated that many new structures will be evolved based on this electromagnetic band gap concept [1, 2].

Monopole antenna has been discovered by Oliver Lodge on 1898 [3]. It was the apparently the first in the history of radio engineering. This antenna was used for a long time in all transceiver. However, recently this antenna is no longer acting outside of the body of receiving and transmitting [4]. A monopole antenna is actually a radio antenna which is one half of a dipole antenna and it is combined with right angle ground plane with considerable length in place of its another half. In other word, a dipole antenna has two halves, but the monopole antenna used one of the halves as electrically conductive surfaces known as ground plane. The ground plane act like the other halve of a dipole antenna as shown in figure 1 below [3, 4].