



**ON A STUDY OF POLYMERIC-FOAM PADDING AS A POTENTIAL  
VIBRATION ABSORPTION FOR USES IN HOUSEHOLD APPLIANCE**

**HAFIZAH BT ABDUL KARIM  
(2002241636)**

A thesis submitted in partial fulfillment of the requirements for the award of  
Bachelor Engineering (Hons) (Mechanical)

**Faculty of Mechanical Engineering  
Universiti Teknologi MARA (UiTM)**

**APRIL 2005**

## ACKNOWLEDGEMENTS

### BISMILLAHIRRAHMANIRRAHIM...

In the name of Allah S.W.T, The Most Gracious who has given me the strength and ability to complete this project. All perfect praises belong to Allah S.W.T, Lord of Universe. May His blessing upon the Prophet Muhammad S.A.W and members of the family and companions.

First of all, I would like to convey my deepest gratitude and thank to my project advisor, Prof. Madya Zamri Abdul Rahman for his guidance, supervision, encouragement and discussion throughout the work on this project. His guidance and patience have definitely ensured me to successfully finish the project. Secondly, to Dr. Azlan Md Isa, I would like thank you for your supervision, advice and guidance throughout this project. Thank you also to Workshop Technician; Mr. Mohd. Farid Mohd. Saat and Dynamic Lab Technician; Mr. Khalili Mat Som, for their help and advice during preparing samples and conducting tests at Mechanical Engineering Dynamic Laboratory.

A very special thanks to Mr. Hazran Husain for being an excellent photographer during the experimentation as well as marvelous work on getting the close up for the specimen images. Special thank also to Mr. Rossi Abdul Ghani for his help and opinion.

Thanks also to Texchem Pack supervisor, Mr. Lo for his cooperation in giving a lot of information, opinion and lead me towards the proper selection of

## **ABSTRACT**

This project is about the study of dynamic responses of polymeric foam when it is subjected to a base motion. There are two types of foam used in this study, namely, polystyrene and polyvinyl chloride. Apart from that, this project also proposes to see the effects of foam padding with variation in layers. The household appliance that has been used in this study is a blender. Literature review and theoretical review of vibration is described first followed by the equipment specifications and handling that involved in calibrating of equipment and handling of analyzer including a brief explanation on MATLAB Software. The methodology and analysis of results are put forward. A justification on the selection of this project, which covers the selection of material (Polystyrene and Polyvinyl Chloride, PVC), fixture design and equipment setting was carried out. The analysis of results was based on the data collected from the experiment. Finally, a conclusion and recommendations on the results obtained were made.

## TABLE OF CONTENTS

CONTENTS	PAGE
ACKNOWLEDGEMENTS	1
ABSTRACT	III
TABLE OF CONTENTS	IV
LIST OF TABLES	VIII
LIST OF FIGURES	IX
LIST OF ABBREVIATIONS	XV

### CHAPTER I LITERATURE REVIEW

1.1	Introduction Of Vibration	1
1.2	Definition Of Vibration	2
1.3	Causes Of Vibration	2
1.4	Control Of Vibration	3
1.5	Control Of Natural Frequencies	3
1.6	Reduction Of Force Transmitted To Foundation	4
1.7	Polymers	5
	1.7.1 Introduction	5
	1.7.2 Classification Of Polymers	7

## **CHAPTER I**

### **LITERATURE REVIEW**

#### **1.1 Introduction of Vibration**

There are numerous sources of vibration in an industrial environment, household appliances, laboratory, etc. These sources of vibration can be seen in impact processes such as pile griving and blasting, rotating or reciprocating machinery such as engines, compressor and motor, transportation vehicles such as aircraft and trains, household appliances such as washing machine, blender and many others.

The presence of vibration often leads to undesirable effects such as structural or mechanical failure, sequece and costly maintenance of machine, and human discomfort. Vibration can sometimes be eliminated on the basis of theoretical analysis. However, the manufacturing costs involved in eliminating the vibration may be too high; a designer must compromise between and acceptable amount of vibration and a reasonable manufacturing cost.

In some places the excitation or shaking force is inherent in the machine. Even a relatively small excitation force can cost an undesirably large response near resonance, especially in lightly damped system. In this cases, the magnitude of the