

DEPARTMENT OF BUILDING

FACULTY OF ARCHITECTURE, PLANNING AND SURVEYING

UNIVERSITI TEKNOLOGI MARA

(PERAK)

SEPTEMBER 2015

STUDENT'S DECLARATION

I hereby declare that this report is my own work, except for extract and summaries for which the original references are stated herein, prepared during a practical training session that I underwent at Perbadanan Memajukan Iktisad Negeri Terengganu for a duration of 5 months starting from 25 MAY and ended 9 OCTOBER 2015. It is submitted as one of the prerequisite requirements of DBN307 and accepted as a partial fulfilment of the requirements for obtaining the Diploma in Building.

Name

Fatin Nabila Binti Othman

UiTM ID No :

:

2013605966

Date

13 October 2015

DEPARTMENT OF BUILDING

FACULTY OF ARCHITECTURE, PLANNING AND SURVEYING

UNIVERSITI TEKNOLOGI MARA

(PERAK)

SEPTEMBER 2015

It is recommended that this practical training report prepared

by

Fatin Nabila Binti Othman

2013605966

entitled

Quality Assessment System in Construction (QLASSIC) at PB Sentral and KP Perdana sites at Kuala Terengganu

be accepted in partial fulfilment of the requirement for obtaining the Diploma in Building.

Report Supervisor

: En. Zulkifli Bin Ab. Halim

Practical Training Coordinator : Pn. Noor Rizallinda Binti Ishak

Programme Chairman

: Dr. Mohd Rofdzi Bin Abdullah

ACKNOWLEDGEMENT

Alhamdulillah, thanks to Allah for giving me the grace of my life to complete my training and report. I took five months to get the report done completely. This report may not be complete without the help and supports from other individuals or groups.

First of all, I would like thank Perbadanan Memajukan Iktisad Negeri Terengganu (PMINT) for the opportunity given me to perform the practical training. I am very grateful to have the enthusiastic Supervisor, Encik Zaidi bin Abdul Rahman and his team such as Encik Abdul Wafa, Encik Nik Nasri, Encik Khairul Azhar, Encik Sazwan and Encik Haji Harith. They never felt tired to teach me and to share their knowledge and the experience about this real life situation.

I would also like to thank both my parents,

binti Giman and other family members, who had supported me. As the inspirers to me, they gave me the strength to continue my training. They also sacrificed the money, energy and time. I could not have reached this stage without their continued prayers and their blessing.

Next, I would also like to thank my report supervisor, Encik Zulkifli bin Ab. Halim, the practical training coordinator, Puan Noor Rizallinda binti Ishak and the program chairman, Dr. Mohd Rofdzi bin Abdullah. They gave me a lot of help in giving the guidelines, time, effort and ideas to produce this report. I also want to extend my appreciation to all the UiTM Seri Iskandar Perak lecturers that have educated me for the precious semester. With the help that have been provided by them, it was like the initial preparation of practical training to me.

ABSTRACT

The quality of workmanship is an important aspect in a construction work and will be affected if there are no proper standards of quality. Thus, CIDB took the initiative to improve the quality of construction work by introducing the system of Quality Assessment System in Construction (QLASSIC). This report was conducted to explain the contributors to the low quality of construction works at Kuala Terengganu. Besides that, it covers the methods of QLASSIC and the elements involved in the quality assessment which is focused to architectural works. The architectural works which more to finishes works in the building. Last but not least, PMINT are expected to increase the efforts in introducing the QLASSIC for every project and can improve the quality of work by referencing the guidelines as set by QLASSIC.

TABLE O	F CO	NTENTS	PAGE NO
Acknowledge	ement		i
Abstract			ii
Table of cont	ents		iii - iv
List of variat	ion		v
List of table			vi
List of figure			vii - viii
List of photo			ix - x
List of appen	dix		xi
CHAPTER	1.0	PREFACE	
	1.1	Introduction	1
	1.2	Objectives	1
	1.3	Scope of study	2
	1.4	Method of study	3
CHAPTER	2.0	COMPANY BACKGROUND	
	2.1	Introduction of company	4
	2.2	Company profile	5
	2.2	Organization chart	6
	2.3	List of project	

		2.3.1 Completed projects	7 - 8
		2.3.2 Projects in progress	9 - 11
		2.3.3 Upcoming projects	12 - 13
CHAPTER	3.0	CASE STUDY	
	3.1	Introduction of project	
		3.1.1 PB Sentral	14 - 15
		3.1.2 KP Perdana Fasa 4A	16 - 17
	3.2	Case Study	
		3.2.1 General	18 - 24
		3.2.2 Defects of the architectural works	25 - 29
		3.2.4 The low usage of QLASSIC	30 - 33
	3.3	Method Statement	
		3.3.1 Method of QLASSIC	34 - 42
		3.3.2 Method of construction work to get	43 - 50
		better score in QLASSIC	
CHAPTER	4.0	CONCLUSION	
	4.1	Conclusion	51
REFERENC	CES		52 - 53
APPENDIX			54

LIST OF ABBREVIATION

PMINT

Perbadanan Memajukan Iktisad Negeri Terengganu

PB Sentral

Paya Bunga Sentral

KP Perdana

Kubang Parit Perdana

CONQUAS

Construction Quality Assessment System

CIS

Construction Industry Standard

PPE

Personal Protective Equipment

CIDB

Construction Industry Development Board

CCC

Certificate of Completion and Compliance

CPC

Certificate of Practical Completion

UBBL

Uniform Building by Law

CREAM

Construction Research Institute of Malaysia

LIST OF TABLE

Table 1.0	Information of 2 Storeys House
Table 1.1	Information of 1 ½ storeys IKS Terraced Workshop
Table 1.2	Information of 1 Storey House Type A
Table 1.3	Information of 4 Storeys Shop House
Table 1.4	Information of 2 Storeys Detached House (KP PerdanaFasa V1)
Table 1.5	Information of 2 Storeys House (KP Perdana 4B)
Table 1.6	Information of 2 ½ Storeys House (KP Perdana 4B)
Table 1.7	Information of 1 Storey Detached House
Table 1.8	Information of 1 Storey Detached House
Table 1.9	Information of 2 Storeys Terraced House
Table 2.0	List of QLASSIC equipment and their functions

LIST OF FIGURE

Figure 1.0	Logo of QLASSIC.
Figure 1.1	CIS: 2006.
Figure 1.2	Logo of PMINT
Figure 1.3	Organization Chart
Figure 1.4	2 Storeys House at Gong Badak
Figure 1.5	1 ½ storeys IKS Terraced Workshop at Kemaman
Figure 1.6	1 Storey House Type A at Marang
Figure 1.7	4 storeys shop house at Dungun
Figure 1.8	2 storeys detached house (KP PerdanaFasa V1) at Kuala Terengganu
Figure 1.9	2 storeys house (KP Perdana 4B) at Kuala Terengganu
Figure 2.0	2 ½ storeys house (KP Perdana 4B) at Kuala Terengganu
Figure 2.1	1 storey detached house at Besut
Figure 2.2	1 storey detached house at Kemaman
Figure 2.3	2 storeys terraced house at Kemaman
Figure 2.4	10 storeys PB Sentral
Figure 2.5	2 storeys detached house Type D (KP Perdana 4A) at Kuala Terengganu
Figure 2.6	2 storeys detached house Type E (KP Perdana 4A) at Kuala Terengganu
Figure 2.7	The elements of building which are used the QLASSIC

Figure 2.8	QLASSIC Press Conferences		
Figure 2.9	Training and workshop participants		
Figure 3.0	Checking the hollowness for the floor		
Figure 3.1	Checking the hollowness on the wall		
Figure 3.2	Checking the angle between a column and wall		
Figure 3.3	Checking the dimensions of a tread and rise of stair		
Figure 3.4	The democratization of the correct way to use the mirror		
Figure 3.5	Inspecting falls in wet areas		
Figure 3.6	Checking the hollowness for floor		
Figure 3.7	Installing the door		

LIST OF PHOTO

Photo 1.0	Sentral is one example of the public building construction that is used the QLASSIC
Photo 1.1	KP Pedana Fasa 4A as the housing construction
Photo 1.2	PMINT's assessors
Photo 1.3	Spirit level (1m)
Photo 1.4	Tapping rod
Photo 1.5	Measuring tape (3.5m)
Photo 1.6	Mirror
Photo 1.7	L square
Photo 1.8	Plumb bop
Photo 1.9	Callipers
Photo 2.0	Cracks on the wall surface Checking
Photo 2.1	Damaged wall
Photo 2.2	Uneven surface at the wall angle
Photo 2.3	Honey comb on the concrete
Photo 2.4	Hollowness at the tiles joint Crack on the wall surface
Photo 2.5	Dirtied wall surface with the excessive of the concrete
Photo 2.6	Uncompleted paint due to the bad conditions of surface
Photo 2.7	The suitable material of nozzles (non-slip tile)
Photo 2.8	QLASSIC briefing

Photo 2.9	Checking the hollowness for the floor
Photo 3.0	Checking the hollowness on the wall
Photo 3.1	Checking the angle between a column and wall
Photo 3.2	Checking the dimensions of a tread and rise of stair
Photo 3.3	The democratization of the correct way to use the mirror
Photo 3.4	Grooving the cement grout
Photo 3.5	Skirting
Photo 3.6	Place the tiles into the position
Photo 3.7	Tap the tile by using a rubber mallet
Photo 3.8	The completed floor tiles
Photo 3.9	Grout between the opposite tiles
Photo 4.0	Cover the floor by using the plywood
Photo 4.1	Check gradient of the frame by using the spirit level
Photo 4.2	Timber as the temporary supporter of frame
Photo 4.3	Connect the wall and frame by using the straps
Photo 4.4	Hinges
Photo 4.5	Fastening the lockset of door

LIST OF APPENDIX

Appendix A Project information of PB Sentral

Appendix B Project information of KP Perdana Fasa 4A

Appendix C QLASSIC information

Appendix D QLASSIC form

Appendix E Sampling guidelines for the architectural works

Appendix F QLASSIC certificate

Appendix G QLASSIC awareness programme

Appendix H QLASSIC statistics

Appendix I QLASSIC application by PMINT

Appendix J QLASSIC scores

CHAPTER 1.0

PREFACE

1.1 INTRODUCTION

A practical training course is compulsory to be taken by all the fifth semester UiTM Diploma in Building students. This training will enable the students to apply the theory learned in the class to the real life situation. Although the theory may be different from the real world but it can help the students to explore the process of building construction.

I underwent my training at Perbadanan Memajukan Iktisad Negeri Terengganu (PMINT). PMINT is responsible as the main development agency of the state of Terengganu including the urban development. I was placed at PB Sentral and KP Perdana sites.

At both sites, there was an assessment conducted known as QLASSIC. QLASSIC means Quality Assessment System in construction. It needs to be done in architectural works-finishes. The QLASSIC was initiated by CIDB to become the nation's Construction Industry Standard (CIS). Every building undergoing the QLASSIC will be examined by CIDB based on the quality of the works.

1.2 OBJECTIVE

The objectives of this report are:

- To identify the defects of the architectural works.
- To describe the methods or process of QLASSIC.
- To determine the good practices for better QLASSIC score.

1.3 SCOPE OF STUDY

This study focuses on QLASSIC that is be used in the construction works especially the architectural works. The quality of the works is able to be determined by applying the QLASSIC on the project. Some construction companies they do not use the system due to the certain factors (refer to Appendix H).

According to the purposes of QLASSIC, it exposes the best quality performance of works to the involved parties like the client, contractor, consultant, and buyer. All of the works must follow the Construction Industry Standard (CIS 7: 2006) as the standard to get the first-rate quality of the building construction works. The score that will be given by CIDB will determine the quality of the works and at the same time it can improve the reputation and ability of the company.

The outline of guidelines by CIDB can be the reference for the construction company and also as the good practices to get the best score. Along with the progress and sophistication of technology, the Q-LASSIC system must be promoted and be adopted by all the construction projects.



Figure 1.0: Logo of QLASSIC.

Source: cidb.gov.my (2012).



Figure 1.1: CIS 7: 2006.

Source: cidb.gov.my (2012).

1.4 METHOD OF STUDY

a) Books

The books are the primary method to obtain the information. The theory from the books is used as my reference. It gives the illustration of the QLASSIC system.

b) Observation

The observation method is the alternative method for collecting the information. By this method, I can observe by myself the QLASSIC system that is applied at the site and it provides more understanding to me to learn about the system.

c) Interview

The interview has been done at the sites and office. A few of the staff and workers were involved in the interview to collect the data. The results of interview were recorded and be used as the additional data for the QLASSIC system.

d) Internet

The information collected for this report is also sourced from the internet. The internet is a technology that can enhance and complement the available data in the real world of construction.

CHAPTER 2.0

COMPANY BACKGROUND

2.1 INTRODUCTION OF COMPANY

Perbadanan Memajukan Iktisad Negeri Terengganu (PMINT) was established on 1 April 1965, under an enactment of the Terengganu State Government as a main development agency. PMINT's roles are as the leader and implementer of socio-economic development including urban development.

A 14 storeys PMINT tower was built and completed in 1988. The area of this building is 0.71 acres. The tower is located at the crossroads between Jalan Sultan Ismail and Jalan Masjid Abidin. It was a pioneer in that area and also the administrative offices were placed in this tower.

In 1990, the WISMA PMINT was built next to the PMINT tower. This 10 storeys building is 0.15 acres and situated on the edge of Jalan Sultan Ismail. It provides the offices for rent. In 1995, the 6 storeys shopping complex which is known as PB plaza was constructed to provide opportunities to the local business community. In accordance with the upgrading of Kuala Terengganu to a city status in 2008, PMINT took the initiative to make MEDAN PMINT as a new landmark in the city central.

PMINT was involved in many activities on a wide scale which cover almost all economic sectors. The sectors include development of property and land, farm, aquaculture, production and services. As a conclusion, the activities in PMINT were performed in two ways, directly and by companies under PMINT.

2.2 COMPANY PROFILE



Figure 1.2: Logo of PMINT

Source: pmint.gov.my (2012).

Name of Company : Perbadanan Memajukan Iktisad Negeri Terengganu

Address : Tingkat 14 Menara Permint, Jalan Sultan Ismail,

20200 Kuala Terengganu, Terengganu Darul Iman.

Telephone & Fax No.

Email : admin@pmint.gov.my.

Date of establishment : 1 April 1965

Vision : To be a main leader, generator, and contributor to the

country's socio-economic development

Mission : To develop a variety of sources and sectors for the

economic development of Negeri Terengganu

towards prosperity

Motto : "KEPERLUAN & KEPUASAN PELANGGAN

KEUTAMAAN KAMI"

Objective of Establishment : - To eradicate the poverty.

- To increase the economy activities.

- To initiate the urban and rural development.

2.3 ORGANIZATION CHART




Figure 1.3: Organization of PMINT

2.4 LIST OF PROJECT

2.4.1 COMPLETED PROJECTS

1) Table 1.0: Information of 2 Storeys House

Location	Gong Badak, Kuala Terengganu
Minimum Land Area	6,835 sq ft
Minimum Price	RM 522,400.00
Unit Overall	16 units

Source: pmint.gov.my (2012).



Figure 1.4: 2 storeys house at Gong Badak.

Source: pmint.gov.my (2012).

2) Table 1.1: Information of 1 ½ Storeys IKS Terraced Workshop

Kemaman	
3,434 sq ft	
2,347 sq ft	
RM 438,160.00	
10 units	
	3,434 sq ft 2,347 sq ft RM 438,160.00



Figure 1.5: 1 ½ storeys IKS terraced workshop at Kemaman.

Source: pmint.gov.my (2012).

3) Table 1.2: Information of 1 Storey House Type A

Location	Marang	
Area	1,440 sq ft	
Minimum Price	RM 302,400.00	
Maximum Price	RM 307,300.00	
Unit Overall	3 units	

Source: pmint.gov.my (2012).



Figure 1.6: 1 storey house Type A at Marang.

2.4.2 PROJECTS IN PROGRESS

1) Table 1.3: Information of 4 Storeys Shop House

Location	Dungun	
Area	5,077 sq ft – 5,797 sq ft	
Minimum Price	RM 192,531.00	
Maximum Price	RM 446,925.00	
% Current Status	86.50 %	
Unit Overall	8 units	

Source: pmint.gov.my (2012).



Figure 1.7: 4 storeys shop house at Dungun.

Source: pmint.gov.my (2012).

2) Table 1.4: Information of 2 Storeys Detached House

Location	Kuala Terengganu
Area	1,484 sq ft
Unit Overall	12 units



Figure 1.8: 2 storeys detached house (KP Perdana V1) at Kuala Terengganu.

Source: pmint.gov.my (2012).

3)

Table 1.5: Information of 2 Storeys House

Location	Kuala Terengganu	
Area	2,965 sq ft	
Unit Overall	2 units	

Source: pmint.gov.my (2012).



Figure 1.9: 2 storeys house (KP Perdana 4B) at Kuala Terengganu.

4) Table 1.6: Information of 2 ½ Storeys House

Location	Kuala Terengganu	
Area	4,028 sq ft	
Unit Overall	2 units	

Source: Pmint.gov.my (2012).



Figure 2.0: 2 ½ storeys house (KP Perdana 4B) at Kuala Terengganu.

2.4.3 UPCOMING PROJECTS

1) Table 1.7: Information of 1 Storey Detached House

Location	Besut	
Area	1,300 sq ft	
Price	RM 260,000.00	
Unit Overall	32 units	

Source: pmint.gov.my (2012).



Figure 2.1: 1 storey detached house at Besut.

Source: pmint.gov.my (2012).

2) Table 1.8: Information of 1 Storey Detached House

Location	Paka, Kemaman	
Area	1,184 sq ft	
Price	RM 280,000.00	
Unit Overall	30 units	



Figure 2.2: 1 storey detached house at Kemaman.

Source: pmint.gov.my (2012).

3) Table 1.9: Information of 2 storeys terraced house

Location	Kemaman	
Unit Overall	35 units	

Source: pmint.gov.my (2012).



Figure 2.3: 2 storeys terraced house at Kemaman.

CHAPTER 3.0

CASE STUDY

3.1 ITRODUCTION OF PROJECT

3.1.1 PB SENTRAL

PB Sentral is a short form for Paya Bunga Sentral. It is one of the mega projects under PMINT. The project title is "Cadangan Merancang, Merekabentuk, Membina, Menyiapkan, Menguji, Mentauliah dan Menyelenggara Pusat Reakreasi (10 Lapis) serta Kerja-kerja Berkaitan yang Mengandungi 7 Unit Lot Kedai (1 Lapis), Parking Bertingkat (6 Lapis), Bowling (1 Lapis), Cineplex (2 Lapis) di atas Lot 4133-4140, Lot 5035-5038, Lot 4145 dan Lot 3068-3071 di Jalan Tengku Embong Fatimah, Mukim Bandar Kuala Terengganu".

PB Sentral is the continuation of the PB Square project that has been in operation since last year. PB Sentral also has a link bridge that connects with PB Square. It provides 11 cinemas including the VVIP set, 36 lanes bowling center and more than 700 lots of the multi-storey parking inside it.

This 10 storeys family recreation central project involved a construction cost of eighty nine million nine hundred sixty eight thousand five hundred seventy seven (RM 89, 968, 577.00). It takes a period of 48 weeks to complete which started on January 2, 2013 and is expected to be completed on November 7, 2015.

KIP Structure Sdn. Bhd. is the contractor which is responsible to build the whole building while AHS Architects Sdn. Bhd. is the architect firm chosen by PMINT to design this project. Perunding NFL Sdn. Bhd, as the surveyor that is in charge for

calculating the costs from the beginning to end of construction and related works. Entech Consult takes the roles as a civil and structure engineer. Their works are focused to road, beam, column, drainage, sewage and others. The works of mechanical and electrical was entrusted to Emech Consulting Engineers.



Figure 2.4: 10 storeys of PB Sentral.

Source: PMINT (2015).

3.1.2 KP PERDANA FASA 4A

KP Perdana is a short form for Kubang Parit Perdana. It is the projects of residential houses and it was built according to the phases. The project title is "Cadangan Membina dan Menyiapkan 10 unit Rumah Berkembar 2 Tingkat di atas Lot PT 1651 hingga PT 1660 Serta Kerja-kerja Berkaitan di KP Perdana Mukim Kubang Parit, Kuala Terengganu (Fasa 4A)".

KP Perdana Fasa 4A has two types of detached houses, which are Type D and Type E. There are 4 houses of Type D and 6 houses of Type E. This project is the continuation of the previous phases and will be continue until phase 6. The designs of both types are same as the type of houses from the previous phases.

For this project, it takes a period of 48 weeks to complete which started on September 2, 2014 and is expected to be completed on August 3, 2015. In addition, the contractor has been issued 3 months of Extension of Time (EOT) for this project because of some problems on the sites. The new date which is expected to be completed is on November 3, 2015.

The contractor who is responsible to build the whole building is SEZ Prima Sdn. Bhd. The designing works is done by Arkitek Aliran Cipta firm. W & K Perunding Ukur Bahan, is the surveyor who is liable for calculating the overall costs of project and related works. Mohd Asbi & Associates is in charge of the civil and structural works. The electrical works is handed over to Emech Consulting Engineers.



Figure 2.5: 2 storeys detached house Type D (KP Perdana 4A) at Kuala Terengganu.

Source: pmint.gov.my (2012).



Figure 2.6: 2 storeys detached house Type E (KP Perdana 4A) at Kuala Terengganu.

3.2 CASE STUDY

3.2.1 GENERAL

3.2.1.1 INTRODUCTION OF QLASSIC

QLASSIC is the acronym for quality assessment in construction. It is a system to evaluate the workmanship quality of building construction works. QLASSIC is conducted based on the construction industry standard (CIS 7:2006). It was introduced by CIDB in 2006 to assess the quality of building construction works. Before this, the quality is assessed by Unit Penyelarasan Pelaksanaan (ICU). This system has the same practices as the system from Singapore which known as CONQUAS in evaluating the quality in the building works. Both of them provide the good practices for the contractors, client, buyers and others. It is a helpful system to get the high scores.

3.2.1.2 ARCHITECTURAL WORKS

This report is focussed to the architectural works. The architectural works is more on the finishes. The quality of finishes will influence the whole aesthetic value of building. It covers the works as follows:

- Internal and external walls
- Ceiling
- Door
- Window
- Fixtures and fittings
- Floors
- Roofs
- Driveway
- Porch

3.2.1.3 BENEFIT OF QLASSIC

The benefits of QLASSIC can be stated as follows:

- Complete quality system
- Improve the developer's credibility
- Increase the competition
- Adaptable for all of projects
- As a guarantee to buyers
- Resolve the defect and others problem



Photo 1.0: PB Sentral is one example of the public building construction that used QLASSIC.



Photo 1.1: KP Pedana Fasa 4A housing construction.



Figure 2.7: The elements of building which are used the QLASSIC. Source: currebtbuzz.my (2015).

3.2.1.4 COMPONENT

QLASSIC contains the standard on quality for the various components. The components can be divided into four components which are architectural, structural, mechanical and electrical (M & E) and external works. Every component has their elements that will be evaluated by sampling method or assessment in sites.

3.2.1.5 ASSESSOR

The assessor must be trained and who have passed the training needed to register with CIDB to become the official assessor. Every assessor must prepare themselves by getting ready on the information related to QLASSIC. The assessor has good attitude if they have sensitivity to their surroundings. They must wear the Personal Protective Equipment (PPE) such as safety helmet and safety boots. It may also be able to convince the users of QLASSIC that the assessor of their projects is the qualified assessor.

PMINT Assessors

1) Name: Mohd Zaidi Bin Abdul Rahman (main assessor)

Position: Civil Engineer

Services period: 13 years

Experience:

- Handling the QLASSIC for PMINT projects.

- The latest involvement is in the housing project.

2) Name: Abdul Wafa Bin Muhammad

Position: Architect Assistant

Services period: 4 years

Experience: -




Photo 1.2: PMINT's assessors.

3.2.1.6 EQUIPMENT OF QLASSIC

Table 2.0: List of QLASSIC equipment and their functions

Equipment Function a) Spirit Level To determine the vertically and evenness. Photo 1.3: Spirit level (1m) b) Tapping rod To identify the hollowness of wall, column, floor and tiles. Photo 1.4: Tapping rod

c) Measuring Tape To measure the length. Photo 1.5: Measuring tape (3.5m) d) Tapping Rod To check the paintwork above and under of door. Photo 1.6: Mirror e) L Square To measure the squareness.

Photo 1.7: L square

f) Plump Bob



Photo 1.8: Set of plumb bob

To determine the verticality.





Photo 1.9: Calliper

To measure the gap between the two opposite sides.

3.2.2 DEFECTS OF THE ARCHITECTURAL WORKS

3.2.2.1 IMPROPER FALL GRADIENT FOR TOILET FLOOR

For the toilet, the floors must have the proper gradient of fall to allow water to flow smoothly into the pipes and then to the manholes. As often happens, the inappropriate gradient will cause the water to flow back to the toilet and stagnant waste water may occur. For this situation, the solution is the floor must be constructed again.

3.2.2.2 CRACKS

a) Plaster

The plastering work is focused to the wall. It is a type of finishes which has functions for smoothing and covering the rough surface of concrete. It also helps to ease the painting work. The plaster used in the construction can be divided into two types, which are skim coat powder and plaster lime (in liquid form). To prevent excessive layers of plaster on the surface, the application must be done by the skilled workers. A thick layer of plaster can cause cracks on it. The best way to overcome this defect is by applying a thin layer of plaster which is enough to ensure it being covered.



Photo 2.0: Cracks on the wall surface.

b) Wall

The crack or break on the wall could be due to vandalism committed by employees. For them, everything they do is for entertainment that will not give any effect but in fact it can impair the quality of work. As the result, the cost to repair the damage is a loss to the contractor.



Photo 2.1: Damaged wall.

3.2.2.3 UNEVEN SURFACE

It is the commonest defects that happen in the construction works. The uneven surface will appear bad visually and can lead the building into the risks, it usually will be hacked down for repair process. This is to prevent the differences in dimension as stated in the construction drawings. The works must be monitored by the supervisor. The evenness of floor can be measured by using the spirit level.



Photo 2.2: Uneven surface at the wall angle.

3.2.2.4 HOLLOWNESS

a) Concrete wall and floor

The hollowness is produced when air is trapped in the concrete. One of the reasons that leads to the hollowness is the concrete was not vibrated or compacted completely. The hollow sound can be detected by using the special QLASSIC tool that is known as a tapping rod.



Photo 2.3: Honey comb on the concrete.

b) Tiles

The tiles are mostly used on the wall and floor. If the grout cement or mortar was not notched by trowel before tapping the tiles or the tiles was not tapped by the rubber mallet, the tiles and the grout cement cannot be jointed to each other. Then, it leads to the hollowness sound. The aesthetic value of the building depends on the quality of tiles installation because it can be determined whether it appears good or not visually.



Photo 2.4: Hollowness at the tiles joint.

3.2.2.5 EXCESSIVE CONCRETE

This situation may happen during pouring process of the concrete into the formwork. The concrete may flow out from the formwork. There are some reasons that lead to the leaking of the formworks such as the formwork was not installed in the correct way and the timber that was used to build the formwork were in bad conditions.



Photo 2.5: Dirtied wall surface with the excessive concrete.

3.2.2.6 FAILURE IN PAINT WORKS

Painting was done after the plaster dries completely. There are 3 layers of paint which must begin with the skim coat, the first coat of colour paint and finally a second layer of colour paint. Before starting the next coat, make sure the previous coat is dried thoroughly. If these steps are not being practiced, the probability of failure in painting is high. It will be cracked, peeled, blistered, chalked, fungi infected and so on. It is usually due to works by unskilled workers.




Photo 2.6: Uncompleted paint due to the bad conditions of surface.

3.2.2.7 NOT ACCORDING TO SPECIFICATIONS

Staircases

The stairs act as an escape route in case of any emergency in the building. The stairs has been designed to suit the types of building and its activities. In the construction, the stairs being constructed with the dimensions of treads too small compared with the biggest foot size of humans while the dimension of the rise being too high. The stairs that are not in accordance to the specifications like UBBL 1984 are not safe to be climbed. This is due to the potential of danger and risks.

Nosing of stair steps

A nosing tile is located at the end of each stair treads. The stair with the nosing is capable of providing safety during climbing of the stair due to its ability of gripping the shoes. The inappropriate material of nosing can cause the users to slip. The joint between the nozzle and treads of stair must also be taken in consideration to avoid any accidents and at the same time to provide a good quality work.




Photo 2.7: The suitable material of nosing (non-slip tile).

3.2.3THE LOW USAGE OF QLASSIC

3.2.3.1 FACTORS OF THE LOW USAGE OF QLASSIC

There are some factors which can give effects to the low usage of QLASSIC. It is as follows:

- Attitude of fly-by-night contractor
- Effect of Low Score
- Lack of Awareness

a) Attitude of fly-by-night contractor

Now, the construction sector is driving the great economy and has generated extensive job opportunities. The contractors whether government or private are expecting to double their profits in each of their projects. The quality of the construction is often overlooked by them because they consider it as the risky things.

b) Effect of low score

The score of QLASSIC that is given to the contractors will determine the quality of the project whether good or bad quality. On first usage of QLASSIC, it is usually they get the low scores. The contractors think too much and believe that low scores in the assessment of QLASSIC will leave a big impact to reputation of their company.

According to CIDB, (n.d), there are a few of factors which are contributed to the low scores. The factors as follows:

- Lack of time to complete the construction works.
- Underexposure of quality.
- Lack of skilled workers.
- Problems due to project management.
- Building design.

c) Lack of awareness

The lack of awareness is the main factor of not using QLASSIC. The awareness about the importance of understanding and knowledge of QLASSIC not only refers to the contractors but also to the buyers. They do not receive the clear disclosure. On behalf of the contractors, they are mostly unfamiliar with the assessment of QLASSIC. Besides that, the attitude of easy acceptance by the buyer also is the big problem which often happens in the society. They are not sensitive to their rights that they can be demand for the better house.

3.2.3.2 SOLUTIONS TO THE LOW USAGE OF QLASSIC

Every problem has the solution. The application of QLASSIC in the projects of construction can be improve by many ways. Some actions have been done and some will be done in the future. The solutions as the following:

- · Exposure of QLASSIC by medias
- Training and workshop
- QLASSIC as a requirement for the Certificate of Completion and Compliance (CCC)

a) Exposure of QLASSIC by medias

The medias especially media electronic are the best and fastest medium to publish the information of QLASSIC. Among the medias that can be use are internet, radio, television, magazines and more. There is much information on QLASSIC in the internet that can be searched and obtained by the parties in the field of construction or the public. CIDB has also taken the proactive action in developing the usage of QLASSIC by revealing it in their web which is known as CIDB Malaysia.



Figure 2.8: QLASSIC Press Conferences.

Source: currentbuzz.my (2015).

b) Training and workshops

CIDB has conducted various QLASSIC training to provide and expose more detailed information about QLASSIC (refer to Appendix G). They also support the efforts of the other companies which held the workshops for QLASSIC. These companies also contribute to the development of publicizing the QLASSIC. The training and workshops are effective because the participants can learn more closely and directly of the assessment that will be conducted.



Figure 2.9: Training and workshop participants.

Source: PMINT (2015).

c) QLASSIC as a requirement for the Certificate of Completion and Compliance (CCC)

Because of the awareness is still low among them, CIDB intends to make QLASSIC as the requirement element for those who want to get the Certificate of the Completion and Compliance (CCC) for their projects. The contractor must submit the CCC form together with accreditation from QLASSIC. This action is to ensure every project that gets the CCC are the projects that meets the standards and have the best quality of the works.

3.3 METHOD STATEMENT

3.3.1 ASSESSMENT METHOD OF QLASSIC

DIAGRAM/ APPENDIX		Photo 2.8: QLASSIC briefing.
METHOD	 During construction, the client is responsible to carry out the internal assessment. This assessment is the same as the final assessment. The comment of work quality is recorded by the client in the QLASSIC form and will be informed to the contractor by a memo or other methods of communication. 	 The purposes of this assessment are: To ensure the contractor conduct their works in the best quality. To help the contractor to get the higher score in the final assessment of QLASSIC.
OPERATION	Internal assessment of QLASSIC	
NO.	1.	






Photo 3.3: The democratization of the correct way to use the mirror.		
	- The contractor must correct all the defects and elements which have been assessed by the client.	- The client will assess again to ensure the contractor did the renovation and improvement to the quality of the construction works. - Continuous renovation works may happen if the works qualities not reach the client's standards and requirements.
	Renovation by the contractor	Second internal QLASSIC by the client
	5	.;

4.	Certificate of Practical	- After the client is satisfied the overall works has being	
	Completion (CPC)	completed, the project is handed over to the client and the contractor will be award CPC.	
		- The CPC is issued by the client.	
1	;		
S.	Application of	- Apply the QLASSIC from CIDB.	Refer to Appendix D for QLASSIC
	QLASSIC	- They will be charged RM 500 for each assessment.	form
		- The client must submit the QLASSIC form together with	
		the construction drawings.	
.9	Pre-QLASSIC	- At this stage, the assessment does not involve all of the	
		building works but only part of them.	
		- It also known as a sampling stage where the samples are	Refer to Appendix E for sampling
		selected by CIDB from the drawings.	guidelines of architectural works
		- The drawings are normally the architectural drawings.	
		- 30 samples are the sufficient amount for sampling	
		process. These 30 samples will be chosen randomly by the	
		assessor.	

	Figure 3.1: Checking the evenness of wall surface. Source: cidb.gov.my (2012).	
- The sampling process is carried out by the CIDB and the result will be not informed to the client or contractor (undisclosed assessment).	 The final assessment will be assessed by the assessor who was appointed by CIDB. The works that have been assessed and have been repaired will not be assess again. CIDB uses the principle of "Do Things Right the First Time and Every Time" to encourage the contractors. The score will be rewarded to project that applied the QLASSIC. 70% is a pass score of assessment. As the appreciation for using QLASSIC, the certificate also will be given and the score of quality obtained is written in that certificate (refer to Appendix G). 	
	Final QLASSIC	
	7.	

Figure 3.2: Checking the hollowness Figure 3.3: Checking the straightness of the angle for internal walls. Source: cidb.gov.my (2012). Source: cidb.gov.my (2012). for internal walls. - The incentive in the form of 1% of the preliminaries cost - Suspended to involve in any PMINT projects for 2 years. - Gives the incentive to the contractor as motivate and PMINT as the client takes the following actions to QLASSIC score. The actions as the following: - Penalty, cut 1% of preliminaries cost (RM). a) Score higher than 70% support to their works. b) Score less than 70% (RM).






3.3.2 METHOD OF CONSTRUCTION WORKS TO GET BETTER SCORE IN QLASSIC

3.3.2.1 FLOOR TILING

GOOD PRACTICES	- Lippage between two tiles are not more than 1mm.
MANPOWER	2 unskilled labour
PLANT/ EQUIPMENT	- Notched trowel
SEQUENTIAL/ DIAGRAM	Photo 3.4: Grooving the cement grout.
METHOD	- Spread the cement grout or adhesive to a small part of floor area Groove it to ensure the joints between the tiles and cement grout will align.
NO. OPERATION	Grooving the cement grout or an adhesive
NO.	Li


- Ton of tiles	skirting to be	level, neat and	consistent.	- Joints are	aligned	between tiles	and consistent	in size.
- 1 skilled	labour	- 2 unskilled	labour		·			
- Rubber	mallet	- Spirit level	- Measuring	tape				
			4				Photo 3.5: Skirting	Photo 3.6: Place the tiles into the position.
- Messure the height of	skirting	- Tap the tiles firmly onto	uniform position of skirting	and floor.	- Check the level of tiles.	- Use plastic spacer(2-3 mm)	at all joints.	
Tilina	Smire							
·	i							



- Consistent in colour tone of tiles and grout.	- No cracks, scratches, chips, stains and hollowness of tiles.
- 1 skilled labour - 2 unskilled labour	2 unskilled labour
- Soft trowel - Damp cloth/ sponge	Plywood
Photo 3.9: Grout between the opposite tiles.	Photo 4.0: Cover the floor by using the plywood.
 Spread the grout to fill the tiles joints completely. Remove the excess grout. Clean the tiles surface. 	- Prohibit the traffic on new tiles flooring after installation for at least 10 days Provide the cover during the construction period to avoid stain or damage.
Grouting	Protecting the tiles surface
e,	4.

3.3.2.2 DOOR INSTALLATION

GOOD PRACTICES	- Free from the corrosion, hollow and discolorations Frame corners are maintained at right angles Alignment and consistency in parallel, to be test and square Neat joints Good paintwork.
MANPOWER	- 1 skilled labour labour
PLANT/ EQUIPMENT	- Measuring tape - Level pegs - Spirit level - Datum
SEQUENTIAL/ DIAGRAM	Photo 4.1: Check gradient of the frame by using the spirit level.
METHOD	- Check the location and dimensions of frame as specified in the drawings Align the frame against the setting out lines Secure the temporary timber to support the frame Fasten the frame in position by using the galvanised straps Grout the gap between the wall and frame.
OPERATION	Installing the frame
NO.	.i



Donot is food	- railei is iree	from damage,	scratch and stain	mark.	- Consistent gap	between the panel	and frame.	- Neat joints.	- No noisy sound	and easy when	opening and	closing.	- Good paintwork,	including top and	bottom of panel.	- Smooth and	even surface.	
1	- I skilled	labour	- 3 unskilled	labour														
Mooniming	- Measuring	tape	- Electrical	screw driver														,
			TO THE PERSON OF		1		T: 2 7. I. 4-1 4 4	Figure 5.7: Installing the door.	Source: FIMILY (2013).							Photo 4.4: Hinges		
Charl the name from the	- Check the panel from the	drawings.	- Install the panel into the	position.	- Fasten the hinges to	connect the frame and panel.												
Installing the	mstannig me	door panel																
C																		

 3.	Installing the	- Fasten the lockset to the		- Electrical	- 1 skilled	- Well-designed
	lockset to door	panel.		screw driver	labour	lockset.
	panel.	- Check the correct type and			- 1 unskilled	- Lockset fit well.
		size used.	l'a		labour	- No sign of
	2	- Conduct a simple				corrosion, defect
		functional test of closing and				and discoloration
		opening the door.				in ironmongery.
			Photo 4.5: Fastening the lockset			
			of door.			

CHAPTER 4.0

CONCLUSION

4.1 CONCLUSION

Based on the study, there are two aspects that can be listed as the factors or causes of the low quality in construction works. These aspects cover all of:

- Defects occur on finishing works.
- Low usage of QLASSIC.

The results of application QLASSIC on the PB Sentral and KP Perdana sites showed that the works performed by the contractor can still be improved. The supervisor who was appointed by the contractor was not responsible enough. They do not monitor the works carried out by the workers whether based on the standards or not.

Safety is very important when conducting the QLASSIC at the site. But, during the internal assessment of QLASSIC, the assessor did not wear the personal protective equipment like safety helmet and safety boots. As the results, they are exposed to the danger which may come from the large machineries, sharp materials, dusty environment and so on.

The methods used by PMINT to encourage the usage of QLASSIC in their projects are the best ways. They gave the initiative to contractors that got the high score in QLASSIC and gave the penalty to contractors which got the low score. These good methods should be taken as an example by the other companies. The hopes for PMINT to continue introducing the QLASSIC to their new parties that will be involved in their projects and make it the requirement for those have been used the QLASSIC.

REFERENCES

1. Book

- CIDB Malaysia & Sime Darby. (n.d). Sharing of Good Practices towards
 Achieving High QLASSIC Score. Kuala Lumpur: CIDB Malaysia.
- Lembaga Pembangunan Industri Pembinaan Malaysia. (2006). Construction Industry Standard (CIS 7: 2006) – Quality Assessment System for Building Construction Works. Kuala Lumpur: CIDB.

2. Web Site- Organisational Author

- CIDB Malaysia. (2012). QLASSIC. Retrieved July 2, 2015, from http://www.cidb.gov.my/cidbv4/index.php?lang=en.
- Perbadanan Memajukan Iktisad Negeri Terengganu. (2012). Laman Web Perbadanan Memajukan Iktisad Negeri Terengganu. Retrieved July 2, 2015, from http://www.pmint.gov.my/v2/main.php?module=49.
- Ehsan Bina Sdn. Bhd. (2010). *Awards and Certificates*. Retrieved on September 25, 2015, from http://www.ehsanbina.com/award.html.

3. Online Article

- Terajui Shoppe. (2013). Apa yang anda perlu tahu tentang CCC. Retrieved October 1, 2015, from http://terajuiniagahomes.blogspot.my/2013/07/apa-yang-anda-perlu-tahu-tentang-ccc.html.
- Ayob Norizam & Marlinda Abdul Malek. (2013). Perception on Quality
 Assessment in Construction (QLASSIC) Implementation in Malaysia.
 Retrieved October 1, 2015, from
 http://www.researchgate.net/publication/262371706_Perception_on_Quality_
 Assessment_System_in_Construction_%28QLASSIC%29_Implementation_i
 n Malaysia.

4. Online Newspaper

- Khoo, G. (2015, March 30). Current Buzz. A Classic Approach to Quality.
 Retrieved May 27, 2015, from http://currentbuzz.my/Promotions/A-Classic-Approach-To-Quality.
- George, Tan. (2015, February 11). Borneo Post Online. CIDB To Make
 QLASSIC a Requirement. Retrieved November 2, 2015, from
 http://www.theborneopost.com/2015/02/11/cidb-to-make-qlassic-a-requirement/.
- Bernama. (2015, February 5). Daily Express. CIDB Encourages Industry
 Players To Participate in QLASSIC. Retrieved July 30, 2015,
 http://www.dailyexpress.com.my/news.cfm?NewsID=96945.
- Kavithah, R. (2014, November 11). The Malaysia Reserve. CIDB to Introduce QLASSIC at Construction Stage. Retrieved Jun 18, 2015, from http://themalaysianreserve.com/new/story/cidb-introduce-qlassicconstruction-stage.

APPENDIX

PERBADANAN MEMAJUKAN IKTISAD NEGERI TERENGGANU

CADANGAN MERANCANG, MEREKABENTUK, MEMBINA, MENYIAPKAN, MENGUJI, MENTAULIAH DAN MENYELENGGARA PUSAT REKREASI (10 LAPIS) YANG MENGANDUNGI 7 UNIT LOT KEDAI (1 LAPIS), PARKING BERTINGKAT (6 LAPIS) PUSAT BOWLING (1 LAPIS), CINEPLEX (2 LAPIS) SERTA KERJA – KERJA BERKAITAN DI ATAS LOT 4133 – LOT 4140, LOT 5035 – LOT 5038, DAN LOT 3068 – LOT 3071, DI ATAS JALAN TENGKU EMBONG FATIMAH, MUKIM BANDAR, KUALA TERENGGANU



MAKLUMAT PROJEK

NO KONTRAK : 1/2013

NILAI KONTRAK : RM 89,968,577.00

TARIKH SETUJU TERIMA : 9 JANUARI 2013

TARIKH MILIK TAPAK : 27 JANUARI 2013

TARIKH SIAP ASAL : 07 NOVEMBER 2015

TARIKH SIAP SEMASA : 11 APRIL 2016

Cadangan Merancang, Merekabentuk, Membina, Menyiapkan Menguji, Mentauliah Dan Menyelenggara Pusat Rekreasi (10 Lapis) Yang Mengandungi 7 Unit Lot kedai (1 Lapis), Parking Bertingkat (6 Lapis), Bowling (1 Lapis), Cineplex (2 Lapis) di atas Lot 4133-4140, Lot 5035-5038, Lot 4145 Dan Lot 3068-3071 Di Jalan Tengku Embong Fatimah.Mukim Bandar. Kuala Terengganu, Terengganu.

UNTUK PERBADANAN MEMAJUKAN IKTISAD NEGERI TERENGGANU

MAKLUMAT KONTRAK

NO KONTRAK

: 1/2013

NILAI KONTRAK

: RM 89,968,577.00

TARIKH SETUJU TERIMA

: 9 JANUARI 2013

No. Ruj

TARIKH MILIK TAPAK

: 27 JANUARI 2013

TARIKH SIAP ASAL

: 07 NOVEMBER 2015

TARIKH SIAP SEMASA

: 11 APRIL 2016 (EOT 1)

TEMPOH KONTRAK ASAL

: 145 MINGGU

TEMPOH KONTRAK (SEMASA)

: 167 MINGGU (EOT 1)

TEMPOH PENYELENGARAAN

: 2 THN, 3 BLN, 28 HARI

NO. PENDAFTARAN JKKP

: TG/13/03/1802

INSURAN

: CONTRACTOR'S ALL RISKS (CAR)

No. Polisi

: TECR-PC655604-BRTEKTG

Tempoh Insuran

: 27/01/2013 - 07/11/2015

Tempoh Selenggara

: 08/11/2015 - 21/02/2018

: WORKMEN COMPENSATION

No. Polisi

: TLWC-PC656660-BRTEKTG

Tempoh Insuran

: 27/01/2013 - 07/11/2015

Tempoh Selenggara


: 08/11/2015 - 21/02/2018

NO. PENDAFTARAN PERKESO : F8204528

Cadangan Merancang, Merekabentuk, Membina, Menyiapkan, Menguji. Mentauliah, Dan Menyelenggara Pusat Rekreasi (10 Lapis) Yang Mengandungi 7 Unit Lot kedai (1 Lapis), Parking Bertingkat (6 Lapis), Bowling (1 Lapis), Cineplex (2 Lapis) di Jalan Tengku Embong Fatimah, Kuala Terengganu.

UNTUK PERBADANAN MEMAJUKAN IKTISAD NEGERI TERENGGANU

PELAN LOKASI




Appendix B: Project information of KP Perdana Fasa 4A

AT AT A DO STEK	: Menbina & Menylapkan 10 Unit Rumah Berkembar 2 Tingkat
	Di Atas Lot PT1651-PT1660 Serta Kerja-Kerja Yang Berkaitan
	Di KP Perdana Mukim Kubang Parit Kuala Terenggau. (FASA 4A)
I HERRAKONTRAK	: RM 2,385,000.00
E TEMPO - KONTRAK	: 48 Minggu
# TIF « - MILIK TAPAK	: 02hb September 2014
E TER « - S AP KERJA ASAL	: 03hb Ogos 2015
- TAR - S AP KERJA (PINDAAN)	:
TEMPO-LIABILITY	: 24 BULAN
ECACATAN / LAD	
E DENDA KELEWATAN	: RM 1300/hari
F NO POUSI INSURANS	
CONTRACTOR ALL RISK)	: TERC-PD121404-BRTEKTG

: 05 % Dari Nilai kontrak

TO BON PELAKSANAAN



Appendix C: QLASSIC information

STANDARD INDUSTRI **PEMBINAAN**

(CONSTRUCTION INDUSTRY STANDARD)

CIS 7:2006

QUALITY ASSESSMENT SYSTEM FOR **BUILDING CONSTRUCTION WORK**

LEMBAGA PEMBANGUNAN INDUSTRI PEMBINAAN MALAYSIA



Lembaga Pembangunan Industri Pembinaan Malaysia

CONSTRUCTION INDUSTRY DEVELOPMENT BOARD MALAYSIA

Thu Pejabat CIDB, Tingkat 7, Grand Seasons Avenue, No 72, Jalan Pahang 53000 Kuala Lumpur P.O. Box. 12278, 50772 Kuala Lumpur

Source: CIS 7 (2006).

QUALITY ASSESSMENT SYSTEM FOR BUILDING CONSTRUCTION WORK

SECTION 1: GENERAL

1.1 Introduction

Quality Assessment System for Building Construction Work is an independent method to assess and evaluate the quality of workmanship of building projects based on this standard.

1.2 Normative references

The following normative reference is indispensable for the application of this construction industry standard. For dated reference, only the edition cited applies. For undated reference, the latest edition of the normative reference (including any amendments) applies.

Uniform Building By-Law 1984

1.3 Definition

For the purpose of this Construction Industry Standard the following definitions apply.

1.3.1 QLASSIC is the acronym for quality assessment system in construction.

1.3.2 Component

General building works are divided into four different components: structural, architectural, mechanical and electrical (M & E) and external works.

1.3.3 Elements

A sub-division of a component, for example formwork for structural works, tiled finishes for architectural works, drains for external works, surface conduits for mechanical and electrical (M & E) works and others.

1.3.4 Qualified person

A qualified person as defined in the Uniform Building By-Laws 1984.

1.3.5 Approved standards

Approved standard shall mean standard specified by the qualified person for the project.

1.4 Objectives of Quality Assessment System for Building Construction Work

Quality Assessment System for Building Construction Work was designed and developed to enable the user to achieve any of the following objectives:

- a) to benchmark the level of quality of the construction industry in Malaysia;
- to have a standard quality assessment system for quality of workmanship of building projects;
- to assess quality of workmanship of a building project based on the approved standards;

- d) to evaluate the performance of contractors based on quality of workmanship; and
- e) to compile data for statistical analysis.

1.5 Use of Quality Assessment System for Building Construction Work

Quality Assessment System for Building Construction Work is intended to complement the normal contractual drawings and specifications in a project. It is not intended to be used independently as working specifications. Unless specified in the building contract, qualified persons should not use Quality Assessment System for Building Construction Work to decide if the building or parts of the building project are in accordance with the relevant by-laws. It is still the responsibility of the qualified person to ensure that the quality of the construction works conforms to approved standards, practices, specifications and drawings.

1.6 Scope of Quality Assessment System for Building Construction Work

This standard sets out the quality of workmanship for the various aspects of the construction elements for the general building works. The Quality Assessment System for Building Construction Work cover four main components. Structural works, Architectural works, Mechanical and Electrical (M & E) works and External works. Assessments on the workmanship are carried out based on this standard and marks are awarded if the workmanship complies with the standards. These marks are then summed up to give a total quality score (%) for the building project.

However, the assessment excludes works such as piling, foundation and sub-structure works which are heavily equipment-based and called under separate contracts or sub contracts.

The building is assessed primarily on **workmanship standards** achieved through site inspection and field testing. The assessment is done throughout the construction process for structural and M & E works. For completed building projects the assessment is done for architectural, M & E fittings and external works.

Apart from site inspection, the assessment also includes field tests, test results on the material and the functional performance of selected services and installations. These tests help to safeguard the interest of building occupants in relation to safety, comfort and aesthetic; these defects may surface only after sometime.

1.7 Assessment approach

In general, the assessor determines the samples (elements or locations) to be assessed prior to each assessment. The samples are selected from drawings and plans. The selected samples shall be distributed as uniformly as possible throughout the project and construction stages. All locations are to be offered for the assessment.

The scoring will be done on the works that are inspected for the first time. Rectification and correction carried out after the assessment will not be re-scored. The objective of this practice is to encourage contractors towards "doings things right the first time and every time".

When an assessed item does not comply with the corresponding QLASSIC standards, it is considered failed and an "X" will be noted in the assessment form. Likewise a "v" is given for an item meeting the standards. A "-" will be given to indicate that the item is not applicable. The score is computed based on the number of "v" over the total number of items assessed.

SECTION 2: QUALITY STANDARD

2.1 Components to be assessed

The quality standards for building construction work are divided into four main components:-

a) Structural works

The structural integrity of the building is of paramount importance as the cost of failure and repairs are very significant. The assessment of structural works comprises:

- Site inspection of formwork, steel reinforcement, prefabricated or pre-cast elements, etc. during construction.
- ii) Laboratory testing of compressive strength of concrete and tensile strength of steel reinforcement.
- iii) Non-destructive testing of the uniformity and the cover of hardened concrete.

The quality standards for structural works are given in Annex A.

b) Architectural works

Architectural works deal mainly with the finishes. This is the part where the quality and standards of workmanship are most visible.

Architectural works are works such as floors, internal walls, ceiling, door and window, fixtures and fittings, external wall, roofs, driveway, porch and apron.

The quality standards for architectural works are given in Annex B.

c) Mechanical and Electrical (M & E) works

The quality of M & E works is important in view of its increasingly high cost proportion and its impact on the performance of a building. The assessment covers electrical works, air-conditioning and mechanical ventilation works (ACMV), fire protection works, sanitary and plumbing works, lifts, escalator and other basic M & E fittings.

The quality standards for M & E works are given in Annex C.

d) External works

External works cover the general external work elements in building construction such as the link-ways/shelters, drains, road works, car parks, footpaths, turfings, playgrounds, gates and fences, swimming pools, hardscapes and electrical substation.

The quality standards for external works are given in Annex D.

SECTION 3: ASSESSMENT

The assessment for building construction work is carried out through a sampling and statistical approach.

3.1 Weightage

The weightage for structural, architectural, M & E and external works are allocated in accordance to four categories of buildings. See Table 1 below.

Table 1. Allocation of weightage for components of building construction work according to building category

ght age syst em, whi ch

Components	Category A (Landed housing) Category B (Stratified housing)		Category C (Public building)	(Special public building)	
Structural works	25 %	30 %	30 %	30 %	
Architectural works	60 %	50 %	45%	35 %	
M & E works	5 %	10 %	15 %	25 %	
External works	10%	10 %	10 %	10 %	
Total score	100 %	100 %	100 %	100 %	

ed at making the score quantitative in representing the quality of workmanship of a building project. It has taken into consideration the distribution between the cost proportions of the four components in the various buildings and their aesthetic considerations.

The total quality score of a building project is the sum of marks awarded to the four components in each category of a building.

Each category of a building comprise as follow:

- i) Category A (Landed Housing) Detached, Semi-Detached, Terrace and Cluster House.
- ii) Category B (Stratified Housing) Flat, Apartment, Condominium, Service Apartment and Town House.
- Category C (Public Building) Office Building, Schools and other related facilities/ buildings built intended for public use.
- iv) Category D (Special Public Building) Hospitals and Airports only.

3.2 QLASSIC assessors

Assessors must attend the QLASSIC training course before being qualified to carry out the actual assessment at the construction sites. The QLASSIC assessors are continuously updated to ensure consistency and effective implementation of the assessment.

Appendix D: QLASSIC form Archa Finishes QLASSIC ASSESSMENT FORM No of Checks (b) No of Compl. Location Finishing Alignment & Evenness Crack & Damages Hollowness Jointing Finishing Alignment & Evenness Crack & Damages Hollowness Jointing Finishing Alignment & Evenness Ceiling Crack & Damages Roughness Jainting Joints & Gap Alingment & Evenness Material & Damages Functionality Accessories Defects Joints & Gap Alignment & Evenness WID Material & Damages Functionality Accessories Defects Assi 1 Joints & Gap Int. f Alignment & Evenness Material & Damages estudy Functionality Accessories Defects Joints & Gap M&E Alignment & Evenness E Fittings Material & Damages

Source: PMINT (2015).

Accessories Defects

PERBADANAN MEMAJUKAN IKTISAD NEGERI TERENGGANU

-			
	FAI		
_	10	ek	
•			

BORANG PENILAIAN QLASSIC/KECACATAN KERJA ARKITEK (KEMASAN DALAMAN)

PT LOT	LOKASI:	Tarikh pemeriksaan
		Pertama :
Nota:	(/) - siap (X) - perlu di baiki/bersih	Ke dua :
		V- ti

,				Ke tiga :		
)			Elemen	Standard QLASSIC/Kecacatan	Alatan/kaedah digunakan	Bacaan/penemuan di tapak/nota
1	Α	LA	NTAI	Standard Umum		
7		1	KEMASAN PEMASANGAN			
\dashv		Ť	Kesan kotoran		Visual	
+		-	Warna konsisten		Visual	
\dashv		1	VVailla Noticiototi		Viodai	
\dashv		2	ALIGNMENT&EVENNESS			
\neg		-	Kerataan permukaan	< 3mm per 1.2 m	spirit level	
7		+	Kecerunan betul ke floor trap	- onim por 1.2 m	& steel rule	
+		1	Varian panjang treads dan risers		a steer rate	***************************************
\dashv		-	tangga tak lebih 5mm dari dwg		measuring	
+		+	tangga tak lebih ommi dan dwg		tape	
\dashv		3	RETAK/ROSAK		tape	
\dashv		-	Kewujudan retak & rosak		Visual	
+		+	Newdjudaii i etak & i osak		Visual	
\dashv		4	Hollowness/Delaminatian			
+		1	Tiada "bunyi" hollow bila alat		Tapping rod	
\dashv		+	ujian digunakan		Tapping Tou	
-		-	Tiada tanda delaminatiaon		Visual	
\dashv		-	l lada tarida delaminatiado		Visual	
\dashv		5	Jointing			
+		-	Tebal skirting yang konsisten		Visual	
+		+-	Tiada gap antara dinding dgn		Visual	
			skirting		Spirit level	
\dashv		1	Bucu lurus dan seragam	< 3mm per 1.2m	& steel rule	
+		-	Ducu luius dali seragain	- 511111 per 1.2111	& Steel Tule	
+	В	1	Jubin Lantai (Floor Tiles)			
+		1	kemasan pemasangan			
\dashv		1	Joints seragam/satu lain dgn			and particular and another section of the section o
			skirting dan wall tiles		visual/caliper	
+		-	Joints seragam dgn/satu line saiz		Vibadirodiipoi	
			tile konsisten		Visual	
\dashv		-	konsisten dan kemas		Visual	
+		-	Lippage between two tiles	< 1mm	caliper	
\dashv		-	Lippage between two tiles	- 1111111	Caliper	
+	С	+	Timber Floor			
+		+	Menggelembung		Visual	
+		+	Timber strips to rest firmaly on		Visual	
			joists or screeds		Visual	
+		+	No visible gaps between timber		visual	
			strips		Visual	
+		-	Edges of the floor to properly		Visual	
			sealed		Visual	
-		1				
+						
+						1/10

Bil			Elemen	Standard QLASSIC/Kecacatan	Alatan/kaedah digunakan	Bacaan/penemuan di tapak/nota
2	Α		DINDING DALAMAN	Standard Umum		
		1	komasan nomasangan			
		+	kemasan pemasangan No stain mark		\ \(\tau_{i=1}^{n} \)	
		-	Consistent colour tone and good		Visual	
		-	Consistent colour tone and good		Visual	
		2	Crack and damage			
1					Vieus	
			No visible damage/defect		Visual	
-		3	Hollowness/delamination			
		3	No hollow sound	 	Tenning and	
-		-	No sign of delamination	 	Tapping rod	
\dashv			140 sign of detaillination		Visual	
		4	Alignment & Evenness			
			Evenness of surface	<3mm per 1.2 m	spirit level	
			Verticality of wall	<3mm per 1.2 m	& steel rule	
			Walls meets at right angle	<4mm per 1.2 m	L-Square	
			Edge to be straight and align	<3mm per 1.2 m	measuring	
		-			tape	
-	В	-	PLASTER FINISHES			
		1	Kemasan pemasangan			
			No visual crack		Visual	
_	С	_	TILES FINISHES			
-	-	1				
-		+	Kemasan pemasangan joints are align between tiles and			
			consistent size			
-		-			caliper/visual	
-		-	Consistent and neat marking	-4	Visual	
-		-	Lippage between 2 tiles	<1mm	Spirit level	
-	D	-	PAINTING		&steel rule	
-	D	1	FINISHES			
-		1	Surface are evenly painted		Viewel	
-			No patchiness from touch up		Visual	
-+		-	Surface free from fading, peeling		\/:1	
		-	blister, chalkiness		Visual	
+			blister, Charkiness		Visual	
\dashv	E		CEILING		 	
		1	FINISHING			
			No stain marks		Visual	
			consistent colour		Visual	
			No patchy surface		Visual	
		2	Alignment & Evenness			
_			Surface smooth not wavy		Visual	
_			Straightness of corners		Visual	
-		3	Crack & Damage			
-		3	Crack & Damages No visible damage, crack, leaks			
		\vdash	Hololo dalliage, orach, leaks			
		4	Roughness			
			No rough surface		Visual	
		5	Jointing			
			Konsisten, seragam & kemas		Visual	

			Elemen	Standard QLASSIC/Kecacatan	Alatan/kaedah digunakan	Bacaan/penemuan di tapak/nota
4	F	i I	PIASTER/SKIM COAT			<u> </u>
+		-	No pin holes,trowel marks		Visual	NAME OF THE PARTY
+		-	Formwork joints are smooth		Visual	
+			Painwork with no brush marks		Visual	
+			No gap between wall & ceiling		Visual	Market and the second of the s
1			No sign of corrosion		Visual	
1	G		DOOR			
		1	JOINT & GAP			
+		l:	Consistent gap between floor			
+			& bottom leaf	<5mm	caliper	
+			No visible gaps between door		- Campon	
+			neats joints		Visual	
+			Consisten gap between door		Visual	
+		-	leaf and frame	<5mm	caliper	
+			icar and frame	-011111	Campon	
		2	ALIGNMENT & EVENNESS			
			Parallel to with the wall		Visual	
1			Door frame squareness	ļ	Spirit level	
-			Double leaf doors to flush			
			each other		Visual	
-			Door leaf and frame corners			
+		-	maintained at right angles		L-Square	
+		3	MATERIAL & DAMAGES			
			No stain marks & damages		Visual	
			No sags, warps on door leaf	The second section of the second section is the second second second second second second second second second	Visual	
			Door joints and nail holes filled			
			up, properly sanded		Visual	
			Galzing clean and evenly sealed		Visual	
1			No sign of corrosion	-	Visual	
1			Good paintwork top & bottom		Visual	
+		4	FUNCTIONALITY			
+		-	Ease in opening/closing	tested 5 times	Physical	
+		-	No squeaky sound	tested 5 times	Physical	
\pm			Lockset should be functional	tested 20 times	Physical	
1		5	Accessories Defects			
+		5	Good fit and no stains		Visual	
+			No sign of corrosion		Visual	
-			No missing or defective		Visual	
\pm						
			VIII.			
+		_	2.2.2.2			
1				T		
			Control Services Control Contr	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		

T			Elemen	Standard	Alatan/kaedah	Bacaan/penemuan di
				QLASSIC/Kecacatan	digunakan	tapak/nota
	F		WINDOW			
		1	Joints and gap			
			Konsisten gap between window			
			leaf and frame	<5mm	caliper	
			No visible gap between window			
			frame and wall		visual	
			Neat joint between window frame			
			and wall internal/external		visual	
1						
1		2	ALIGNMENTS & EVENNESS			
+			Parallel with wall opening		visual	
+			Window frame square	The second section of the second section is a second section of the second section of the second section is a second section of the section o	visual	
+		\vdash	Window leaf corner at right		L-square	
+		\vdash	angle	<4mm per 300mm	&steel rule	
+		\vdash	arigie			
+		3	Material & damages			
+		3	No stain mark & visible		visual	
-					visual	
-			damage/defect		Visual	
_			Louvered window with glass		visual	
1			panel of correct length		Visual	
			Galzing clean and evenly sealed		ļ	
			with gasket for Al windows		visual	
			No sign of corrosion		visual	
			Good paintwork		visual	
1			TIMOTIONAL ITY			A CONTRACTOR OF THE RESIDENCE AND ADDRESS OF THE PARTY OF
_		4	FUNCTIONALITY		physical	
_			Ease of opening/closing		physical	
			No squeaky sound during		<u> </u>	
			opening/closing		physical	
		5	Accessories defect		<u> </u>	
			Lockset with good fit and aligned		visual	
			No sign of corrosion		visual	
1			No missing or defective		visual	
1	G	-	ROOF		<u></u>	
1		1	FINISHING	_	+	<u> </u>
			No stain marks		visual	+
1			good paintwork	<u> </u>	visual	
-		-	Dough/Unaver/Falls		+	
-		2	Rough/Uneven/Falls		visual	
_			Look smooth with no tool marks		visual	
			Even and no stripping			
_			Falls in right direction		visual	
+		3	Crack and damages	 	 	
-		3	No visible damage/crack		visual	
+		-	NO VISIBLE GALLIAGE/CLACK		13441	
+		4	Joint/sealant/alignment		 	
+		+-	Consistent joint width, neat/align		visual	
+		+	Consistent joint with, neartingin			1
+		5	Chockage/ponding	+	† -	T
-		1	No sign of ponding/leaking	+	visual	T
			140 digit of portaling/locating			†

Pon surfile property per	Elemen	Standard QLASSIC/Kecacatan	Alatan/kaedah digunakan	Bacaan/penemuan di tapak/nota
Surfile Pro Ope Ope Pro Ope	LAT ROOF			
Pro Ope pes Clea I PIT No No No Ope pes Cor Pro J WA Sho Cor Go No Cle No K GU No K GU No Cu RW GG Cu RO	Ponding less than 3mm		Steel rule	
I PIT No No No Good Pess Con Pro J WA Sho Con Good Roo Roo Roo Roo Roo Roo Roo Roo Roo	surface level to avoid protrusion		visual	
I PIT No No No Good Rood Pes Con Pro J WA Sho Con Good Rood Pro K GU No K GU RO	Proper dressing for any protrusion		visual	
I PIT No No Roo Good Pro J WA Sho Con Good Roo Con Pro K GU No No RW Gu Gu Gu RO	Opening to be sealed to prevent			
I PIT No No Roo Good Pro J WA Sho Con Good Roo Con Pro K GU No No RW Gu Gu Gu RO	pest invasion		visual	
I PIT No No No Gor Ror Ope pes Cor Pro J WA Shr Cor Gor No Cle No No K GU No RW Gu Gu	Clean and no stain marks		visual	
No No No No Roc Ope pes Cor Pro J WA Sho Cor No Cle No No K GU No RW Gu Gu Gu Gu RV Gu Gu Gu Gu RV	Slean and no stain marks		7,000	med tree to the same of the sa
J WA Sho Con No Cle No K GU No RW GO GO GO GO RO RO RO RO RO RO RO RO GO RO RO RO RO GO RO RO RO RO GO RO RO GO RO RO RO GO RO RO GO RO RO GO RO RO GO GO RO	PITCHED ROOF			
J WA Sho Con Roo Fro Sho Con Roo Roo Roo Roo Roo Roo Roo Roo Roo R	No leaking		visual	
J WA Sho Con Roo Pro J WA Sho Con Roo Roo Roo Roo Roo Roo Roo Roo Roo R	No rust or stains		visual	Marie 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
J WA Sho Con Goo No Cle No K GU No RW Gu Gu	Good painting to roof		visual	
J WA Sho Con Goo No Cle No K GU No RW	Roof tiles in alignment		visual	
J WA Sho Con Goo No Cle No K GU No RW Gu Gu	Opening to be sealed to prevent		Viodai	
J WA Sho Con Goo No Cle No K GU No RW Gu Gu			visual	
J WA Sho Con Goo No Cle No K GU No RW Gu	pest invasion			
J WA Sho Cor Go No Cle No No K GU No RW	Consisten colour tone	L	visual	
K GU No RW Gur	Proper dressing for any protrusion	<u></u>	visual	man of the contract of the con
K GU No RW Gur	WATERPROOFING (EXPOSED)			
K GU No RW			visual	
K GU No RW Gordan	Should be evenly installed			
K GU No No RW Gu	Complete adhesion to base		visual	
K GU No No RW Gu	Good laps at joint		visual	
K GU No No RW Gu	No leaking sign		visual	
K GU No No RW Gu	Clean and no mortar stains		visual	
No No RW Gu	No paint defects		visual	
No No RW Gu			-	
No RW Gu	GUTTERS AND RWDP		ļ ;	
RW Gu	No ponding and chockage		visual	
Gu	No cracks/other visible damages		visual	
	RWDP inlet lower		visual	
Cle	Gutter and RWDP covered		visual	
	Clean and no cement stains		visual	
	A CONTRACT OF THE PARTY OF THE			
			T	
	and the second s		† · · · · · ·	
			T	
	AND THE RESIDENCE OF SHAPE AND THE PROPERTY STREET, AND THE PROPERTY OF SHAPE AND ADDRESS OF	+		
		 		
			 	
			T	
			T	
			+	8 8 8 8
		+	+	-
		+		
			_	
			+	
			STREET, ST. MANAGEMENT	
			T	
				- 5/11

Bil			Elemen	Standard QLASSIC/Kecacatan	Alatan/kaedah digunakan	Bacaan/penemuan di tapak/nota
			EXTERNAL WALLS		in the latest and the	And the last has been been been been been been been bee
	A	\vdash	GENERAL REQUIREMENTS			
		1	KEKEMASAN	The second secon		
	-	1	No stain marks		visual	
	-	\vdash			visual	
			Consistent colour tone and good		visual	
			paintwork		- viouai	
		2	RETAK & ROSAK	The same of the sa		
	-	2	Kesan retak/rosak		visual	
	-	\vdash	Resali Tetalorosak			
	-	3	KEKASARAN (ROUGHNESS)			
	-		Berombak dan bertampal		visual	
			DOI OTTI DELL'ARTE DE			
	В	\vdash	KEMASAN JUBIN (TILE)			
	-	\vdash	Joint are align and consistent		caliper	
	-	\vdash	Consistent and neat marking		visual	
	1		Lippage between two tiles	<1mm	caliper	
			z.ppago source.			
	C		CAT			
			Permukaan dicat samarata		visual	
			Tone warna kerana touch up		visual	
			Kepudaran		visual	
	1		Permukaan gelupas,			
			gelembung dan lebihan kapur		visual	
	1					
	1					
		1				
					1	
					1	
						- 0.00
					+	
				4	+	_
					_	I compared to the compared to
					4	1
1	1		The same of the sa		1	1

Bil	Elemen		Elemen	Standard QLASSIC/Kecacatan	Alatan/kaedah digunakan	Bacaan/penemuan di tapak/nota
	1	T	APRON/PERIMETER DRAINS	hander skamt i Agaskandagat i kandensti iskuurtuurtuurtuu tuurtuu kuu kunki iskuuti iskuuti iskuu kii kiiski k	Applic Call (Amelia Neill Carl North C No.) Carl	5 See Grad. "Audio Sand and and and and class" Sand and a development when the abundanching and continued within
	A		GENERAL REQUIREMENTS			
		1	No stains marks		visual	
			damages/defect		visual	
		2	finishes must be even, level,		spirit level	
			align and consisten		measure tape	
		3	consisten joints witdh and neat		visual	
	В		PERIMETER DRAINS & APRON			
		1	DRAIN			
		-	Free flowing and no ponding		visual	
		2	DRAIN COVER			
			Level and no warp or rock		visual	
			Gap between drain cover	5-10mm wide	caliper	
			Gap between sides of drain	5-10mm wide	caliper	
		_	Drain grating proper painted		visual	
		3	APRON			
			No visible crack		visual	
			No water ponding		visual	
			Bitumen joints with neat edges			
			and sufficient length		visual	

Pemeriksa,		Wakil Tapak PMINT	
()	()
	Wakil Kontra	aktor	
	()	

Appendix E: Sampling for the architectural works

3.3 Sampling

As it is impractical to assess all elements in a building project, the assessment is carried out through a sampling approach. The sampling, which is based on the gross floor area (GFA) of the building and 10 m length section or per location for external work is to ensure that the assessment adequately represents the entire building project.

Architectural works assessment

Assessment of architectural works is carried out upon completion of the building project and before handing over of the project.

The weightage for architectural elements are allocated as per Table 2.

Table 2. Weightage for architectural element

	A valida atura I - I		ghtage %
Arch	itectural elements	Total	Breakdown
Internal Finishes		56	
	Floor		16
	Internal wall		16
	Ceiling		6
	Door		6
	Window		6
	Fixtures (Internal)		6
Roof		10	
External wall		10	
Apron and perimeter drain		4	
Material and Functional tests		20	
	Skim coat or Pre-packed plaster		3
	Field window water tightness test (WTT)		6
	Wet area water-tightness test		6
	Pull-off-test for internal wall tiles		5
Total		1	00

NOTE

A weightage of 3 % is automatically awarded to projects where skim coat or pre-packed plaster is used. This is to encourage the use of these products in the industry.

The assessment is based on the sampling guidelines. See Table 3.

Table 3. Sampling guidelines for architectural work

No.	Items	GFA per sample	Min Sample	Max Sample	Remarks
1a	Internal Finishes	70 m ²	30	700	For landed housing
1b	Internal Finishes	70 m ²	30	600	For stratified housing
10	Internal Finishes	500 m ²	30	150	For public building
1d	Internal Finishes	500 m ²	30	100	For special public building
2	External wall	-	50 %		50 % of the blocks/units
3	Skim coat and Pre- packed plaster	-	-	-	Declaration by qualified person
4	Roof	-	50 %		50 % of the blocks/units
5	Apron and perimeter drain	-	2	-	10 m length section per sample
6a	Field window water- tightness test (WTT)	1 000 m ²	20	100	Independent testing
6b	Field window water- tightness test (WTT)	-	25 %	-	Self-testing with declaration by qualified person
7a	Wet area water- tightness test	-	20	100	 10 % of all bathrooms and/or toilets (by location) all will be tested if < 20 nos.
7b	Wet area water- tightness test	-	100 %	-	- Self-testing with declaration by qualified person
8	Pull-off test for internal wall tiles	10 000 m ²	1 Set	5 Sets	5 tiles per set (by location)
NOTE	GFA means Gross Floor Are	a			

A location for **Internal Finishes** assessment is a functional space of a building such as a room, hall, toilet, kitchen, corridor or lobby. Locations are further categorised into three types:

- Principal locations are major functional places such as halls and rooms.
- Circulation locations include lift lobbies, corridors and staircases.
- Service locations are utility areas such as toilets, kitchens, balconies and yards.

The total number of locations will be distributed according to "Principal", "Circulation" and "Service" based on the percentage set out in the four categories of buildings in Table 4.

Scoring of internal finishes is based on the defects groups shown in Annex E 'Defects Group for Assessment of Architectural Works (Internal Finishes)'. In general, any item which is not available in a project will not be considered for scoring. For such case, the architectural score will be pro-rated accordingly.

Table 4. Weightage for location of architectural work according to building category

Locations	Category A (Landed Housing)	Category B (Stratified Housing)	Category C (Public Building)	Category D (Special Public Building)
Principal	40 %	40 %	60 %	60 %
Service	40 %	40 %	15 %	15 %
Circulation	20 %	20 %	25 %	25 %

An item under assessment will be considered failed if it does not meet the standards. In addition, any item found to be defective functionally such as evidence of water seepage in the window, slab, ceiling or roof, is considered to have failed the assessment. Likewise for a particular defect that is found excessive in an item (say excessive cracks on a wall).

For the assessment of external wall, a minimum 50 % of the total number of building will be assessed. For a building, the external wall will be divided into 4 walls for assessment.

Under the material & functional tests, self testing items like field window water-tightness test for 25 % of windows and the use of skim coat or pre-packed plaster for all plastering works are based on declaration by the project Qualified Person (QP). In general, declaration on passing for self-testing is based on first-time-right basis.

3.5 External works assessment

Assessment of external works is carried out upon completion of the building and before handing over of the project.

The assessment consists of the following locations:

a) Link-way/Shelter - 10 m length section per sample and minimum 2 samples:

b) External Drain - 10 m length section per sample and minimum 2 samples;

c) Roadwork and Car park - 10 m length section per sample and minimum 1 sample;

d) Footpaths and turfing - 10 m length section per sample and minimum 2 samples;

e) Playground - 1 location;f) Court - 1 location;

g) Fence and Gate - 10 m length section per sample and minimum 1 sample;

h) Swimming Pool - 10 m length section per sample and minimum 1 sample; and

i) Electrical substation - 1 locationj) Guard House - 1 location

k) Rubbish Chamber - 1 location





SIJIL QLASSIC

(Sistem Penilaian Kualiti Bagi Projek Pembinaan)

Tajuk Projek

CADANGAN PEMBANGUNAN PANGSAPURI SERVIS 27 TINGKAT YANG MENGANDUNGI 21 TINGKAT PANGSAPURI SERVIS (230 UNITS) 1 TINGKAT KEMUDAHAN REKREASI 4 TINGKAT BERSAMA 1 TINGKAT MEZZANINE TEMPAT LETAK KERETA ARAS TANAH 1 TINGKAT LOBI UTAMA (ARAS TANAH) DENGAN 2 TINGKAT TEMPAT LETAK KERETA BAWAH TANAH DIATAS LOT 124 JALAN CEYLON, SEKSYEN 57 KUALA LUMPUR.

- LAMAN CEYLON -

No. Permohonan:

Tarikh Penilaian:

WP-14 B0016 (P)

19 - 21 OGOS 2014

Pemaju/Pemilik :

Kontraktor (Utama) :

EMINENT ACE SON BHD

DIG-CAST CONSTRUCTION SDN BHD

No. Pendaftaran Syarikat :

No. Pendaftaran CIDB :

341126 - T


1971009-PH043738

Mata CCD : 20 MATA

Gred : G7

Skor QLASSIC :

69%



Lembaga Pembangunan Industri Pembinaan Malaysia




adalah seperti di mukasurat 2.

LAPORAN PENILAIAN OLASSIC



No. Permohonan : WP-14 B0016 (P) CADANGAN PEMBANGUNAN PANGSAPURI SERVIS 27 TINGKAT YANG MENGANDUNGI 21 TINGKAT PANGSAPURI SERVIS (230 UNITS) 1 TINGKAT KEMUDAHAN REKREASI 4 TINGKAT BERSAMA 1 TINGKAT MEZZANINE TEMPAT LETAK KERETA ARAS TANAH 1 TINGKAT LOBI UTAMA (ARAS TANAH) DENGAN 2 TINGKAT TEMPAT LETAK KERETA BAWAH TANAH DIATAS LOT 124 JALAN CEYLON, SEKSYEN 57 KUALA LUMPUR. LAMAN CEYLON Gross Floor Area (GFA): 22,407.00 m2 Nilai Kontrak Projek: RM 101,924,488.37 Kontraktor Utama: DIG-CAST CONSTRUCTION SDN BHD Pemaju / Pemilik: EMINENT ACE SDN BHD 52-3 & 52-4, JALAN METRO PUDU2 31 G-2 KELANA MALL JALAN SS6/12, KELANA JAYA FRASER BUSINESS PARK, OFF JALAN YEW 55100 KUALA LUMPUR 47301 PETALING JAYA SELANGOR No. Pendaftaran CIDB: 1971003-PH043738 Gred: G7 No. Pendaftaran Syarikat: 341126-T Pengurus Projek / Superintending Officer (SO): EN. TEE LIAN HOE ARKITEK KDI SDN BHD Arkitek HUSSIEN & KH CHONG JURUTERA PERUNDING (M) SDN BHD Jurutera Struktur NORMAN DISNEY & YOUNG SDN BHD Jurutera M & E Wakii Kontraktor/ Pemaju/ Pemilik: 1. EN. VINOTH A/L VARANAMUTHU Pegawai Penilai (assessor) 1, EN. MURALI SUNDARESON 2.EN. MOHD. NORAZMAN MOHD SAID Skop Penilaian: Tarikh Penilaian: 1. Architectural Works 19 - 21 OGOS 2014 2. External Works 3. Basic M&E Fittings Cuaca: BAIK Keterangan Penilaian: Sebanyak 320 sample telah di nilai. Hanya penilaian untuk Architectural Works, External Works dan Basic M&E Fittings sahaja dilakukan. Structural Works dan M&E Works tidak dinilai bagi maksud penilaian ini. Sampling dan penilaian adalah berdasarkan kepada Construction Industry Standard (CIS) 7:2006 Quality Assessment System For Building Construction Work yang dikeluarkan oleh CIDB. Peralatan yang digunakan semasa penilaian dijalankan adalah seperti berikut:a) Spirit Level (1.2 m length) b) Steel Measuring e) Tapping Rod f) Retractable Plum-bob Steel Measuring Tape (8m) f) Long Measuring Tape (30m) Digital Calliper L-square (24" X 12") g) Long Measurih) Steel Wedge Pecahan markah penilaian untuk Architectural Works, External Works dan Basic M&E Fittings bagi projek ini



Lembaga Pembangunan Industri Pembinaan Malaysia 1/2





No. Permohonan: WP-14 B0016 (P)

ITEM	ELEMENT	TOTAL WEIGHTAGE	BREAKDOWN WEIGHTAGE	SCORE (%)
A	ARCHITECTURAL WORKS	AND DESIGNATIONS OF THE PROPERTY OF THE PARTY OF THE PART		51.45
1	Internal Finishes	65.12		
1.1	Floor		18.61	12.41
1.2	Internal Wali		18.61	13.58
1.3	Ceiling		6.98	5.48
1.4	Door		6.98	4.39
1.5	Window		6.98	6.75
1.6	Fixtures (Internal)		6.98	5.84
2	Roof	11.63		2.33
3	External Wall	11.63		7.27
4	Apron & Perimeter Drain	4.65		1.86
5	Material & Functional Test	6.98		6.98
8	EXTERNAL WORKS	15.38		11.86
C	BASIC M&E FITTINGS	7.69	Harris San	5.98
QLASSI	SCORE (%)	lakerika katasi		69.29

Kesimpulan: OLASSIC SCORE: 69 %

Disemak/Disediakan oleh:	Disahkan oleh:
Tarikh: 25/5/14	Tarikh: 24/1/
Diluluskan oleh:	Taikit manifestati t
- 1 - 1 · ·	
Tarikh: 2 10 14	

Nota:


QLASSIC is a method to evaluate the quality of workmanship and finishes of building project against approved standard and the assessment is based on random sampling and statistical approach. CIDB Malaysia is not liable for reliance of this report for whatever purposes. The project architect and/or the project engineer at all time responsible for the quality of construction according to the approved practices, specifications and drawings.


(Rujuk Pengiraan Skor QLASSIC Di Lampiran I)



Lembaga Pembangunan Industri Pembinaan Malaysia 2/2

Appendix G: QLASSIC awareness programme





Appendix H: QLASSIC statistics

Perception on Quality Assessment System in Construction (QLASSIC) 75
Implementation in Malaysta

The findings are summaries as follows




Figure 1. Correspondence Perception Towards QLASSIC Implementation

It was found that 57.55% respondents agree that QLASSIC increases quality of work 34.33% agrees that QLASSIC will increase the value of products and 28.78% agrees that the procedures in QLASSIC are simple. Nevertheless, 42.45% agrees that QLASSIC will cause delay in the work activities and 28.06% agrees that QLASSIC will affect cost.

Incorporating results and findings deliberated in this study below are several discussions attain

- 1 There are still many companies in Selangor that have not implemented QLASSIC as Quality Assessment
- 2 The property developers and contractor workers perceived QLASSIC is able to.
 - 1 Increase the quality of work
 - ii. Increase the value of product

At the same time, it is also found that procedure in QLASSIC is simple to be adopted. On the contrary, their perceptions on QLASSIC are

- 1 QLASSIC is causing delay in construction activities
- 11 QLASSIC have effect on cost of production
- 3 The level of knowledge on QLASSIC depends on the level of the worker in the company's hierarchy. Worker at a higher level has higher QLASSIC knowledge compared to the worker at a lower level.
- 4 The property developers and contractor workers are willing to adopt QLASSIC as their Quality Assessment method at their workplaces if suitable motivation and incentives are provided.




SISTEM PENILAIAN KUALITI BAGI PROJEK PEMBINAAN




Statistik Penilaian QLASSIC Januari Hingga Disember 2012


Graf 1: Bilangan Penilaian QLASSIC dari Januari sehingga Disember 2012 Mengikut Negeri




Graf 3: Pecahan Penilaian QLASSIC Mengikut Kategori



Graf 5: Peratus Purata Skor QLASSIC Untuk Tahun 2012




Graf 2: Perbandingan Bilangan Penilaian QLASSIC Mengikut Tahun




Graf 4: Bilangan Penilaian QLASSIC Mengikut Jenis Projek





Graf 6: Peratus Purata Skor QLASSIC Mengikut Kategori untuk Tahun 2012




SISTEM PENILAIAN KUALITI BAGI PROJEK PEMBINAAN




Statistik Penilaian QLASSIC Januari Hingga Disember 2011


Graf 1: Bilangan Penilaian QLASSIC dari Januari sehingga Disember 2011 Mengikut Negeri




Graf 3: Pecahan Penilaian QLASSSIC Mengikut Kategori




Graf 5: Peratus Purata Skor QLASSIC untuk Tahun 2011




Graf 2: Perbandingan Bilangan Penilaian QLASSIC Mengikut Tahun



Graf 4: Bilangan Penilaian QLASSIC Mengikut Jenis Projek



Graf 6: Peratusan Purata Skor QLASSIC Mengikut Kategori untuk Tahun 2011



Graf 7: Projek yang Mendapat Skor Qlassic Tertinggi Tahun 2011

Bil.	Kontraktor Utama	Pemaju	Tajuk Projek	Skor (%)	
1	Bina Tegas Sdn. Bhd.	Archicentre Sdn. Bhd.	Cadangan Meroboh Sebuah Banglo 1 Tingkat Sediada dan Membina Semula Sebuah Banglo 2 Tingkat Beserta Kolam Renang di atas (Lot 216) No. 7 Jalan 11/8E, Seksyen 11, Bandar Petaling Jaya, Selangor Darul Ehsan untuk Dr. Tan Loke Mun dan Puan Chew May-Ann.	88	-
2	Makassar Sdn. Bhd.	Perumahan Kinrara Berhad	80 Unit Rumah Teres 2 Tingkat & Sebuah Pencawang Elektrik (Double Chamber), Fasa B39 & B40, Bandar Kinrara, Mukim Petaling, Daerah Petaling, Selangor Darul Ehsan untuk Tetuan Perumahan Kinrara Berhad.	84	
3	Bina Rezeki Sdn. Bhd.	Sime Darby Property Bhd	10 Unit Rumah Berkembar 2 Tingkat Beserta Attic di Fasa F9 di atas Sebahagian Lot 53663, Seksyen U8, Bukit Jelutong.	81	_
4	Lim Hoo Seng Construction Sdn. Bhd.	Puchong Gateway Development Sdn. Bhd.	Cadangan Pembangunan Komersil 60 Unit Pejabat dan 1 Unit Pencawang Elektrik (Double Chamber)di atas Sebahagian Lot 48733 (PT45266), Pusat Perniagaan Suria Puchong, Mukim Petaling, Daerah Petaling, Selangor.	81	

Graf 7: Projek yang Mendapat Skor Qlassic Tertinggi Tahun 2012

Graf	7: P	rojek yang Mendapat	t Skor Qlassic Tertinggi Ta	ahun 2012	
Bil.		Contraktor Utama	Pemaju	Tajuk Projek	Skor (%)
1		Coronation Estates Sdn Bhd	Yee Seng Heights Sdn Bhd	Cadangan Membina Sebuah Rumah Banglo 3 Tingkat Dengan Kolam Renang di atas Lot No. PT37223, Jalan Bayu 7, Bukit Gita Bayu, Serdang, Mukim Kajang, Daerah Hulu Langat, Selangor Darul Ehsan Untuk Tetuan Yee Seng Heights Sdn Bhd	88
2		Sunway Construction Sdn Bhd	Heritage Land Sdn Bhd	Sambungan Bangunan 25 Tingkat Si Sisi Kanan Mengandungi 9 Tingkat Pangsapuri Servis, 1 Tingkat Kemudahan Hotel, 9 Tingkat Hotel, 7 Tingkat Tempat Letak Kereta dan 1 Besmen Untuk Kemudahan Hotel, Tambahan Bilik Gymnasium di atas Tingkat 25 di Jalan Pinang, Kuala Lumpur Untuk Heritage Land Sdn Bhd	85
3		Selangor Industrial Corp. Sdn Bhd	Must Ehsan Development Sdn Bhd	Cadangan Pembangunan 70 Unit Rumah Teres Dua Tingkat (Parcel G) di atas Sebahagian Lot PT 8093, Mukim Bukit Raja, Seksyen U12, 40170 Shah Alam, Selangor Darul Ehsan (Cahaya Alam - Camelia 2)	83
4		Aik Bee Construction Sdn Bhd	Perumahan Kinrara Bhd	Proposed Construction and Completion of 4 Units Double Storey Detached House, Phase 7415A, Bandar Kinrara, Mukim and Daerah Petaling, Selangor Darul Ehsan	82
5		Aik Bee Construction Sdn Bhd	Perumahan Kinrara Bhd	Cadangan Pembangunan 25 Unit Rumah Banglo Dua Tingkat, Fasa 9A9(C) , Bandar Kinrara, Mukim Petaling, Daerah Petaling, Selangor Darul Ehsan Untuk Tetuan Perumahan Kinrara Berhad	81
)	Taki Engineering Sdn Bhd	Sunway City (Ipoh) Sdn Bhd	28 Unit Rumah Link 2 Tingkat (22' x 75') di Plot 5, Sebahagian Lot P.T 146131, Mukim Ulu Kinta, Ipoh, Perak Darul Ridzuan. (Garden Villa Phase 9)	80
	7	Kitacon Sdn Bhd	Sime Darby Poperty Berhad	Cadangan Membina 26 Unit Rumah Banglo Yang Mengandungi 15 Unit Rumah Banglo 2 Tingkat Beserta 1 Tingkat Separa Bawah Tanah Jenis A dan 11 Unit Rumah Banglo 2 Tingkat Beserta 1 Tingkat Separa Bawah Tanah dan Kolam Renang Jenis B, di Fasa J-7A, Seksyen U8, Bukit Jelutong, Shah Alam, Selangor Darul EhsanSDBJ26-	80
	8	PJD Construction Sdn Bhd	Bindev Sdn Bhd	Superstructure & External Work For Blok Pangsapuri Kos Sederhana 30 Tingkat (386 Unit) Dengan Podium Ruang Letak Kereta, Kolam Renang dan Kemudahan Awam (Fasa 8) For Cadangan Skim Perumahan di atas Lot 440,441,803 & 1578, Jalan Assumption Seksyen 4, Daerah Seberang Perai Utara, Pulau Pinang	80
_	9	Jurutama Sdn Bhd	Jelutong Development Sdn Bhd	The Construction and Superstructure Main Contract Works for The Proposed Mixed Development On Lot 171 (Lot C) at Persiaran KLCC, Kuala Lumpur City Centre, Kuala Lumpur for Arena Merdu Sdn Bhd	. 80
-	10	Daewoo Engineering Construction Co. Ltd		Cadangan Untuk Mendirikan Pemajuan di atas (Shore Front Development): Fasa 1, 1 Blok (A) 28 Tingkat Kondominium Termasuk 1 Tingkat Podium Tempat Letak Kereta dan 1 Tingakat Separa Besmen Tempat Letak Kereta (88 unit) di atas Lot 691, Seksyen 8, Bandar Georgetown, Pulau Pinang.	80

Appendix I: QLASSIC application by PMINT

PROGRAM PENINGKATAN KUALITI

Sistem Pengurusan Kualiti MS ISO 9001: 2008

Balan mempertingkatkan tahap kepuasan pelanggan terhadap penyampaian perkilidmatan. PMINT mendidik warga kerjanya supaya beratih pemikiran daripada budaya output dan perbelangan atau kesan nyata semata mata dan kini diterapkan pula dengan budaya yang mementingkan kebermasilar cara halistik Setiap perlaksimaan akan dikaji dan ditelitragar lebih berkesan dan dapat menyumbang semula secara maksimum, serta dapat mengelakkan danpada berlaku semuaziran Perbelanjaan atau peruntukan kerajaan datam membuyai sesebuah projek pembangunan disupakan secara berhemah, kena pada tempat, masa dan kerika serta dapat memperi kesan secara mempada pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat, masa dan kerika serta dapat memberi kesan secara memberiah pada tempat memberiah pada tempat memberiah pada tempat pada tempat memberiah pada tempat pada

itsteru, prosedur prosedur kerja yanu didokumenkan di dalam SPK ISO (901). 2008 dikaji dan ditambahbah agar sentiasa relevan dengan keperluan dan keriendak keriasa. Ia termisuklah menyingkirkan karenah biroktasi yang menjulajikan kecada birokrasi yang menjulajikan kecada birokrasi yang menjudah cara serta menyenangkan pelangan. Pengawasan secara berterusan melalui program Audit. Dataman secara berkala juga dilaksanakan agar perkhidmatan dipertingkatkan kualah dan keberkesanaannya bagi memastik ian sistem yang diguna pakai sentiasa relevan dengan kebendak senasia.



Bermula pada tahun 2012, Jabatan Ternik al Miliki terjah meniguinapakai Sistem Penilaian Kualith Dalam Pembinaan (QLASSK), yang merupakan satu sistem atau kaedah untuk mengukur dan mendalagual by a karkeransi en jauatu kerja penihanaan, berdasarkan kepadu kerja penihanaan, berdasarkan kepadu kepeduan standard yang berkenaan. Dengan QLASSIC (quadi nafi kastaman funation projek penibiniaan dapat dibuat perbandangan secara objektif melalui sistem pemarkahan yang ditetapkan oleh pahak CIDB Markah ditenikan jika elemen pembinaan tersebut menatuhi keperluan standard tersebut. Markah yang terkumpul akan digunakan untuk pengunan skor QLASSIC (%) bagi suatu pada kersahanaan tarakan QLASSIC (%) bagi suatu pada kersahanaan

Penilaian QLASSIC of the CIDB diffuat melalui penicriksaan tapak dan mengikut prinsip diat time inspections, Sebarang ketja penibinaan yang



diperbetulkan selepas suatu penilaian di alankan tidak akan dinilai semula

Objektif primap inradalah untuk menggalakkan kontraktor untuk Buat Kerja Dengan Betul Pada Kali Pertania Dar Buat Kerja Dengan Betul Setiap Kali

Untuk memastikan standard QLASSIC ini dipatuh dan dicapai pada setiap projek pembangunan hartanah PMIN Fisatu unti persuntau kualit dalaman PMIN I telah ditubuhkan dengan diketuas oleh seorang Pegawai Fenyelia Kualit Projek yang bertanggung awab menyelia semua projek pembangunan tiattanah PMINT Pegawai Penyelia yang dilantik aikan menyediakan padai lawatan persenksian kualiti secara berkati. Segata kecacatan yang dijumpai semasa lawatan pemeriksian kualiti akan dilaporkan kepada penyelia projek yang bertanggungjawab untuk dilambat tindakan pembalkan.

ANTARA PROJEK-PROJEK PERUMAHAN SOMERMAL DAN PERKEDAJAN PMINI PANG TELAH DIJALANK SUPENIL AJAM DI ASSIC PADA TAHUN 2013 ADALAH H



Source: pmint.gov.my (2012).

Appendix J: QLASSIC scores

BIL	PROJEK	TAHUN DI NILAI	MARKAH (%)
1	PERUMAHAN FASA 1 KP PERDANA	11/05/2010	58
2	PERUMAHAN FASA 1A KP PERDANA	12/07/2011	57
3	PERUMAHAN TERES FASA 3A KP PERDANA	14/03/2012	74
4	KEDAI BUKIT KECIL	13/03/2012	69
5	PANGSAPURI LADANG GEMILANG 2	17/04/2012	65
6	BENGKEL JAKAR 3	20/06/2012	71
7	PERUMAHAN KUALA BERANG	13/06/2012	62
8	KEDAI KG BATIN	28/05/2013	66
9	PANGSA KG DUYONG	21/05/2013	56
10	PERUMAHAN SEBERANG PAKA	15/07/2013	60
11	PERUMAHAN TERES FASA 3B KP PERDANA	17/07/2013	62
12	PERUMAHAN BINJAI RENDAH FASA 2	21/10/2013	57
13	PERUMAHAN GONG BADAK 8	23/10/2013	56
14	BENGKEL TELUK KALONG FASA 2	10/12/2013	59
15	PERUMAHAN KG CHABANG FASA 1	11/12/2013	62
16	BENGKEL CHENDERING	12/12/2013	62
17	BENGKEL TELOK KALONG FASA 1	14/12/2013	57
18	PERUMAHAN KP PERDANA FASA 4	12/12/2013	60
19	PERUMAHAN KP PERDANA FASA 5 b(i)		80
20	PERUMAHAN KP PERDANA FASA 5 b(ii)		80
21	PUSAT PAMERAN JALAN KEMAJUAN	07/04/2015	64

Source: PMINT (2015).



Top 5 QLASSIC Score out of 11 projects for Category B (Stratified Housing) as of 8/8/08				STREET, SQUARE STREET
RANKING	PROJECT TITLE	DEVELOPER/ PROJECT OWNER	MAIN	QLASSIC SCORE (%)
-	Cadangan Mendirikan 2 Blok Pangsapuri Kos Sederhana (Jumlah 448 unit) bersama kemudahan awam Rumah Kelas di atas Lot 64592 (PT 10271), USJ 1, Mukim Petaling, Daerah Petaling, Selangor	USJ ONE AVENUE SDN BHD	MODULAR CONSTRUCTION TECHNOLOGY SON BHD	71%
2	Proposed 1 Block 27 Storey (53 units) Condominium, 16 units 3 storey Semi- D, 2 units 3 storey Bungalow, 1 units 3 Storey Club House & 2 Levels Basement Car Park With Swimming Pool, Mukim Batu, Kuala Lumpur - Condominium Block	FLORA MURNI SDN BHD	EHSAN BINA SON BHD	%69
33	Cadangan Pembangunan Perumahan 220 Unit Pangsapuri Kos Sederhana 5, Tkt Fasa II, Pencawang TNB, Persiaran Casurina, Bandar Botanic, Klang Selangor	HARUM INTISARI SDN BHD	N.V BINA SDN BHD	%89
3	3 Biok Condo 35 Tgkt (Fasa 3) Mont' Kiara, Mukim Batu, KL	KIARAMAS DEVELOPMENT SDN BHD	SHIMIZU	%89
4	Cadangan Pembangunan Kediaman 2 Blok Pangsapuri 16 Tingkat mengandungi 326 unit pangsapuri, 1 unit Bangunan Serbaguna , 1 Unit Pondok Pengawal dan 1 unit Kolam Renang di atas Lot 1181 & 1182, Mukim Petaling, Daerah Petaling, Selangor. (Bukit Serdang) - Blok Pangsapuri	VILLAMAS SON BHD	TRIENTEL INDUSTRIES SON BHD	%59
interests adverging control to the control of the c	Cadangan Pembinaan 8 Blok Rumah Pangsa 5 Tingkat Kos Sederhana Rendah (310 unit), 4 Buah Kebuk Sampah dan Sebuah Pencawang Elektrik TNB di atas PTD 83511, Taman Desa Tebrau, Mukim Tebrau, Daerah Johor Bahru, Johor	PLENITUDE TEBRAU SON BHD	PEMBINAAN BINTANG BARU SDN BHD	%59

Source: ehsanbina.com (2010).

RANKING	PROJECT TITLE	DEVELOPER/ PROJECT OWNER	MAIN CONTRACTOR	QLASSIC SCORE (%)
1	Cadangan Pembangunan 24 unit rumah Berkembar 2 1/2 Tingkat (Jenis A&B) di RP 5 (Rasa 3B) Kofa Kemuning, Seksyen 31, Shah Alam, Selangor Daruf Ehsan untuk Tetuan Hicom Development Sdn 8hd	HICOM GAMUDA DEVELOPMENT SDN BHD	N.V BINA SON BHO	81%
/2	Cadangan Pembinaan Rumah Berbandung 42 Unit (Rumah Berbandung 2:1/2-Tingkat Sebanyak 26 Unit Jenis A, 4 Unit Jenis B dan 10 Unit Jenis C Juga Rumah Berbandung 2 Timgkat Sebanyak 2 Unit Jenis D) di Taman Dera Tebrau, Mukim Tebrau, Daerah Johor Bahru, Johor	PLENITUDE TEBRAU SDN. BHD.	PEMBINAAN KAMICON SON BHD	78%
3	Proposed 1 Block 27 Storey (53 units) Condominium, 16 units 3 storey Serni- D, 2 units 3 storey Bungalow, 1 units 3 Storey Club House & 2 Levels Basement Car Park With Swimming Pool, Mukim Batu, Kuala Lumpur - 3 Storey Semi-D	FLORA MURNI SON BHO	EHSAN BINA SDN BHD	77%
•	Cadangan Membina 150 unit Rumah Teres 2 Tingkat dan 1 unit Pencawang Elektrik di atas Lot PTD 117032, Fasa 2A, Mukim Tebrau, Daerah Johor Bahru	DYNASTY VIEW SDN BHD	TOTAL TEAMWORK SDN BHD	75%
4	Cadangan Membina Dan Menyiapkan Rumah 28 Unit Rumah Berkembar 2 Tingkat, Fasa 7A9(8), Bandar Kinrara, Puchong, Selangor Untuk Tetuan Perumahan Kinrara Berhad	PERUMAHAN KINRARA BHD	ALUNAN ASAS SON BHD	75%
5	Cadangan Pembangunan 132 unit Rumah Berkembar 1 tingkat dan 12 unit Rumah Berkembar 2 tingkat di Fasa 6A dan 2 unit rumah Teres 1 tingkat dan 2 unit Rumah Teres 2 tingkat di Fasa 6, Mukim Sg. Rasir, Daerah Kuala Muda, Kedah	PLENITUDE HEIGHTS SON BHD	RENTAS JAYA SDN. BHD.	74%
6	Cadangan pembangunan perumahan sesebuah 2 tingkat dan rumah berkembar 3 tingkat berjumlah 122 unit mengandungi 70 unit rumah berkembar 3 tingkat (40' x 80'), 52 unit rumah sesebuah 2 tingkat (60'x100'), 2 unit Pencawang Elektrik di atas Lot PT 938, PT 939, PT 941, PT 942, PT 943, PT 944, PT 945, Seksyen 13, Shah Alam, Selangor Darul Ehsan	TTDI HARTA SON BHD	MAKASSAR CONSTRUCTION SDN BHD	73%
6	Cadangan Pembangunan (Fasa 1682A) yang mengandungi 18 unit rumah berkembar 2 tgkat, Bandar Botanic	HARUM INTISARI SON BHD	TIMBUNAN BAKTI CONSTRUCTION SON BHD	73%
7	Cadangan Pembinaan Yang Mengandungi 32 unit Rumah Teres 1 1/2 tingkat Jenis A, 63 unit Rumah Teres 1 tingkat Jenis B, 78 unit Rumah Teres 1 1/2 tingkat Jenis C dan 87 unit Rumah Teres 1 tingkat Jenis D, di Fasa 3C5 Bandar Seri Alam, Mukim Plentong, Daerah Johor Bharu	SERI ALAM PROPERTIES SON BHD	KIMLUM SON BHD	70%
8	Cadangan Membina 105 unit Rumah Teres 2 1/2 tingkat di atas Lot 22883, mukim Dengkil, Daerah Sepang, Selangor Darul Ehsan	BUKIT HITAM DEVELOPMENT SON BHD	JASMURNI CONSTRUCTION SON BHD	69%



Source: ehsanbina.com (2010).

Daily Express - 15 Dec 2011 - Thursday



(From left) Eric Wong, Wong, Fong, Chan and Lam.

Firm rated among nation's 10 best

Sherell Ann Jeffrey

KOTA KINABALU: Wah Mie Group subsidiary, Wilakaya Sdn Bhd, was recently rated among

the top ten developers in Malaysia.

The Group through its recently completed Alam Damai Condominium was assessed under the stringent standards of the Quality Assessment System in Construction (QLAS-

SIC).
"The project was started in 2008 until 2011
"The project was started in 2008 until 2011 and only recently in July 2011 we received our

occupancy certificate (OC).
"In August 2011, we requested the Industry Malaysian Construction Development Board (CIDB) to come here to make an assessment on the quality audit of our building," said its Project Manager Wong Lin Chen here, Wednesday.

"We scored 70 per cent in the assessment, which places us well above the industry average of 65.11 per cent in the category B for

Stratified Housing projects.

"The ranking is based on cumulative yearly assessment since its inception in 2007 and benchmarked against other stratified housing projects assess in Malaysia.

"We currently rank seventh nationwide

and this is the first time in Sabah that we have

received this ranking," said Wong.
Meanwhile, its Executive Director, Fong Kin Vui added that the Group is committed to building quality homes for the nation.

"With this recognition, our customers will have more confidence in our products, in terms of quality of workmanship and architec-tural works, as this QLASSIC assessment is evi-

dence of the value of our products."

In addition, Fong said the Group was recently commended by the State government as a good corporate citizen in fulfilling their

corporate social responsibility.

We will have a few new project launching here and in Sandakan next year which can be viewed at www.wahmie.com," he said.

QLASSIC is a programme under the CIDB that measures and evaluates the quality of workmanship of a construction work based on the relevant approved standard.

It enables quality of workmanship between construction projects to be objectively com-

pared through a scoring system.

Also present were its General Manager Lam Kok Goon, Sales and Marketing Manager Eric Wong and Director Chan Ka Tsung.

Source: dailyexpress.com.my (2015).